

Description

The Traditional Paint Company Pozzolan Limewash is an external limewash made from pure filtered slaked lime with a pozzolanic additive modified with minimal linseed oil and synthetic polymer resin for increased adhesion and water shedding properties.

Ideal for application onto difficult surfaces, cement render, already painted surfaces etc as well as traditional lime render and wattle and daub. Gives traditional limewash finish across lime renders as well as difficult surfaces giving good breathability where needed as well as adhering to the modern surfaces and coatings. Pozilime has a slight textured finish due to the pozzolanic additive.

Colour & Finish

Available in stock colours & broad range of colours via tinting. Matt finish. Has a slight textured finish due to the pozzolanic additive.

Application

Brush (2 knot brush or good masonry brush)

Follow Application Guidelines sheet for full instructions.
Recommended 3 coat system. (Please read application guidelines)

Technical Data

- ▶ Specific Gravity: 1.2
- ▶ Drying Time: 4 hours at 20°C depending on airflow and humidity
- ▶ Overcoatable: 24 hours at 20°C

Coverage Rate

9m² per litre per coat (based on dilution rates and Application Guidelines sheet)

Thinner / Cleaner

Water

Shelf Life

6 months if stored in original unopened container at temperatures between 5 and 25°C.

Packaging

Available in 2.5, 5 and 10 Litres.

Information given is based upon formulations in use at time of printing. We reserve the right to modify any product without notice although in the case of any major modification a new data sheet will be issued.