

Description

The Traditional Paint Company Traditional Barn Paint is a traditional decorative and protective coating blended from a waterborne emulsified linseed oil. Suitable for used for plinths, barns, fences, sheds and all woodwork including windows and doors. Provides a water resistant, flexible coating, with high opacity, longevity and easy application. Traditional barn paint also offers good adhesion to suitably primed steel and aged concrete.

Colour & Finish

Available in stock colours & broad range of colours via tinting. Matt finish.

Application

Apply via brush (recommended) or medium pile roller.

Recommended 3 coat system, consisting of 1x priming coat, followed by 2x full coats.

Technical Data

- ▶ Water Resistant: 1 hour at 20°C
- ▶ Fully Dry: 3 - 7 days at 20°C depending on weather
- ▶ Overcoatable: 24 hours at 20°C

Coverage Rate

8m² per litre per coat.

Thinner / Cleaner

Water.

Shelf Life

12 months if stored in original unopened container at temperatures between 5 and 25°C.

Packaging

Available in 2.5, 5 and 10 Litres.

Safety Precautions

Application materials and soiled rags may self ignite without warning. Dispose of safely by laying flat and allowing to dry or clean with warm soapy water to avoid fire risks.

Information given is based upon formulations in use at time of printing. We reserve the right to modify any product without notice although in the case of any major modification a new data sheet will be issued.