

FLAG Bilge Paint



PRODUCT DATA

Description:

One coat system for all internal surfaces, giving good resistance to oil, grease, salt water and fresh water.

Area of use:

Bilges, lockers, engine compartments.

Substrates:

Wood, GRP and Steel and Concrete

Packing:

1 litre

Physical Constants:

Colour:	Off White
Finish:	Satin
Volume solids:	60%
Theoretical spreading rate:	10 –12 sq.metres per litre
Flash point:	38°C
Specific gravity:	1.3
Dry to touch:	4 – 6 hours
Overcoating time:	16 hours

****The theoretical spreading rate** has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants** are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Conventional spray Airless spray Roller
Thinner:	White Spirit
Cleaning of tools:	White Spirit

<u>Surface condition:</u>	The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.
----------------------------------	--

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.