



SAFETY DATA SHEET

Date of issue/Date of revision

: 6 June 2022

Version

: 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

Product code : 1.775.3900/E19K

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Industries Italia S.r.l., Via Comasina, 121, 20161 Milano, Italy Tel: +39 02 6404.1

PPG Industries (UK) Ltd., Needham Road, Stowmarket, Suffolk, IP14 2AD, UK Tel: +44 (0) 1449 773 338

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

National contact

PPG Industries (UK) Ltd.

Customer Services and Sales Group, Needham Road, Stowmarket, Suffolk, IP14 2AD

Tel: +44 (0) 1449 773993 Fax: +44 (0) 1449 771603

1.4 Emergency telephone number

Supplier

Company emergency telephone number : +39 02 6404.1 (0800-1700)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

STOT SE 3, H335

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms



Signal word

: Warning

Hazard statements

: **F**lammable liquid and vapour.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause respiratory irritation.
 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.

Response

: **C**ollect spillage.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.
P280, P210, P273, P391, P403 + P233, P501

Hazardous ingredients

: Hydrocarbons, C9, aromatics
 xylene

Supplemental label elements

: Contains N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide). May produce an allergic reaction.
 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
Hydrocarbons, C9, aromatics	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 64742-95-6	≥10 - <20	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304	[1] [2]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≥5.0 - ≤10	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1] [2]
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	≤0.30	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤0.30	Repr. 2, H361	[1]
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.30	Eye Irrit. 2, H319 Repr. 2, H361d (oral) Aquatic Chronic 3, H412	[1]
Hexanoic acid, 2-ethyl-, zinc salt, basic	REACH #: 01-2119979093-30 EC: 286-272-3 CAS: 85203-81-2	≤0.30	See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

Code : 1.775.3900/E19K	Date of issue/Date of revision : 6 June 2022
7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS	

SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard
 [2] Substance with a workplace exposure limit
 [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
 [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
 [5] Substance of equivalent concern
 [6] Additional disclosure due to company policy

This mixture contains $\geq 1\%$ of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
- Inhalation** : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 4: First aid measures

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
 carbon oxides
 sulfur oxides
 phosphorus oxides
 metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Code : 1.775.3900/E19K	Date of issue/Date of revision : 6 June 2022
7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS	

SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 441 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 220 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 552 mg/m ³ 15 minutes. STEL: 125 ppm 15 minutes. TWA: 441 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects	
Hydrocarbons, C9, aromatics	DNEL	Long term Inhalation	150 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	32 mg/m ³	General population	Systemic	
	DNEL	Long term Dermal	11 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Oral	11 mg/kg bw/day	General population	Systemic	
	xylene	DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic
		DNEL	Short term Inhalation	260 mg/m ³	General population	Local
		DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic
		DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic
		DNEL	Short term Inhalation	442 mg/m ³	Workers	Systemic
		DNEL	Long term Inhalation	221 mg/m ³	Workers	Local
		DNEL	Short term Inhalation	442 mg/m ³	Workers	Local
DNEL		Long term Dermal	212 mg/kg bw/day	Workers	Systemic	
trizinc bis(orthophosphate)	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic	
ethylbenzene	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	15 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic	

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 8: Exposure controls/personal protection

N,N'-ethane-1,2-diyIbis (12-hydroxyoctadecan- 1-amide)	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	293 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.83 mg/m ³	General population	Local
zinc oxide	DNEL	Long term Inhalation	3.35 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.5 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
propylidynetrimethanol	DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	1.68 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.68 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.79 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	5.03 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	19.54 mg/m ³	Workers	Systemic
	DNEL	Short term Oral	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	83.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	138.8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	925 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	3037.3 mg/m ³	Workers	Systemic
	Hexanoic acid, 2-ethyl-, zinc salt, basic	DNEL	Long term Oral	0.83 mg/kg bw/day	General population
DNEL		Long term Inhalation	2.5 mg/m ³	General population	Systemic
DNEL		Long term Dermal	3.21 mg/kg bw/day	General population	Systemic
DNEL		Long term Inhalation	5 mg/m ³	Workers	Systemic
DNEL		Long term Dermal	6.41 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
xylene	-	Fresh water	0.327 mg/l	-
	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
	-	Fresh water sediment	12.46 mg/kg dwt	-
	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
trizinc bis(orthophosphate)	-	Fresh water	20.6 µg/l	Sensitivity Distribution
	-	Marine water	6.1 µg/l	Sensitivity Distribution
	-	Sewage Treatment Plant	100 µg/l	Assessment Factors
	-	Fresh water sediment	117.8 mg/kg dwt	Sensitivity Distribution
	-	Marine water sediment	56.5 mg/kg dwt	Equilibrium Partitioning
	-	Soil	35.6 mg/kg dwt	Sensitivity Distribution
ethylbenzene	-	Fresh water	0.1 mg/l	Assessment Factors
	-	Marine water	0.01 mg/l	Assessment Factors
	-	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	-	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	-	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
zinc oxide	-	Secondary Poisoning	20 mg/kg	-
	-	Fresh water	20.6 µg/l	Sensitivity Distribution
	-	Marine water	6.1 µg/l	Sensitivity Distribution
	-	Fresh water sediment	117 mg/kg dwt	Sensitivity Distribution
	-	Sewage Treatment Plant	52 µg/l	Assessment Factors
	-	Marine water sediment	56.5 mg/kg dwt	Assessment Factors
-	Soil	35.6 mg/kg dwt	Sensitivity Distribution	

Code : 1.775.3900/E19K	Date of issue/Date of revision : 6 June 2022
7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS	

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves :  For prolonged or repeated handling, use the following type of gloves:

May be used: nitrile rubber

Recommended: Chloroprene, neoprene, natural rubber (latex), polyvinyl alcohol (PVA), Viton®

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
Colour : White.
Odour : Characteristic.
Odour threshold : Not available.
pH : Not applicable. insoluble in water.
Melting point/freezing point : May start to solidify at the following temperature: -43.77°C (-46.8°F) This is based on data for the following ingredient: 1,2,4-trimethylbenzene. Weighted average: -77.54°C (-107.6°F)
Initial boiling point and boiling range : >37.78°C
Flash point : Closed cup: 23°C
Evaporation rate : Highest known value: 0.84 (ethylbenzene) Weighted average: 0.78 compared with butyl acetate
Flammability (solid, gas) : liquid
Upper/lower flammability or explosive limits : Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light aromatic)
Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.3	1.2				

- Vapour density** : Highest known value: 4.1 (Air = 1) (1,2,4-trimethylbenzene). Weighted average: 3.8 (Air = 1)
Relative density : 1.39
Solubility(ies) : Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/ water : Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
xylene	432	809.6	

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).

- Viscosity** : Kinematic (room temperature): >400 mm²/s
 Kinematic (40°C): >21 mm²/s

- Viscosity** : 60 - 100 s (ISO 6mm)

- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

- Oxidising properties** : Product does not present an oxidizing hazard.

9.2 Other information

No additional information.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides phosphorus oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C9, aromatics	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat - Female	3492 mg/kg	-
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
trizinc bis(orthophosphate)	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
N,N'-ethane-1,2-diybis (12-hydroxyoctadecan-1-amide)	LC50 Inhalation Dusts and mists	Rat	>5.11 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
zinc oxide	LD50 Oral	Rat	>2000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
propylidynetrimethanol	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	10 g/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value
Dermal	16554.55 mg/kg
Inhalation (vapours)	95.62 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 11: Toxicological information

Conclusion/Summary

Skin : There are no data available on the mixture itself.
Eyes : There are no data available on the mixture itself.
Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself.
Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9, aromatics	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : May cause respiratory irritation.
Ingestion : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. Defatting to the skin.
Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
Ingestion : No specific data.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 11: Toxicological information

Skin contact : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9, aromatics	EC50 3.2 mg/l LC50 9.2 mg/l	Daphnia Fish	48 hours 96 hours
trizinc bis(orthophosphate)	Acute LC50 0.112 mg/l Chronic NOEC 0.026 mg/l	Fish Fish	96 hours 30 days
ethylbenzene	Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Daphnia Daphnia - Ceriodaphnia dubia	48 hours -
N,N'-ethane-1,2-diyIbis(12-hydroxyoctadecan-1-amide)	Acute EC50 29 to 43 mg/l Acute EC50 94 mg/l	Algae - Pseudokirchneriella subcapitata Daphnia - Daphnia magna	72 hours 48 hours
zinc oxide	Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - Daphnia magna - Neonate	72 hours 48 hours

Code : 1.775.3900/E19K **Date of issue/Date of revision** : 6 June 2022
7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 12: Ecological information

propylidynetrimethanol	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours
	Acute LC50 >1000 mg/l	Fish	96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9, aromatics ethylbenzene N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	75 % - Readily - 28 days	-	-
	-	79 % - Readily - 10 days	-	-
	-	63 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9, aromatics xylene ethylbenzene N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	-	-	Readily
	-	-	Readily
	-	-	Readily
	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	low
ethylbenzene	3.6	79.43	low
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	>6	-	high
propylidynetrimethanol	-0.47	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 13: Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 04 metallic packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(trizinc bis (orthophosphate), Solvent naphtha (petroleum), light aromatic)	Not applicable.

Additional information

ADR/RID : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.

Tunnel code : (D/E)

Code	: 1.775.3900/E19K	Date of issue/Date of revision	: 6 June 2022
7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS			

14. Transport information

- ADN** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.
- IMDG** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria


Category

P5c
E2

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

Code : 1.775.3900/E19K Date of issue/Date of revision : 6 June 2022
 7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS


SECTION 16: Other information

 Indicates information that has changed from previously issued version.


Abbreviations and acronyms

ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 PBT = Persistent, Bioaccumulative and Toxic
 vPvB = Very Persistent and Very Bioaccumulative
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 IMDG = International Maritime Dangerous Goods
 IATA = International Air Transport Association


Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
 Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

 H225 H226 H304 H312 H315 H317 H319 H332 H335 H336 H361 H361d H373 H400 H410 H411 H412 EUH066	Highly flammable liquid and vapour. Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
---	--

Full text of classifications [CLP/GHS]

 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Repr. 2 Skin Irrit. 2	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2
---	--

Code : 1.775.3900/E19K **Date of issue/Date of revision** : 6 June 2022
7-539 SELEMIX DIRECT BINDER GL 80% LIGHT COLORS

SECTION 16: Other information

Skin Sens. 1B STOT RE 2 STOT SE 3	SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
---	--

History

Date of issue/ Date of revision : 6 June 2022

Date of previous issue : 26 April 2022

Prepared by : EHS

Version : 14

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.