

Reviewed on: 30/06/2021 Printing date: 30/06/2021

	dentification of the substance/mixture and	l of the company
	ndertaking	
• 1.1 Product ide	ntifier	
• <i>Trade name:</i> PLATIN 4545		
Article number / 454500	Safety Data Sheet:	
	entified uses of the substance or mixture and uses advised ag e substance / the preparation I	ainst
<ul> <li>1.3 Details of the second secon</li></ul>	ne supplier of the safety data sheet upplier:	
Industriestrasse LI-9487 Gampri T +423 375 94 (	n-Bendern )0	
F +423 375 94 9	99	
Product safety of	<i>ion obtainable from:</i> lepartment. e-mail address: li-sdb@teknos.com	
<ul> <li>1.4 Emergency</li> </ul>	telephone number: ical Information Centre, CH-8032 Zürich Emergency telephor	ne: +41 (0)44 251 51 51 (International)
	lazards identification	
	n of the substance or mixture cording to Regulation (EC) No 1272/2008	
Void <ul> <li>2.2 Label eleme</li> </ul>	nts	
	ling to Regulation (EC) No 1272/2008	
<ul> <li>Hazard pictogra Void</li> </ul>	ms	
<ul> <li>Signal word</li> </ul>		
Void <ul> <li>Hazard stateme</li> </ul>	ata	
	ns 1,2-benzisothiazol-3(2H)-one. May produce an allergic	
reaction.	data sheet available on request.	
<ul> <li>2.3 Other hazai</li> </ul>		
	and vPvB assessment	
<ul> <li>PBT: Not applicable.</li> </ul>		
<ul> <li>vPvB:</li> </ul>		
Not applicable.		
SECTION 03: C	composition/information on ingredients	
	haracterization: Mixtures	
<ul> <li>Description: Mixture of subst</li> </ul>	ances listed below with nonhazardous additions.	
<ul> <li>Dangerous com</li> <li>CAS Number</li> </ul>	ponents:	%
108-01-0	2-dimethylaminoethanol	0,50- 1,00
	EC number: 203-542-8	0,00 1,00
	Record number 01-2119492298-24	
	🔗 Skin Corr. 1B - H314; 🚸 Flam. Liq.	
	3 - H226; 🚸 Acute Tox. 4 - H302, Acute	
	Tox. 4 - H312, Acute Tox. 4 - H332	
		(continued on page 2)



Reviewed on: 30/06/2021 Printing date: 30/06/2021

		(continued of page 1)
2634-33-5	<b>1,2-benzisothiazol-3(2H)-one</b> EC number: 220-120-9 � Eye Dam. 1 - H318;	0,0015- 0,50
	- H302, Skin Irrit. 2 - H315, Skin Sens. 1 - H317; 🚸 Aquatic Acute 1 - H400	
112-34-5	<b>2-(2-butoxyethoxy)ethanol</b> EC number: 203-961-6 Record number 01-2119475104-44	1,00- 5,00
111-76-2	<b>2-butoxyethanol</b> EC number: 203-905-0 Record number 01-2119475108-36	1,00- 5,00
	H312, Acute Tox. 4 - H332, Skin Irrit. 2 - H315, Eye Irrit. 2 - H319	
57-55-6	Propylene glycol           EC number: 200-338-0           Record number         01-2119456809-23	5,00- 10,00

## SECTION 04: First aid measures

• 4.1 Description of first aid measures

- After inhalation:
- Supply fresh air; consult doctor in case of complaints.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly. After eye contact:
- Rinse opened eye for several minutes under running water.
- After swallowing:
- Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
   5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- Protective equipment:
  - Mouth respiratory protective device.
- Do not inhale explosion gases or combustion gases.
- Additional information Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.



mg/m3

mg/m3

(continued on page 4)

ppm

ppm

#### 4059909

Reviewed on: 30/06/2021 Printing date: 30/06/2021

#### **PRODUCT: PLATIN 4545** (continued of page 2) SECTION 06: Accidental release measures · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. In case of seepage into the ground inform responsible authorities. Dilute with plenty of water. In case of gas release or seepage into the ground inform responsible authorities. Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. SECTION 07: Handling and storage • Handling: 7.1 Precautions for safe handling Open and handle receptacle with care. Use only in well ventilated areas. Information about fire - and explosion protection: Prevent impact and friction. • 7.2 Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by storerooms and receptacles: Store only in the original receptacle. Information about storage in one common storage facility: Not required. Further information about storage conditions: Protect from frost. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. SECTION 08: Exposure controls/personal protection 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 108-01-0 2-dimethylaminoethanol WEL Short-term value 22 mg/m3 6 ppm 7.4 Long-term value mg/m3 2 ppm 112-34-5 2-(2-butoxyethoxy)ethanol WEL

101.2

15

10

67.5

111-76-2

Short-term value

Long-term value

2-butoxyethanol



Reviewed on: 30/06/2021 Printing date: 30/06/2021

PRODUCT	: PLATIN 4545		/
WEL			(continued of page 3)
	Short-term value	246	mg/m3
		50	ppm
	Long-term value	123	mg/m3
	Long-term value	25	ppm
	Sk, BMGV	23	ppin
57-55-6	Propylene glyco	1	
WEL			
	Long-term value	474* 10**	mg/m3
	Ū	150*	ppm
	*total vapour and particula	tes **particulates	
<ul> <li>Ingredi</li> </ul>	ents with biological limit value		
111-76-2	2 2-butoxyethanol	l	
BMGV			
	240 mmol/mol creatinine		
	Medium: urine		
	Sampling time: post shift		
A alalitia	Parameter: butoxyacetic ac	cid	
	nal information: ts valid during the making were	e used as basis.	
Be sur <i>Respir</i> <i>device</i> <i>Protec</i> <i>prepar</i> <i>of diffu</i> Materia The se varies the glo Penetr The ex observ The de Therefi <i>Eye pr</i>	in case of insufficient ventilati tion of hands: The glove materi ation. Due to missing tests no ation/ the chemical mixture. Set sion and the degradation Impe- al of gloves lection of the suitable gloves of from manufacturer to manuface ve material can not be calcular ation time of glove material act break through time has to ed. termined penetration times ac	iratory protective device recommended. Us on. rial has to be impermeable and resistant to recommendation to the glove material can election of the glove material on considera- ervious gloves does not only depend on the material, but a sturer. As the product is a preparation of se ted in advance and has therefore to be che be found out by the manufacturer of the pr cording to EN 374 part III are not performe which corresponds to 50% of the penetration	the product/ the substance/ the be given for the product/ the tion of the penetration times, rates also on further marks of quality and everal substances, the resistance of ecked prior to the application. rotective gloves and has to be ed under practical conditions.
	109: Physical and ch		
	ition on basic physical and c	cnemical properties	
Appearanc			
	σ.		
Appearanc		Liquid	
Appearanc Form:		Liquid	
Appearanc		Liquid According to product specifica Characteristic Characteristic	

0 °C

(continued on page 5)

Change in condition

Melting point/freezing point:



Reviewed on: 30/06/2021 Printing date: 30/06/2021

### PRODUCT : PLATIN 4545

	(continued of page 4)
Initial boiling point and boiling range:	Undetermined.
Flash point:	> 100 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	at 20 °C 23,0000 mbar
Density:	1,0600 g/cm3
Solubility in / Miscibility with	
water:	Not determined.
Viscosity:	
	Not determined.
	at 23 °C 18 - 21 s DIN 4 mm
9.2 Other information	No further relevant information available.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity
- No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions
- No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials:
- No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

### • 11.1 Information on toxicological effects

- Acute toxicity
- LD/LC50 values relevant for classification:
- 108-01-0 2-dimethylaminoethanol

Oral, LD50: 2000 mg/kg (rat) Dermal, LD50: 1370 mg/kg (Rabbit) Inhalative, LC50/4h: 3,25 mg/l (mouse) Oral, LD50: 10000 mg/kg (rat) Oral, LD50: 5660 mg/kg (rat) Dermal, LD50: 4000 mg/kg (Rabbit) Oral, LD50: 1746 mg/kg (rat) Oral, LD50: 1414 mg/kg (guinea Pig) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 1000 mg/kg (Rabbit) Oral, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 20800 mg/kg (Rabbit) Oral, LD50: 5135 mg/kg (rat) Dermal, LD50: >19000 mg/kg (Rabbit)

7631-86-9	silicon dioxide, chemically prepared
112-34-5	2-(2-butoxyethoxy)ethanol
111-76-2	2-butoxyethanol
57-55-6	Propylene glycol
34590-94-8	Dipropylene glycol monomethyl ether

- Primary irritant effect:
- Skin corrosion/irritation
- No irritant effect.
- Serious eye damage/irritation



Reviewed on: 30/06/2021 Printing date: 30/06/2021

### **PRODUCT: PLATIN 4545** (continued of page 5) No irritating effect. Respiratory or skin sensitisation No sensitising effects known. Additional toxicological information: The product can cause deformations. The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. SECTION 12: Ecological information 12.1 Toxicity Aquatic toxicity: No further relevant information available. 12.2 Persistence and degradability No further relevant information available. Behaviour in environmental systems: 12.3 Bioaccumulative potential No further relevant information available. 12.4 Mobility in soil No further relevant information available. Additional ecological information: General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. 12.5 Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. 12.6 Other adverse effects No further relevant information available. SECTION 13: Disposal considerations · 13.1 Waste treatment methods . European and swiss waste code 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 wastes from MFSU and removal of paint and varnish 08 01 19 aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
   Decomposition:
- Recommendation:
- Disposal must be made according to official regulations.
- Recommended cleansing agents:
- Water, if necessary together with cleansing agents.

### SECTION 14: Transport information

• 14.1 UN-Number	
ADR	Void
IMDG	Void
ΙΑΤΑ	Void
• 14.2 UN proper shipping nam	е
ADR	Void



Reviewed on: 30/06/2021 Printing date: 30/06/2021

		(continued of page 6)
IMDG	Void	
ΙΑΤΑ	Void	
<ul> <li>14.3 Transport has ADR</li> </ul>	azard class(es)	
Class	Void	
IMDG		
Class	Void	
IATA		
Class	Void	
• 14.4 Packing gro	ир	
ADR	Void	
IMDG	Void	
ΙΑΤΑ	Void	
<ul> <li>14.5 Environmen Not applicable.</li> <li>14.7 Transport in Not applicable.</li> </ul>	tal hazards: bulk according to Annex II of MARPOL73/7	78 and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Technical instructions (air):

Class Share in %	
I	3,04
III	5,50

Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eve irritation. H332
- Harmful if inhaled. H400
  - Very toxic to aquatic life.

Department issuing MSDS:

Environment protection department.

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(continued on page 8)

# Page : 8 / 8 MATERIAL SAFETY DATA SHEET according to 1907/2006/EC, Article 31



4059909

Reviewed on: 30/06/2021 Printing date: 30/06/2021

	(continued of page 7
	(continued of page 7)
	ement international concernant le transport des marchandises dangereuses par chemin de fer
( U	ns Concerning the International Transport of Dangerous Goods by Rail)
IMDG: Inte	ernational Maritime Code for Dangerous Goods
IATA: Inte	rnational Air Transport Association
ICAO: Inte	rnational Civil Aviation Organisation
GHS: Glo	pally Harmonised System of Classification and Labelling of Chemicals
	European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances
	mical Abstracts Service (division of the American Chemical Society)
	al concentration. 50 percent
	al dose. 50 percent
	istent, Bioaccumulative and Toxic
	/ Persistent and very Bioaccumulative
	npared to the previous version altered.