

Reviewed on: 09/02/2022 Printing date: 09/02/2022

SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- Trade name: HYDROPUR 2K COLOR 7515
- Article number / Safety Data Sheet: 751500
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation Coating material
- 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Teknos AG Industriestrasse 7 LI-9487 Gamprin-Bendern T +423 375 94 00

- F +423 375 94 99
- Further information obtainable from:
- Product safety department. e-mail address: li-sdb@teknos.com 1.4 Emergency telephone number:
- Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 - H317 May cause an allergic skin reaction.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



- Signal word
- Warning
- Hazard-determining components of labelling: 1,2-benzisothiazol-3(2H)-one / 2-methyl-2H-isothiazol-3-one / reaction mass of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)
 Hazard statements H317 May cause an allergic skin reaction. EUH211 Warning! Hazardous respirable droplets may be formed when
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- Precautionary statements
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P321 Specific treatment (see on this label).
 P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.
 2.3 Other hazards
 Results of PBT and vPvB assessment
- PBT: Not applicable.



| | | (continued of page 1) |
|---|--|-----------------------|
| vPvB: Not applicable. | | |
| | | |
| | Composition/information on ingredients | |
| Description: | characterization: Mixtures | |
| Dangerous cor | nponents: | |
| CAS Number | 1.0 henriesthistel 2/01) ene | % |
| 2634-33-5 | 1,2-benzisothiazol-3(2H)-one EC number: 220-120-9 | 0,0015- 0,50 |
| | Eventime 220-120-9 Event and the event of the e | |
| | - H302, Skin Irrit. 2 - H315, Skin Sens. 1 - | |
| | H317; Aquatic Acute 1 - H400 | |
| 55965-84-9 | reaction mass of: 5-chloro-2-methyl-4- | 0,00-0,0015 |
| 55905-04-9 | isothiazolin-3-one [EC no. 247-500-7] and 2- | 0,00-0,0015 |
| | methyl-2H-isothiazol-3-one [EC no. 220-239- | |
| | 6] (3: 1) | |
| | 🐼 Skin Corr. 1C - H314, Eye Dam. 1 - | |
| | H318; 🚸 Acute Tox. 3 - H301, Acute Tox. | |
| | 2 - H310, Acute Tox. 2 - H330; 🚸 Skin | |
| | Sens. 1A - H317; 🔶 Aquatic Acute 1 - | |
| | H400, Aquatic Chronic 1 - H410 | |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 1,00- 5,00 |
| | EC number: 203-961-6 | , , |
| | Record number 01-2119475104-44 | |
| | 🕩 Eye Irrit. 2 - H319 | |
| 111-76-2 | 2-butoxyethanol | 1,00- 5,00 |
| | EC number: 203-905-0 | |
| | Record number 01-2119475108-36 | |
| | Acute Tox. 4 - H302, Acute Tox. 4 - | |
| | H312, Acute Tox. 4 - H332, Skin Irrit. 2 - | |
| | H315, Eye Irrit. 2 - H319 | 0.0015.0.50 |
| 2682-20-4 | 2-methyl-2H-isothiazol-3-one EC number: 220-239-6 | 0,0015- 0,50 |
| | Skin Corr. 1B - H314, Eye Dam. 1 - | |
| | H318; Acute Tox. 3 - H301, Acute Tox. | |
| | 3 - H311, Acute Tox. 2 - H330; 🚸 Skin | |
| | Sens. 1A - H317; 😵 Aquatic Acute 1 - | |
| | • | |
| 34590-94-8 | H400, Aquatic Chronic 1 - H410 Dipropylene glycol monomethyl ether | 0,0015- 0,50 |
| U7UJU-37"U | EC number: 252-104-2 | 0,0015-0,50 |
| | Record number 01-2119450011-60 | |
| | substance with a Community workplace | |
| | exposure limit. | |
| 13463-67-7 | titanium dioxide | 10,00- 25,00 |
| | EC number: 236-675-5 | |



(continued of page 2)

2983624

*

Reviewed on: 09/02/2022 Printing date: 09/02/2022

PRODUCT : HYDROPUR 2K COLOR 7515

🎸 Carc. 2 - H351

Additional information:

For the wording of the listed risk phrases refer to section 16.

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- After inhalation:
 - Supply fresh air and to be sure call for a doctor.
 - In case of unconsciousness place patient stably in side position for transportation.
 - After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.

- After eye contact:
- Rinse opened eye for several minutes under running water.
- After swallowing:
- Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device. Do not inhale explosion gases or combustion gases.
 Additional information
- Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

| • | 6.1 Personal precautions, protective equipment and emergency procedures |
|---|--|
| | Wear protective equipment. Keep unprotected persons away. |
| | Ensure adequate ventilation |
| • | 6.2 Environmental precautions: |
| | Do not allow product to reach sewage system or any water course. |
| | Inform respective authorities in case of seepage into water course or sewage system. |
| | In case of seepage into the ground inform responsible authorities. |
| | Dilute with plenty of water. |
| | In case of gas release or seepage into the ground inform responsible authorities. |
| | Do not allow to enter sewers/ surface or ground water. |
| • | 6.3 Methods and material for containment and cleaning up: |
| | Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). |
| | Dispose contaminated material as waste according to item 13. |
| • | 6.4 Reference to other sections |
| | See Section 7 for information on safe handling. |
| | See Section 8 for information on personal protection equipment. |
| | See Section 13 for disposal information. |
| | |



| CECTION 07. Handling and stars | (continued of page 3 |
|---|----------------------|
| SECTION 07: Handling and storage | |
| | |
| Handling: A Dressutiums for sofe boardling | |
| 7.1 Precautions for safe handling Open and handle receptacle with care. | |
| Prevent formation of aerosols. | |
| Information about fire - and explosion protection: | |
| Prevent impact and friction. | |
| | |
| 7.2 Conditions for safe storage, including any incompatibilities | |
| Storage: | |
| Requirements to be met by storerooms and receptacles: | |
| Store only in the original receptacle. | |
| Information about storage in one common storage facility: | |
| Not required. Further information about storage conditions: | |
| Protect from frost. | |
| Store in cool, dry conditions in well sealed receptacles. | |
| Protect from heat and direct sunlight. | |
| 7.3 Specific end use(s) | |
| No further relevant information available. | |
| | |
| | |
| SECTION 08: Exposure controls/personal protection | n |


| 112-34-5 | 2-(2-butoxyethox | y)ethanol | |
|--------------------------|----------------------------|---------------------|------|
| WEL | | | |
| Short | t-term value | 101.2 | mg/m |
| | | 15 | ppn |
| Long | -term value | 67.5 | mg/m |
| | | 10 | ppn |
| 111-76-2 | 2-butoxyethanol | | |
| WEL | | | |
| Short | t-term value | 246 | mg/m |
| | | 50 | ppn |
| Long | -term value | 123 | mg/m |
| | | 25 | ppn |
| Sk, B | MGV | | |
| 34590-94-8 WEL | Dipropylene glyc | ol monomethyl ether | |
| Long | -term value | 308 | mg/m |
| | | 50 | ppn |
| Sk | | | |
| 0 | th biological limit values | | |
| 111-76-2 | 2-butoxyethanol | | |
| BMGV | | | |
| - | nmol/mol creatinine | | |
| | um: urine | | |
| - | oling time: post shift | | |
| Parar Additional info | meter: butoxyacetic ac | d | |
| | during the making were | used as basis. | |
| 8.2 Exposure | controls | | |
| | | | |



| | (continued of page 4) |
|--|---|
| Personal protective equipment: | (continued of page 4) |
| General protective and hygienic measures: | |
| The usual precautionary measures are to be adhered to when handling chemicals. Immediately remove all soiled and contaminated clothing | |
| Do not inhale gases / fumes / aerosols | |
| Do not inhale dust / smoke / mist. | |
| Avoid contact with the eyes and skin. | |
| Do not eat or drink while working. | |
| Be sure to clean skin thoroughly after Bespiratory protection: In case of brief | work and before breaks. f exposure or low pollution use respiratory filter device. In case of intensive |
| or longer exposure use self-contained | respiratory protective device. Suitable respiratory protective device |
| recommended. Use suitable respirator | y protective device in case of insufficient ventilation. |
| Protection of hands: The glove materia | al has to be impermeable and resistant to the product/ the substance/ the |
| | ecommendation to the glove material can be given for the product/ the |
| of diffusion and the degradation Protect | ection of the glove material on consideration of the penetration times, rates stive gloves Impervious gloves |
| Material of gloves | |
| The selection of the suitable gloves do | es not only depend on the material, but also on further marks of quality and |
| varies from manufacturer to manufactu | urer. As the product is a preparation of several substances, the resistance o |
| Penetration time of glove material | ed in advance and has therefore to be checked prior to the application. |
| | e found out by the manufacturer of the protective gloves and has to be |
| observed. | |
| The determined penetration times acc | ording to EN 374 part III are not performed under practical conditions. |
| The second se | de la la companya de la FOO/ estable en executive d'accelle de service en de d |
| Therefore a maximum wearing time, w | hich corresponds to 50% of the penetration time, is recommended. |
| Therefore a maximum wearing time, wEye protection: Safety glassesBody protection: Protective work cloth. | |
| Therefore a maximum wearing time, wEye protection: Safety glasses | |
| Therefore a maximum wearing time, w Eye protection: Safety glasses Body protection: Protective work cloth. | ing |
| Therefore a maximum wearing time, w Eye protection: Safety glasses Body protection: Protective work cloth. | ing |
| Therefore a maximum wearing time, w Eye protection: Safety glasses Body protection: Protective work cloth. | emical properties |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth <u>SECTION 09:</u> Physical and che | emical properties |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch | emical properties |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance | emical properties |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work clother SECTION 09: Physical and choose 9.1 Information on basic physical and choose Appearance Appearance: | emical properties |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work clother SECTION 09: Physical and chr 9.1 Information on basic physical and chr Appearance Appearance: Form: | emical properties |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work clother SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance Appearance: Form: Colour: | emical properties Liquid According to product specifica |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance Appearance: Form: Colour: Odour: Odour threshold: | emical properties Liquid According to product specifica Characteristic Characteristic Not determined. |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance Appearance: Form: Colour: Odour: | emical properties Liquid According to product specifica Characteristic Characteristic Not determined. |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance Appearance: Form: Colour: Odour: Odour: Odour threshold: pH-value: Change in condition | emical properties tiquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch 9.1 Information on basic physical and ch 4.1 4.1 5.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 | emical properties Eliquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 0 °C |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work clother SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance Appearance: Form: Colour: Odour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: | emical properties tiquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 0 °C Undetermined. |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance Appearance: Form: Colour: Odour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: | ing emical properties Liquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 0 °C Undetermined. Not applicable. |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch Appearance Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability (solid, gas): | ing emical properties Liquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 0 °C Undetermined. Not applicable. Not applicable. |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch 9.1 Infor | ing emical properties Liquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 0 °C Undetermined. Not applicable. Undetermined. |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and cf Appearance Appearance: Form: Colour: Odour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability (solid, gas): Ignition temperature: Decomposition temperature: | ing emical properties Liquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 0 °C Undetermined. Not applicable. Undetermined. Not applicable. Undetermined. Not determined. |
| Therefore a maximum wearing time, w • Eye protection: Safety glasses • Body protection: Protective work cloth SECTION 09: Physical and ch 9.1 Information on basic physical and ch 9.1 Informatic physical and ch | ing emical properties Liquid According to product specifica Characteristic Characteristic Not determined. at 20 °C 7,5 - 8,0 0 °C Undetermined. Not applicable. Undetermined. |

| Explosive properties: | Not determined. |
|----------------------------------|-----------------------|
| Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Vapour pressure: | at 20 °C 23,0000 mbar |
| Density: | 1,2100 g/cm3 |
| Solubility in / Miscibility with | |
| water: | Not determined. |
| Viscosity: | |
| | Not determined. |
| | (continued on page 6) |





- Aquatic toxicity:
- No further relevant information available. 12.2 Persistence and degradability
- No further relevant information available. Behaviour in environmental systems:
- 12.3 Bioaccumulative potential
- No further relevant information available.
- 12.4 Mobility in soil



Reviewed on: 09/02/2022 Printing date: 09/02/2022

PRODUCT : HYDROPUR 2K COLOR 7515

No further relevant information available.

(continued of page 6)

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- 12.5 Results of PBT and vPvB assessment
- PBT:
- Not applicable.
- vPvB:
- Not applicable. 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

European and swiss waste code

08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 wastes from MFSU and removal of paint and varnish 08 01 19 aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

Uncleaned packaging:
Recommendation:

- Disposal must be made according to official regulations.
- Recommended cleansing agents:

Water, if necessary together with cleansing agents.

SECTION 14: Transport information

| • 14.1 UN-Number | |
|---|------|
| ADR | Void |
| IMDG | Void |
| ΙΑΤΑ | Void |
| • 14.2 UN proper shipping name | е |
| ADR | Void |
| IMDG | Void |
| ΙΑΤΑ | Void |
| 14.3 Transport hazard class(e ADR | s) |
| Class | Void |
| IMDG | |
| Class | Void |
| ΙΑΤΑ | |
| Class | Void |
| 14.4 Packing group | |
| ADR | Void |
| IMDG | Void |
| ΙΑΤΑ | Void |
| • 14.5 Environmental hazards: | |

Not applicable.

• 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

(continued on page 8)



(continued of page 7)

2983624

Beviewed on: 09/02/2022 Printing date: 09/02/2022

PRODUCT: HYDROPUR 2K COLOR 7515

- Transport/Additional information: Not applicable.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II
- None of the ingredients is listed. • REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- None of the ingredients is listed. Annex II - REPORTABLE EXPLOSIVES PRECURSORS
- None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

- Technical instructions (air): • Class Share in %
- 1,62
- Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

- 15.2 Chemical safety assessment:
- A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life. H410
- Very toxic to aquatic life with long lasting effects.
- Department issuing MSDS:

Environment protection department. Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association ICAO: International Civil Aviation Organisation GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

(continued on page 9)

*

Page : 9 / 9 MATERIAL SAFETY DATA SHEET according to 1907/2006/EC, Article 31



2983624

| PRODUCT : | HYDROPUR 2K COLOR 7515 | |
|---|---|-----------------------|
| LC50: Leth LD50: Leth PBT: Pers vPvB: very | nical Abstracts Service (division of the American Chemical Society) al concentration, 50 percent al dose, 50 percent stent, Bioaccumulative and Toxic Persistent and very Bioaccumulative pared to the previous version altered. | (continued of page 8) |