

Date of last issue: -Revision Date: 02.03.2021 Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sika MonoTop-3020

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS		EHS@uk.sika.com

1.4 Emergency telephone number

+44 (0)1707 363899 (available during office hours).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 Serious eye damage, Category 1 Specific target organ toxicity - single exposure, Category 3, Respiratory system H315: Causes skin irritation. H318: Causes serious eye damage. H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)				
Hazard pictograms	:	E Z		
Signal word		Danger	•	
Hazard statements	:	H315 H318 H335	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.	
Precautionary statements	:	P101 P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.	



Date of last issue: -Revision Date: 02.03.2021 Version 1.0

Prevention:	
P271	Use only outdoors or in a well-ventilated ar- ea.
P280	Wear protective gloves/ eye protection/ face protection.
Response:	
P305 + P351 +	 P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove con- tact lenses, if present and easy to do. Con- tinue rinsing. Immediately call a POISON CENTER/ doctor.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

Cement (chromium reduced)

2.3 Other hazards

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006. The product reacts highly alkaline with water.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

oomponenta			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		· · · ·
Cement (chromium reduced)	65997-15-1	Skin Irrit. 2; H315	>= 20 - < 25
	266-043-4	Eye Dam. 1; H318	
		STOT SE 3; H335	
		(Respiratory system)	
Substances with a workplace expo	sure limit :		
calcium carbonate	471-34-1		>= 25 - < 40
	207-439-9		
	01-2119486795-18-		
	XXXX		
Quartz (SiO2)	14808-60-7		>= 20 - < 25
	238-878-4		



Date of last issue: -Revision Date: 02.03.2021 Version 1.0

Limestone	1317-65-3	>= 2,5 - < 5
Contains:	215-279-6	
Quartz (SiO2) <5µm >= 0,1 %		
Fumes, silica	69012-64-2	>= 1 - < 2,5
	273-761-1	
	01-2119486866-17-	
	XXXX	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms	and e	ffects, both acute and delayed
Symptoms	:	Cough Respiratory disorder Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	:	irritant effects Causes skin irritation.
		Causes serious eye damage. May cause respiratory irritation.
Country GB 10000026776		3/



Date of last issue: -Revision Date: 02.03.2021 Version 1.0

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media :	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from the Hazardous combustion prod- : ucts		substance or mixture No hazardous combustion products are known
5.3 Advice for firefighters Special protective equipment for firefighters Further information :	:	In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective Personal precautions :	e equipment and emergency procedures Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
6.2 Environmental precautions Environmental precautions :	Try to prevent the material from entering drains or water courses.
6.3 Methods and material for contai Methods for cleaning up :	nment and cleaning up Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.
6.4 Reference to other sections	

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see
, a nee en eare namaing		



Date of last issue: - Revision Date: 02.03.2021	Version 1.0	Print Date 02.03
	section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be pro plication area. Follow standard hygiene measures when h products	
Advice on protection against : fire and explosion	Avoid dust formation. Provide appropriate of at places where dust is formed.	exhaust ventilation
Hygiene measures :	Handle in accordance with good industrial practice. When using do not eat or drink. W smoke. Wash hands before breaks and at	Vhen using do not
7.2 Conditions for safe storage, in	cluding any incompatibilities	
Requirements for storage : areas and containers	Keep container tightly closed in a dry and v place. Store in accordance with local regul	
Further information on stor- : age stability	Keep in a dry place. No decomposition if stored and applied as	directed.
7.3 Specific end use(s)		

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m3	GB EH40
	dust and inha will be collect the methods pling and gra aerosols., Th health include in air equal to dust or 4 mg. any dust will above these WELs and ex limits., Most i sizes. The be after entry int sponse that if HSE distingu termed 'inhala the fraction o	nation: For the purpo- nation: For the purpo- nation of the sourd of any kind we or greater than 10 r m-3 8-hour TWA of r be subject to COSHI levels. Some dusts h sposure to these must ndustrial dusts conta- the human respira- telicits, depend on the ishes two size fractionation able' and 'respirable' f airborne material the ing and is therefore	fractions of airbor a undertaken in ac 4/4 General meth respirable, thoracia of a substance ha when present at a c ng.m-3 8-hour TW respirable dust. Th H if people are exp ave been assigne at comply with the in particles of a w and fate of any pa tory system, and t ne nature and size ons for limit-setting ., Inhalable dust a nat enters the nose	ne dust which cordance with ods for sam- c and inhalable zardous to concentration /A of inhalable nis means that oosed to dust d specific appropriate ide range of rticular particle he body re- of the particle. I purposes pproximates to and mouth



Date of last issue: -Revision Date: 02.03.2021

Quartz (SiO2)	penetrates to tions and exp dusts contain the relevant li short-term ex	act. Respirable dust the gas exchange r lanatory material are components that ha mits should be com posure limit is listed e limit should be use TWA (Respirable dust) TWA (Respirable	egion of the lung e given in MDHS ave their own ass plied with., Where , a figure three tir	. Fuller defini- 14/4., Where igned WEL, all e no specific	
	Further inform genetic dama	fraction) nation: Capable of c	(Silica) ausing cancer an	d/or heritable	
Cement (chromium reduced)	65997-15-1	TWA (inhalable dust)	10 mg/m3	GB EH40	
		TWA (Respirable dust)	4 mg/m3	GB EH40	
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m3	GB EH40	
	the methods of pling and grav aerosols., The health include in air equal to dust or 4 mg.1 any dust will b above these I WELs and ex limits., Most in sizes. The be after entry into sponse that it HSE distingui termed 'inhala the fraction of during breath respiratory tra penetrates to tions and exp dusts contain the relevant li short-term ex	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be used.			
Fumes, silica	69012-64-2	TWA (Respirable dust) TWA (inhalable	4 mg/m3 6 mg/m3	GB EH40 GB EH40	
	Further inform dust and inha will be collect	ation: For the purpo lable dust are those ed when sampling is described in MDHS1	(Silica) oses of these limi fractions of airbo s undertaken in a	ts, respirable orne dust which ccordance with	



Date of last issue: -Revision Date: 02.03.2021

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

general dust value

Form of exposure	Value type	Control parameters	Basis	
Inhalable	TWA	10 mg/m3	GB EH40	
Respirable fraction	TWA	4 mg/m3	GB EH40	

8.2 Exposure controls

Eye protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water	
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. 	
	Recommended: Butyl rubber/nitrile rubber gloves. Contaminated gloves should be removed.	
Skin and body protection	: Dust impervious protective suit Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.	
	7	14

Date of last issue: -



Revision Date: 02.03.2021 Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. particulate filter P P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. **Environmental exposure controls** General advice : Try to prevent the material from entering drains or water courses.

Version 1.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour Threshold	· · · ·	solid powder grey odourless No data available
рН	:	> 11 Concentration: 500 g/l
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	No data available
Density	:	No data available
Bulk density	:	ca. 1.300 kg/m3 (20 °C)



Date of last issue: -Revision Date: 02.03.2021 Version 1.0

Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature		No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data availa	ole
--------------------------------------	-----

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Date of last issue: -Revision Date: 02.03.2021 Version 1.0

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation Not classified based on available information.

Germ cell mutagenicity Not classified based on available information.

Carcinogenicity Not classified based on available information.

Reproductive toxicity Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential No data available

12.4 Mobility in soil

No data available

Country GB 10000026776

Print Date 02.03.2021

Date of last issue: -	
Revision Date: 02.03.2021	

Version 1.0

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Ρ	r	ο	d	u	С	t:	

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or minir wherever possible. Empty containers or liners may retain some product This material and its container must be disposed of way. Dispose of surplus and non-recyclable products via waste disposal contractor. Disposal of this product, solutions and any by-produ at all times comply with the requirements of environ protection and waste disposal legislation and any re local authority requirements. Avoid dispersal of spilled material and runoff and co soil, waterways, drains and sewers.	t residues. in a safe a licensed ucts should mental egional
European Waste Catalogue	17 01 06* mixtures of, or separate fractions of cond bricks, tiles and ceramics containing dangerous sub	
Contaminated packaging	15 01 10* packaging containing residues of or conta by dangerous substances	aminated

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sika MonoTop-3020

Print Date 02.03.2021

Date of last issue: -Revision Date: 02.03.2021 Version 1.0

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

	REACH - Restrictions on the man the market and use of certain dan preparations and articles (Annex 2	gerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Cement (chromium reduced) (Number on list 47)
	International Chemical Weapons Schedules of Toxic Chemicals an		:	Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			:	Not applicable
	REACH - Candidate List of Subst	ances of Very High	:	None of the components are listed
	Concern for Authorisation (Article			(=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)			:	Not applicable
		:	Not applicable	
	Regulation (EC) No 850/2004 on lutants	persistent organic pol-	:	Not applicable
	REACH Information:	All substances contained	əd i	n our Products are
		- registered by our upst	trea	am suppliers, and/or
		- registered by us, and/		
 excluded from the reg 				
		- exempted from the re	gisi	tration.
			ent	t and of the Council on the control of ma-
	jor-accident hazards involving dar	Not applicable		

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties



Date of last issue: -Revision Date: 02.03.2021 Version 1.0

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:
 Environmental Protection Act 1990 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)
 May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

This product contains cement. Wet cement or mortar may cause alkali burns if in direct and/or prolonged contact with the skin. Wear protective clothing at all times when working with cement based products.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H335	May cause respiratory irritation.	
Full text of other abbreviatio		
Eye Dam.	Serious eye damage	
Skin Irrit.	Skin irritation	
STOT SE	Specific target organ toxicity - single exposure	
GB EH40	UK. EH40 WEL - Workplace Exposure Limits	
GB EH40 / TWA	Long-term exposure limit (8-hour TWA reference period	
ADR	European Agreement concerning the International Carri	lage of
	Dangerous Goods by Road	
CAS	Chemical Abstracts Service	
DNEL	Derived no-effect level	
EC50	Half maximal effective concentration	
GHS	Globally Harmonized System	
IATA	International Air Transport Association	
IMDG	International Maritime Code for Dangerous Goods	- 4
LD50	Median lethal dosis (the amount of a material, given all once, which causes the death of 50% (one half) of a gro test animals)	
LC50	Median lethal concentration (concentrations of the chen	nical in
	air that kills 50% of the test animals during the observat period)	ion
MARPOL	International Convention for the Prevention of Pollution Ships, 1973 as modified by the Protocol of 1978	from
OEL	Occupational Exposure Limit	
PBT	Persistent, bioaccumulative and toxic	
PNEC	Predicted no effect concentration	
REACH	Regulation (EC) No 1907/2006 of the European Parliam	nent

Country GB 10000026776



Date of last issue: - Revision Date: 02.03.2021		Version 1.0	Print Date 02.03.202	
SVHC vPvB	istration, E cals (REA : Substance	and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative		
Further information				
Classification of the mi	Classification of the mixture:		Classification procedure:	
	11045			

		•
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN