



SAFETY DATA SHEET

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

Product number 515/Q113/ACT - FOR RED

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier TEAL & MACKRILL LIMITED
LOCKWOOD STREET
HULL
HU2 0HN
+44(0)1482 320194(T)
+44(0)1482 219266(F)
info@teamac.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 20979

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) -

Human health The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

Physicochemical When handled correctly, undamaged units represent no danger.

2.2. Label elements

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED**Hazard pictograms****Signal word**

Danger

Hazard statements

H312+H332 Harmful in contact with skin or if inhaled.
 H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing vapour/ spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

XYLENE, 2-METHYLPROPAN-1-OL

Supplementary precautionary statements

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

XYLENE		30-40%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-xxxx
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		Classification (67/548/EEC or 1999/45/EC) Xn;R20/21,R65. Xi;R36/37/38. R10.

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

2-METHYLPROPAN-1-OL		5-10%
CAS number: 78-83-1	EC number: 201-148-0	REACH registration number: 01-2119484609-23-XXXX
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information	Get medical attention promptly if symptoms occur after washing.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Toxic gases or vapours.
-------------------------	-------------------------

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water.
---	---

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours. Avoid spilling. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep containers upright.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

2-METHYLPROPAN-1-OL

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

WEL = Workplace Exposure Limit

XYLENE (CAS: 1330-20-7)

DNEL

Consumer - Oral; Long term systemic effects: 1.6 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³
 Industry - Dermal; Long term systemic effects: 180 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 77 mg/m³
 Industry - Inhalation; Short term local effects: 289 mg/m³

PNEC

- Fresh water; 0.327 mg/l
 - marine water; 0.327 mg/l
 - Intermittent release; 0.327 mg/l
 - Sediment (Freshwater); 12.46 mg/kg
 - Sediment (Marinewater); 12.46 mg/kg
 - Soil; 2.31 mg/kg
 - STP; 6.58 mg/kg

2-METHYLPROPAN-1-OL (CAS: 78-83-1)

DNEL

Workers - Inhalation; Long term local effects: 310 mg/m³
 Consumer - Inhalation; Short term local effects: 55 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Unprotected persons should be kept away from treated areas.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Viton rubber (fluoro rubber). Thickness: > 0.2 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. or Polyvinyl alcohol (PVA). Thickness: 0.2 - 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 240 mins. or Polyethylene. Thickness: > 0.062 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
Respiratory protection	Respiratory protection may be required if excessive airborne contamination occurs. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Amber.
Odour	Amine.
Odour threshold	Not determined.
pH	Technically not feasible.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	25°C Closed cup.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.1 (xylene) g/100 g Upper flammable/explosive limit: 7.0 (xylene) g/100 g
Other flammability	Not determined.
Vapour pressure	Not determined.
Vapour density	heavier than air
Relative density	1.0 - 1.4 @ 20°C
Solubility(ies)	Insoluble in water
Partition coefficient	Not determined.
Auto-ignition temperature	270 (xylene)°C
Decomposition Temperature	Not determined.
Viscosity	1.0 - 3.0 (cone and Plate) P @ 25°C
Explosive properties	Not determined.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.

9.2. Other information

Volatile organic compound	EU: (cat A/j): 500 g/l 2010. This product contains a maximum VOC content of 500 g/l.
----------------------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not occur

10.4. Conditions to avoid

Conditions to avoid Not known.

10.5. Incompatible materials

Materials to avoid Strong acids. Alkalis - inorganic. Amines. Mercaptans (thiols).

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

General information No specific health hazards known.

Inhalation May cause respiratory system irritation.

Ingestion Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritating to eyes.

Acute and chronic health hazards May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.

Route of exposure Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

XYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,523.0

Species Rat

ATE oral (mg/kg) 3,523.0

Acute toxicity - dermal

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

Serious eye damage/irritation

Serious eye damage/irritation Severely irritating to skin. Irritation of eyes is assumed. No testing is needed.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility This substance has no evidence of toxicity to reproduction.

Aspiration hazard

Aspiration hazard Kinematic viscosity <= 20.5 mm²/s.

Inhalation Harmful by inhalation.

Ingestion Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact Harmful in contact with skin.

Eye contact May cause severe eye irritation.

Target organs Central nervous system Liver

2-METHYLPROPAN-1-OL**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2,830.0

Species Rat

ATE oral (mg/kg) 2,830.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,100.0

Species Rat

ATE dermal (mg/kg) 2,100.0

Skin corrosion/irritation

Animal data Non Corrosive to skin.

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vivo Data lacking.

Carcinogenicity

Carcinogenicity No evidence of carcinogenicity in animal studies

Reproductive toxicity

Reproductive toxicity - development Data lacking.

Inhalation Irritating to respiratory system.

Eye contact May cause severe eye irritation.

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

Ecological information on ingredients.

XYLENE

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Ecological information on ingredients.

XYLENE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 2.6 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3.62 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 3.2 mg/l, Algae

2-METHYLPROPAN-1-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1430 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1100 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 593 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms IC₅₀, 16 hours: >1000 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability No data available.

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

Ecological information on ingredients.

XYLENE

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

XYLENE

Partition coefficient log Kow: 3.12 - 3.2

12.4. Mobility in soil

Mobility The product is non-volatile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

XYLENE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. DO NOT reuse containers containing residual product without commercial cleaning

Waste class When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID) 1263

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT OR PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels

**14.4. Packing group**

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

515/Q113 - HIGH PERFORMANCE MARINE PRIMER - ACTIVATOR FOR RED**SECTION 16: Other information**

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate.
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
	CAS: Chemical Abstracts Service.
	DNEL: Derived No Effect Level.
	GHS: Globally Harmonized System.
	IATA: International Air Transport Association.
	ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
	IMDG: International Maritime Dangerous Goods.
	LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose).
	PBT: Persistent, Bioaccumulative and Toxic substance.
	PNEC: Predicted No Effect Concentration.
	REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
	vPvB: Very Persistent and Very Bioaccumulative.
	EC ₅₀ : 50% of maximal Effective Concentration.
Classification abbreviations and acronyms	Aquatic Acute = Hazardous to the aquatic environment (acute)
	Aquatic Chronic = Hazardous to the aquatic environment (chronic)
	Asp. Tox. = Aspiration hazard
	Eye Dam. = Serious eye damage
	Eye Irrit. = Eye irritation
	Resp. Sens. = Respiratory sensitisation
	Skin Corr. = Skin corrosion
	Skin Irrit. = Skin irritation
	Skin Sens. = Skin sensitisation
	STOT RE = Specific target organ toxicity-repeated exposure
	STOT SE = Specific target organ toxicity-single exposure
Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 This is the first issue.
Issued by	Technical Dept. (P.E.)
Revision date	12/03/2020
Revision	0.0
SDS number	20979
SDS status	Approved.
Hazard statements in full	H226 Flammable liquid and vapour.
	H312 Harmful in contact with skin.
	H315 Causes skin irritation.
	H318 Causes serious eye damage.
	H332 Harmful if inhaled.
	H335 May cause respiratory irritation.
	H336 May cause drowsiness or dizziness.
Signature	Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.