

SAFETY DATA SHEET 525/Q607 - PEEL AWAY MARINE

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 525/Q607 - PEEL AWAY MARINE

Product number 525/Q607/40

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PAINT REMOVAL SYSTEM

1.3. Details of the supplier of the safety data sheet

Supplier TEAL & MACKRILL LIMITED TEAL AND MACKRILL EU B.V.

 Lockwood Street
 Zandvoorrtstaat 69

 HULL UK
 1976 BN IJMUIDEN

 HU2 OHN
 THE NETHERLANDS

 +441482320194 (T)
 +441482320194 (T)

 +441482219266 (F)
 info@teamac.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 11546

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H302+H332 Harmful if swallowed or if inhaled.

525/Q607 - PEEL AWAY MARINE

Precautionary statements P102 Keep out of reach of children.

P261 Avoid breathing fume, vapours.
P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. P501 Dispose of contents/ container in accordance with national regulations.

Contains BENZYL ALCOHOL

Supplementary precautionary statements

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

 BENZYL ALCOHOL
 30-60%

 CAS number: 100-51-6
 EC number: 202-859-9

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn;R20/22

Acute Tox. 4 - H332

kaolin 10-30%

CAS number: 1332-58-7

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Never give anything by mouth to an unconscious person.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and

ensure breathing can take place.

Ingestion DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh

air and keep warm and at rest in a position comfortable for breathing.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing

immediately and wash skin with soap and water.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an

extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is non-combustible. Toxic and corrosive gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Avoid the spillage or runoff entering drains, sewers or watercourses. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray mists. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely. Label the

containers containing waste and contaminated materials and remove from the area as soon

as possible.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

kaolin

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³ WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Eye/face protection

Wear approved, tight fitting safety glasses where splashing is probable.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturers' performance data suggest that the optimum glove for use should be: Neoprene, nitrile, polyethylene or PVC. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter (type P2).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Not applicable.

Appearance Viscous, cloudy liquid.

Colour Grey.

Odour threshold Not determined. Melting point Not applicable. Initial boiling point and range Not determined. Flash point

525/Q607 - PEEL AWAY MARINE

Evaporation rateNot determined.Evaporation factorNot determined.Flammability (solid, gas)Not applicable.

Upper/lower flammability or

explosive limits

Not applicable.

Vapour pressure Not determined.

Vapour density Not determined.

Bulk density Not applicable.

Solubility(ies) Miscible with water Miscible with the following materials: Alcohols.

Auto-ignition temperature >400°C

Explosive properties Not applicable.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Volatile organic compound Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not determined.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

products other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

Acute toxicity - oral

ATE oral (mg/kg) 500.0

525/Q607 - PEEL AWAY MARINE

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 20.0

General information No specific health hazards known.

Inhalation Vapours may irritate throat/respiratory system. Symptoms following overexposure may include

the following: Coughing.

Ingestion Irritating. Symptoms following overexposure may include the following: Nausea, vomiting.

Stomach pain.

Skin contact Liquid may irritate skin.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

This product has low toxicity. Only large quantities are likely to have adverse effects on

human health.

Route of exposure Skin absorption. Ingestion. Skin and/or eye contact.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

BENZYL ALCOHOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 1,620.0

mg/kg)

Species Rat

ATE oral (mg/kg) 1,620.0

Acute toxicity - inhalation

ATE inhalation (vapours 11.0

mg/l)

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product contains substances, which are water soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

525/Q607 - PEEL AWAY MARINE

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated

as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the

requirements of the local Waste Disposal Authority.

Disposal methods Avoid the spillage or runoff entering drains, sewers or watercourses.

Waste class When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as non-

hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). Part used containers, not drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02

(plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

Road transport notes Not classified.

Rail transport notes Not classified.

Sea transport notes Not classified.

Air transport notes Not classified.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

Proper shipping name

PAINT OR PAINT RELATED MATERIAL

(ADR/RID)

Proper shipping name (IMDG) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT OR PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as

amended).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

CAS: Chemical Abstracts Service.

DNEL: Derived No Effect Level.

GHS: Globally Harmonized System.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

PNEC: Predicted No Effect Concentration.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

SVHC: Substances of Very High Concern.

vPvB: Very Persistent and Very Bioaccumulative. cATpE: Converted Acute Toxicity Point Estimate.

EC $_{50}$: 50% of maximal Effective Concentration.

Classification abbreviations and acronyms

Aquatic Acute = Hazardous to the aquatic environment (acute)
Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Asp. Tox. = Aspiration hazard Carc. = Carcinogenicity

Eye Dam. = Serious eye damage

Eye Irrit. = Eye irritation

Resp. Sens. = Respiratory sensitisation

Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation

STOT SE = Specific target organ toxicity-single exposure STOT RE = Specific target organ toxicity-repeated exposure

Revision comments Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in

accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Amendment to Section 8.2, recommendations for respiratory protective equipment

and hand protection. Addition of EU supplier information

Issued by Technical Dept. (P.E.)

Revision date 09/02/2021

Revision 1.1

Supersedes date 17/04/2019

SDS number 11546

SDS status Approved.

Hazard statements in full H302 Harmful if swallowed.

H332 Harmful if inhaled.

Signature Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.