according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date : 15.05.2014 **Version (Revision) :** 2.0.0 (1.0.0)

Date of print : 16-09-2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lacq energol black (6450)

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Product categories [PC]

PC9A - Coatings and paints, thinners, paint removers

Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Vliegenthart B.V.

Street: Zuiderhavenweg 42

Postal code/city: 4004 JJ TIEL
Telephone: +31 (0)344 63 33 36
Telefax: +31 (0)344 63 16 16

1.4 Emergency telephone number

+31 (0)344 63 33 36 (During officehours: 08:30 - 17:00 hour.)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

None

Classification according to Regulation (EC) No. 1272/2008 [CLP]

None

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH208 Contains 2-BUTANONE OXIME; HYDROCARBONS - TERPENE; COBALT BIS(2-

ETHYLHEXANOATE). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Page: 1 / 8

(EN / NL)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date: 15.05.2014 **Version (Revision):** 2.0.0 (1.0.0)

Date of print: 16-09-2014

HYDROCARBONS, C10 - C13, N-ALKANES, ISOALKANES, CYCLICS, < 2; REACH registration No.: 01-2119457273-39; EC No.

: 918-481-9

Weight fraction: 10 - 25 % Classification 67/548/EEC: Xn; R65 Classification 1272/2008 [CLP]: None

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSINE - UNSPECIFIED; REACH registration No.: 01-

2119484819-18; EC No: 265-149-8; CAS No.: 64742-47-8

Weight fraction: 2,5 - 10 %
Classification 67/548/EEC: Xn; R65
Classification 1272/2008 [CLP]: Asp. Tox. 1; H304

 $\ \, \text{HYDROCARBONS, C10-C13, ISOALKANES, CYCLICS, } < 2\% \ \text{AROMATICS} \ ; \ \text{REACH registration No.} : 01-2119474196-32 \ ; \ \text{EC No.}$

: 918-317-6

Weight fraction : < 2,5 % Classification 67/548/EEC : Xn ; R65 R66 Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; EC No: 265-185-4; CAS No.: 64742-82-1

Weight fraction : < 2,5 % Classification 67/548/EEC : Xn ; R65 Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

2-BUTANONE OXIME; REACH registration No.: 01-2119539477-28; EC No: 202-496-6; CAS No.: 96-29-7

Weight fraction: < 1 %

Classification 67/548/EEC: Carc. Cat.3; R40 R43 Xi; R41 Xn; R21

Classification 1272/2008 [CLP]: Carc. 2; H351 Eye Dam. 1; H318 Acute Tox. 4; H312 Skin Sens. 1; H317 HYDROCARBONS - TERPENE; REACH registration No.: 01-2119980606-28; EC No: 273-309-3; CAS No.: 68956-56-9

Weight fraction: 0.1 - 1 %

Classification 67/548/EEC : R10 N ; R51/53 R43 Xn ; R65 Xi ; R36/38

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317

Aquatic Chronic 2; H411

 ${\sf COBALT~BIS} (2\text{-ETHYLHEXANOATE})~;~ REACH~ registration~ No.: 01-2119524678-29~;~ EC~No: 205-250-6;~ CAS~No.: 136-52-7~ C$

Weight fraction: 0,1 - 0,25 %

Classification 67/548/EEC: N; R50/53 Repr. Cat.3; R62 R43

Classification 1272/2008 [CLP]: Repr. 2 ;H361f Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of R-, H- and EUH-phrases: see section 16.

3.3 Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Page: 2/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date: 15.05.2014 **Version (Revision):** 2.0.0 (1.0.0)

Date of print: 16-09-2014

If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eve contact

If possible, remove contactlenses. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do not induce vomiting. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam. Extinguishing powder. Carbon dioxide (CO2). Sand. Water mist

Unsuitable extinguishing media

High power water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a heath hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Do not allow run-off from fire-fighting to enter drains or water courses. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For cleaning up

Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent

Page: 3 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date: 15.05.2014 **Version (Revision):** 2.0.0 (1.0.0)

Date of print : 16-09-2014

cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling





Protective measures

Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment. (see chapter 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Avoid the forming of inflammable or explosive concentrations of vapour in the air and exposure concentrations higher than permitted, Comply with the health and safety at work laws.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.

Requirements for storage rooms and vessels

Keep container tightly closed. Ensure adequate ventilation of the storage area. Restrict access to stockrooms.

Hints on joint storage

Keep away from

Keep away from ignition sources. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protection equipment

Eye / face protection

Page: 4/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date: 15.05.2014 **Version (Revision):** 2.0.0 (1.0.0)

Date of print : 16-09-2014



Eye glasses with side protection

Skin protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes). Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

Hand protection

Long Gloves PVC (Polyvinyl chloride) PE (polyethylene) NR (natural rubber, natural latex)

Recommended Thickness DIN EN 374

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour: Colourless.

Odour: Characteristic.

Odor Threshold value Not determined

Safety relevant basis data

Physical state: liquid
Melting point / melting range: No data available
Boiling temperature / boiling range
: Not determined
: Decomposition temperature: (1013 hPa) Not determined
Evaporation rate Not determined
Flash point: Not determined

 Ignition temperature :
 Not determined

 Flammability (gas, solid)
 Not determined

 Lower explosion limit :
 Not determined

 Upper explosion limit :
 Not determined

 Explosive properties
 Not determined

 Vapour pressure :
 (50 °C)
 <</td>
 1000

Oxidising properties

Partition coefficient n-

octanol/water Not determined

Page: 5 / 8

Not determined

CC

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date : 15.05.2014 **Version (Revision) :** 2.0.0 (1.0.0)

Date of print : 16-09-2014

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7 and 8).

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Phototoxicity

Additional information

According to known data, also after prolonged contact, no hazard to health has occured

11.4 Additional information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

Page: 6 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date : 15.05.2014 **Version (Revision) :** 2.0.0 (1.0.0)

Date of print : 16-09-2014

12.7 Further ecological information

Additional information

Product should not be released into water without pre-treatment (biological sewage plant).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

14.1 UN number

No dangerous goods in sense of this transport regulation.

14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

14.3 Transport hazard class(es)

No dangerous goods in sense of this transport regulation.

14.4 Packing group

No dangerous goods in sense of this transport regulation.

14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

None

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients

16.2 Abbreviations and acronyms

None

Page: 7 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq energol black

Revision date: 15.05.2014 **Version (Revision):** 2.0.0 (1.0.0)

Date of print: 16-09-2014

16.3 Key literature references and sources for data

None

16.5 Relevant R-, H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H361f Suspected of damaging fertility.
H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

10 Flammable.

21 Harmful in contact with skin. 36/38 Irritating to eyes and skin.

40 Limited evidence of a carcinogenic effect.

41 Risk of serious damage to eyes.

43 May cause sensitization by skin contact.

50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

62 Possible risk of impaired fertility.

65 Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

Make sure that employees are aware of the safety risk. People wearing breathing apparatus must be appropriately trained.

16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 8 / 8