



# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

# SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : LINITOP ACRYL VERNIS BRILLANT Product code : LVAVB01.

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Acrylic Polyurethane varnish

## 1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A..

Address : Z.I. "La Marinière" 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE.

Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84.

info@durieu.com

www.durieu.com

# 1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

## Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE: Ireland National Poisons Information Centre: +353 (0) 1 8379964 AUSTRALIA: Poison Information Centre: 131 126 NEW ZEALAND: Poison Information Centre 0 800 764 766:

#### **SECTION 2 : HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

#### In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

#### In compliance with EC regulation No. 1272/2008 and its amendments.

| Additional labeling :         |  |
|-------------------------------|--|
| EUH208                        | Contains 2,4,7,9,-TETREMETHYLDEC-5-YNE-4,7 DIOL. May produce an allergic reaction. |
| EUH208                        | Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.           |
| Precautionary statements - G  | eneral :   |
| P101                          | If medical advice is needed, have product container or label at hand.              |
| P102                          | Keep out of reach of children.   |
| Precautionary statements - Pr | revention :  |
| P262                          | Do not get in eyes, on skin, or on clothing.                                       |

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

# 3.2. Mixtures

#### Composition :

| - |                         |                |      |                |
|---|-------------------------|----------------|------|----------------|
|   | Identification          | (EC) 1272/2008 | Note | %              |
|   | INDEX: PCP226           |                | [1]  | 0 <= x % < 2.5 |
|   | CAS: 57-55-6            |                |      |                |
|   | EC: 200-338-0           |                |      |                |
|   | REACH: 01-2119456809-23 |                |      |                |
|   |                         |                |      |                |

| ETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)<br>TOP ACRYL VERNIS BRILLANT - LVAVB01 |                         | Version 5.1 (26-08-2020) - Page 2/9 |                 |  |
|--|-------------------------|-------------------------------------|-----------------|--|
| PROPANE-1,2-DIOL   |                         |                                     |                 |  |
| INDEX: 603-027-00-1  | GHS07                   | [1]                                 | 0 <= x % < 2.5  |  |
| CAS: 107-21-1  | Wng                     |                                     |                 |  |
| EC: 203-473-3  | Acute Tox. 4, H302      |                                     |                 |  |
| ETHANEDIOL   |                         |                                     |                 |  |
| INDEX: 147   | GHS05, GHS07            |                                     | 0 <= x % < 2.5  |  |
| CAS: 126-86-3  | Dgr                     |                                     |                 |  |
| EC: 204-809-1  | Skin Sens. 1B, H317     |                                     |                 |  |
| REACH: 01-2119954390-3   | Eye Dam. 1, H318        |                                     |                 |  |
|  | Aquatic Chronic 3, H412 |                                     |                 |  |
| 2,4,7,9,-TETREMETHYLDEC-5-YNE-4<br>,7 DIOL   |                         |                                     |                 |  |
| INDEX: 603-053-00-3  | GHS07                   | [1]                                 | 0 <= x % < 2.5  |  |
| CAS: 107-41-5  | Wng                     |                                     |                 |  |
| EC: 203-489-0  | Eye Irrit. 2, H319      |                                     |                 |  |
| REACH: 01-2119539582-35  | Skin Irrit. 2, H315     |                                     |                 |  |
| 2-METHYLPENTANE-2,4-DIOL   |                         |                                     |                 |  |
| INDEX: 199   | GHS07, GHS05, GHS09     |                                     | 0 <= x % < 0.05 |  |
| CAS: 2634-33-5   | Dgr                     |                                     |                 |  |
| EC: 220-120-9  | Acute Tox. 4, H302      |                                     |                 |  |
| REACH: 01-2120761540-60  | Skin Irrit. 2, H315     |                                     |                 |  |
|  | Skin Sens. 1, H317      |                                     |                 |  |
| 1,2-BENZISOTHIAZOL-3(2H)-ONE   | Eye Dam. 1, H318        |                                     |                 |  |
|  | Aquatic Chronic 2, H411 |                                     |                 |  |
|  | Aquatic Acute 1, H400   |                                     |                 |  |
|  | M Acute = 1             |                                     |                 |  |
| INDEX: 019-002-00-8  | GHS05, GHS07            | [1]                                 | 0 <= x % < 0.01 |  |
| CAS: 1310-58-3   | Dgr                     |                                     |                 |  |
| EC: 215-181-3  | Acute Tox. 4, H302      |                                     |                 |  |
|  | Skin Corr. 1A, H314     |                                     |                 |  |
| POTASSIUM HYDROXIDE  |                         |                                     |                 |  |
| NDEX: 350  | GHS09                   | [1]                                 | 0 <= x % < 2.5  |  |
| CAS: 128-37-0  | Wng                     |                                     |                 |  |
| EC: 204-881-4  | Aquatic Acute 1, H400   |                                     |                 |  |
| REACH: 01-2119565113-46  | M Acute = 1             |                                     |                 |  |
|  | Aquatic Chronic 1, H410 |                                     |                 |  |
| 2,6-DI-TERT-BUTYL-P-CRESOL   | M Chronic = 1           |                                     |                 |  |

(Full text of H-phrases: see section 16)

# Information on ingredients :

S L

[1] Substance for which maximum workplace exposure limits are available.

# **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

## In the event of splashes or contact with eyes :

Wash thoroughly with soft clean water for 15mn holding the eyelids open. Refer to an ophthalmologist in particular if there is any redness, pain or visual impair.

#### In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

## Wash thoroughly with soft clean water.

Remove contaminated clothing and wash skin thoroughly with soap and water or a recognized cleaner.

DO NOT use solvents or thinners.

# In the event of swallowing :

Seek medical attention, showing the label.

In case of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. In case of accidental ingestion, call a doctor to assess the appropriateness of monitoring and subsequent treatment in hospital, if necessary. Show the label.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# SECTION 5 : FIREFIGHTING MEASURES

This product is not classed as flammable.

#### 5.1. Extinguishing media

#### Suitable methods of extinction

In the event of a fire, use :

- water with AFFF (Aqueous Film Forming Foam) additive

- foam
- multipurpose ABC powder
- carbon dioxide (CO2)

CO2, extinguishing powder or pulverized water.

Unsuitable methods of extinction

Direct water jet.

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Bring independant breathing apparatus.

#### **SECTION 6 : ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid contact with skin and eyes

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

## 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

# **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

#### Fire prevention :

Prevent access by unauthorised personnel.

## Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in the original container

Stock between +5°C and +30°C in a dry, well ventilated place.

#### Storage

Keep out of reach of children.

# Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

# SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

## Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

| CAS          | VME-mg/m3 :             | VME-ppm :             | VLE-mg/m3 :           | VLE-ppm :              | Notes :      |          |  |
|--------------|-------------------------|-----------------------|-----------------------|------------------------|--------------|----------|--|
| 107-21-1     | 52                      | 20                    | 104                   | 40                     | Peau         |          |  |
| - ACGIH T    | LV (American Conferer   | nce of Governmental   | Industrial Hygienists | , Threshold Limit Valu | ues, 2010) : |          |  |
| CAS          | TWA :                   | STEL :                | Ceiling :             | Definition :           | Criteria :   |          |  |
| 107-21-1     | -                       | -                     | 100                   | -                      | -            |          |  |
| 107-41-5     |                         |                       | 25 ppm                |                        |              |          |  |
| 1310-58-3    |                         |                       | 2 mg/m3               |                        |              |          |  |
| 128-37-0     | 2 (IFV) mg/m3           |                       |                       | A4                     |              |          |  |
| - Germany    | - AGW (BAuA - TRGS      | 900, 08/08/2019) :    |                       |                        |              |          |  |
| CAS          | VME :                   | VME :                 | Excess                | Notes                  |              |          |  |
| 107-21-1     |                         | 10 ppm                |                       | 2(Ι)                   |              |          |  |
|              |                         | 26 mg/m <sup>3</sup>  |                       |                        |              |          |  |
| 128-37-0     |                         | 10 mg/m <sup>3</sup>  |                       | 4 (II)                 |              |          |  |
| - France (II | NRS - ED984 / 2019-14   | 487) :                |                       |                        |              |          |  |
| CAS          | VME-ppm :               | VME-mg/m3 :           | VLE-ppm :             | VLE-mg/m3 :            | Notes :      | TMP No : |  |
| 107-21-1     | 20                      | 52                    | 40                    | 104                    | *            | 84       |  |
| 107-41-5     | -                       | -                     | 25                    | 125                    | -            | 84       |  |
| 1310-58-3    | -                       | -                     | -                     | 2                      | -            | -        |  |
| 128-37-0     | -                       | 10                    | -                     | -                      | -            | -        |  |
| - Czech Re   | epublic (Regulation No. | 361/2007):            |                       |                        |              |          |  |
| CAS          | TWA :                   | STEL :                | Ceiling :             | Definition :           | Criteria :   |          |  |
| 107-21-1     | 50 mg/m <sup>3</sup>    | 100 mg/m <sup>3</sup> |                       | D                      |              |          |  |
| 1310-58-3    | 1 mg/m <sup>3</sup>     | 2 mg/m <sup>3</sup>   |                       | I                      |              |          |  |
| - UK / WEL   | (Workplace exposure     | limits, EH40/2005, 20 | 011):                 |                        |              |          |  |
| CAS          | TWA :                   | STEL :                | Ceiling :             | Definition :           | Criteria :   |          |  |
| 57-55-6      | 150 ppm                 | - ppm                 |                       |                        |              |          |  |
|              | 474 mg/m <sup>3</sup>   | - mg/m³               |                       |                        |              |          |  |
| 107-21-1     | 20 ppm                  | 40 ppm                |                       |                        |              |          |  |
|              | 52 mg/m <sup>3</sup>    | 104 mg/m <sup>3</sup> |                       |                        |              |          |  |
| 107-41-5     | 25 ppm                  | 25 ppm                |                       |                        |              |          |  |
|              | 123 mg/m <sup>3</sup>   | 123 mg/m <sup>3</sup> |                       |                        |              |          |  |
| 1310-58-3    | - ppm                   | - ppm                 |                       |                        |              |          |  |
|              | - mg/m³                 | 2 mg/m <sup>3</sup>   |                       |                        |              |          |  |
| 128-37-0     | - ppm                   | - ppm                 |                       |                        |              |          |  |
|              | 10 mg/m <sup>3</sup>    | - mg/m³               |                       |                        |              |          |  |

#### 8.2. Exposure controls

# Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

Use personal protection equipment.

### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVC (polyvinyl chloride)

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

Permeability time : >480 min for a thickness >0.45 mm

CEN recommendations : EN 420 and EN 374/3

## - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

After contact with the product, soiled clothing must be removed and the skin must be cleaned with soap and water or a suitable cleaner for skin. - Respiratory protection

# Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP2

Type of mask with combined filters :

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A2 (Brown)

- B2 (Grey)

Particle filter according to standard EN143 :

- P2 (White)

CEN recommendations : EN 136, EN 140, EN 405 for masks and EN 143, EN 149 for filters.

## **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

## General information :

| Physical state :                                       | Fluid liquid.   |
|--|-----------------|
| Colour :   | Milky.          |
| Important health, safety and environmental information | on              |
| pH :   | 8.50 .          |
|  | Slightly basic. |
| Boiling point/boiling range :                          | Not specified.  |
| Flash point interval :                                 | Not relevant.   |
| Vapour pressure (50°C) :                               | Not relevant.   |
| Density :  | > 1             |
| Water solubility :                                     | Dilutable.      |
| Melting point/melting range :                          | Not specified.  |
| Self-ignition temperature :                            | Not relevant.   |
| Decomposition point/decomposition range :              | Not specified.  |
| 9.2. Other information                                 |                 |
| VOC (g/l) :  | 90              |

VOC (g/i) :

## **SECTION 10 : STABILITY AND REACTIVITY**

## 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

#### No data available.

#### 10.4. Conditions to avoid

Avoid :

- frost

Always stock in its original packaging. Do not transfer in another package.

## 10.5. Incompatible materials

No data available.

## 10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

# SECTION 11 : TOXICOLOGICAL INFORMATION

Slightly toxic. Can cause varying degrees of harm to the lungs. Based on relative experimental data on products with similar structure. Slightly irritating on skin if exposed over extended period. Based on relative experimental data on products with similar structure. Can cause slight temporary eye irritation. Based on relative experimental data on products with similar structure.

#### 11.1. Information on toxicological effects

No data available.

# 11.1.1. Substances

## Acute toxicity :

| 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)<br>Oral route : | LD50 = 597 mg/kg<br>Species : Rat                           |
|---|---|
|   | OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)   |
| Dermal route :  | LD50 > 2000 mg/kg   |
|   | Species : Rat   |
|   | OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée) |
| PROPANE-1,2-DIOL (CAS: 57-55-6)                               |   |
| Oral route :  | LD50 = 22000 mg/kg  |
|   | Species : Rat   |
| Dermal route :  | LD50 > 2000 mg/kg   |
|   | Species : Rabbit  |
| Inhalation route (Dusts/mist):                                | LC50 > 315642 mg/l  |
|   | Species : Rabbit  |
| Respiratory or skin sensitisation :                           |   |
| PROPANE-1,2-DIOL (CAS: 57-55-6)                               |   |
| Local lymph node stimulation test :                           | Non-Sensitiser.   |
|   | Species : Rabbit  |
|   | OCDE Ligne directrice 406 (Sensibilisation de la peau)      |
|   | OCDE Ligne directrice 406 (Sensibilisation de la peau)      |
|   | OCDE Ligne directrice 406 (Sensibilisation de la peau)      |

## 11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

# Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 128-37-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

# **SECTION 12 : ECOLOGICAL INFORMATION**

## 12.1. Toxicity

Do not leave this product, not diluted or in great quantity, penetrate the ground water, waters or the drains.

## 12.1.1. Substances

| FETY DATA SHEET (REGULATION (EC) n° 1907/2006 -<br>IITOP ACRYL VERNIS BRILLANT - LVAVB01 | REACH) Version 5.1 (26-08-2020) - Pag                                     |
|--|---|
| 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)  |   |
| Fish toxicity :  | LC50 = 0.74 mg/l  |
|  | Duration of exposure : 96 h   |
| Crustacean toxicity :  | EC50 = 2.44 mg/l  |
|  | Species : Daphnia magna   |
|  | Duration of exposure : 48 h   |
| PROPANE-1,2-DIOL (CAS: 57-55-6)  |   |
| Fish toxicity :  | LC50 = 40613 mg/l   |
|  | Species : Oncorhynchus mykiss   |
|  | Duration of exposure : 96 h   |
|  | OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)              |
| Crustacean toxicity :  | EC50 = 18340 mg/l   |
|  | Species : Ceriodaphnia dubia  |
|  | Duration of exposure : 48 h   |
|  | OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate) |
| Algae toxicity :   | ECr50 = 19000 mg/l  |
|  | Species : Pseudokirchnerella subcapitata                                  |
|  | Duration of exposure : 96 h   |
|  | OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)   |
| 12.1.2. Mixtures   |   |
| No aquatic toxicity data available for the mixture.                                      |   |
| 12.2. Persistence and degradability  |   |
| 12.2.1. Substances   |   |
| 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)  |   |
| Biodegradability :   | Rapidly degradable.   |
| PROPANE-1,2-DIOL (CAS: 57-55-6)  |   |
| Biodegradability :   | no degradability data is available, the substance is considered as not    |
|  | degrading quickly.  |
| 12.3. Bioaccumulative potential  |   |
| 12.3.1. Substances   |   |
| 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)  |   |
| Octanol/water partition coefficient :  | log Koe = 0.4   |
| Bioaccumulation :  | BCF = 1.4   |
| 12.4. Mobility in soil   |   |
| Contains volatile products that will disperse in air.                                    |   |
| Contains a solid phase.  |   |
| 12.5. Results of PBT and vPvB assessment   |   |
| No data available.   |   |
| 12.6. Other adverse effects  |   |
|  |   |

## **SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

# Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Version 5.1 (26-08-2020) - Page 8/9

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

## Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 \* packaging containing residues of or contaminated by dangerous substances

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

#### **SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

14.1. UN number

14.2. UN proper shipping name

- 14.3. Transport hazard class(es)
- -
- 14.4. Packing group
- 14.5. Environmental hazards
- -
- 14.6. Special precautions for user
- SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)
- Container information:

No data available.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 90 g/l.

The permitted European levels of VOC in the ready-to-use product (category IIAe) are 150 g/l maximum in 2007 and 130 g/l maximum in 2010. - Particular provisions :

No data available.

- 15.2. Chemical safety assessment
  - No data available.

## **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

#### Wording of the phrases mentioned in section 3 :

| H302 | Harmful if swallowed.                                 |  |
|------|---|--|
| H314 | Causes severe skin burns and eye damage.              |  |
| H315 | Causes skin irritation.                               |  |
| H317 | May cause an allergic skin reaction.                  |  |
| H318 | Causes serious eye damage.                            |  |
| H319 | Causes serious eye irritation.                        |  |
| H400 | Very toxic to aquatic life.                           |  |
| H410 | Very toxic to aquatic life with long lasting effects. |  |
| H411 | Toxic to aquatic life with long lasting effects.      |  |
| H412 | Harmful to aquatic life with long lasting effects.    |  |

#### Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.