SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| 1.1 Product identifier | |
|------------------------------|-------------------------|
| Product name | : Cleanser/Thinner No.1 |
| Product code | : C1 |
| Index number | : 649-405-00-X |
| REACH Registration number | : 01-2119458049-33 |
| CAS number | : 64742-88-7 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Material uses | : | Paint or paint related material. |
|---------------|---|----------------------------------|
| | : | Industrial use only. |

1.3 Details of the supplier of the safety data sheet

Sherwin-Williams UK Limited - Protective & Marine Coatings Division EMEAI Tower Works Kestor Street Bolton BL2 2AL United Kingdom +44 (0) 1204 521771

The Sherwin-Williams Company Inver France SAS 2 Rue Jean Revaus - BP 80088 - 79102 Thouars CEDEX France

e-mail address of person : hse.pm.emea@sherwin.com responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

| : +353 1 809 2166 (08:00-22:00) |
|----------------------------------------------|
| |
| : +(44)-870-8200 418 |
| : Emergency contact available 24 hours a day |
| |

SHW-A4-EU-CLP44-IE

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition

: Mono-constituent substance

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Lig. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

1

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

| Signal word | : Danger |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard statements | : Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. |
| Precautionary statements | |
| Prevention | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour. |
| Response | : Collect spillage. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. |
| Storage | : Not applicable. |
| Disposal | : Not applicable. |
| Hazardous ingredients | : - |
| Supplemental label elements | : FOR INDUSTRIAL USE ONLY |
| Special packaging requirer | nents |

Not applicable.

2.3 Other hazards

| Product meets the criteria : for PBT or vPvB according | РВТ | Р | В | т | vPvB | vP | vB |
|-----------------------------------------------------------|-----|-----|-----|-----|------|-----|-----|
| to Regulation (EC) No. 1907/2006, Annex XIII | N/A | N/A | N/A | Yes | N/A | N/A | N/A |

Other hazards which do not result in classification

: None known.

SHW-A4-EU-CLP44-IE

SECTION 3: Composition/information on ingredients

:

3.1 Substance

| Product/ingredient name | Identifiers | % | Regulation (EC) No. 1272/2008 [CLP] | Туре |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------|------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | REACH #: 01-2119458049-33 CAS: 64742-88-7 Index: 649-405-00-X | 100.0 | Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 (central nervous system (CNS)) Asp. Tox. 1, H304 Aquatic Chronic 2, H411 | [A] |
| | | | See Section 16 for the full text of the H statements declared above. | |

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

<u>Type</u>

[A] Constituent

[B] Impurity

[C] Stabilising additive

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General | In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact | Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. |
| Inhalation | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

| Date of issue/Date of revision | : 15, Jun, 2022 | Date of previous issue | : 14, Jan, 2022 | Version : 1.01 | 3/14 |
|--------------------------------|-----------------|------------------------|-----------------|--------------------|------|
| | | | | SHW-A4-EU-CLP44-IE | |

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Specific treatments | : No specific treatment. |

See toxicological information (Section 11)

| SECTION 5: Firefighting | m | easures |
|------------------------------------------------------------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5.1 Extinguishing media Suitable extinguishing media | : | Recommended: alcohol-resistant foam, carbon dioxide, powders. |
| Unsuitable extinguishing media | : | Do not use water jet. |
| 5.2 Special hazards arising fi | ron | n the substance or mixture |
| Hazards from the substance or mixture | : | Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. |
| Hazardous combustion products | : | Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. |
| 5.3 Advice for firefighters | | |
| Special protective actions for fire-fighters | : | Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. |
| Special protective equipment for fire-fighters | : | Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. |
| SECTION 6: Accidental | rel | ease measures |
| 6.1 Personal precautions, pre | ote | ctive equipment and emergency procedures |
| For non-emergency personnel | : | Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. |
| | | Keep unnecessary and unprotected personnel from entering. |
| For emergency responders | : | If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : | Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations. |
| 6.3 Methods and material | : | Contain and collect spillage with non-combustible, absorbent material e.g. sand, |

- for containment and cleaning up
 6.4 Reference to other
 earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
 See Section 1 for emergency contact information.
- sections See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

C1

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

| 7.1 Precautions for safe handling | Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. Information on fire and explosion protection Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour in all cases. |
|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7.2 Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Notes on joint storage Keep away from: oxidising agents, strong alkalis, strong acids. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Contaminated absorbent material may pose the same hazard as the spilt product. |
| | Store in closed original container at temperatures between 5°C and 25°C. |
| 7.3 Specific end use(s) | |
| Recommendations | : Not available. |
| Industrial sector specific solutions | : Not available. |

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

C1

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

| Recommended monitoring procedures | : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

: Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

SHW-A4-EU-CLP44-IE

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

| 8.2 Exposure controls | | | | | |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
| Appropriate engineering controls | : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. | | | | |
| | Users are advised to consider national Occupational Exposure Limits or other equivalent values. | | | | |
| Individual protection mea | asures | | | | |
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | | | | |
| Eye/face protection | : Use safety eyewear designed to protect against splash of liquids. | | | | |
| Skin protection | | | | | |
| Hand protection | : Wear suitable gloves tested to EN374. | | | | |
| Gloves | Gloves for term exposure/splash protection (less than 10 min):Nitrile>0.12 mm Gloves for splash protection need to be changed immediately when in contact with chemicals. Gloves for repeated or prolonged exposure (breakthrough time > 240 min.) When he hazardous ingredients in Section 3 contain any of the following: Aromatic solvents (Xylene, Toluene) or Aliphatic solvents or Mineral Oil use: Polyvinyl alcohol PVA) gloves 0.2-0.3 mm Otherwise use: Butyl gloves >0.3 mm For long term exposure or spills (breakthrough time >480 min.): Use PE laminated gloves as under gloves Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. | | | | |
| | The recommendation for the type or types of glove to usewhen handling this product | | | | |
| Date of issue/Date of revision | : 15, Jun, 2022 Date of previous issue : 14, Jan, 2022 Version : 1.01 6/14 | | | | |

C1

SECTION 8: Exposure controls/personal protection

| | is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG). |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. The user must check that the final choice of type of glove selected for handling this |
| | product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. |
| Body protection | : Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres. |
| | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Environmental exposure controls | : Do not allow to enter drains or watercourses. |

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| <u>Appearance</u> | |
|------------------------------|---------------------------------------------------------|
| Physical state | : Liquid. |
| Colour | : Colourless. |
| Odour | : Reducer |
| Odour threshold | : Not Available (Not Tested). |
| рH | : Not applicable. |
| Melting point/freezing point | : Not relevant/applicable due to nature of the product. |

SECTION 9: Physical and chemical properties

| Initial boiling point and boiling range | : | 153°C |
|-------------------------------------------------|---|------------------------------------------------------------------------------------------------|
| Flash point | : | Closed cup: 39°C [Pensky-Martens Closed Cup] |
| Evaporation rate | : | 0.18 (butyl acetate = 1) |
| Flammability (solid, gas) | : | Not relevant/applicable due to nature of the product. |
| Upper/lower flammability or explosive limits | : | LEL: 0.9% (Med. Aliphatic Hydrocarbon Solvent) UEL: 8% (Med. Aliphatic Hydrocarbon Solvent) |
| Vapour pressure | : | 0.37 kPa (2.78 mm Hg) |
| Vapour density | : | Not relevant/applicable due to nature of the product. |
| Relative density | : | 0.77 |
| Solubility(ies) | : | Not relevant/applicable due to nature of the product. |
| Partition coefficient: n-octanol/ water | : | Not relevant/applicable due to nature of the product. |
| Auto-ignition temperature | : | Not relevant/applicable due to nature of the product. |
| Decomposition temperature | | Not relevant/applicable due to nature of the product. |
| Viscosity | : | Kinematic (40°C): <20.5 mm²/s |
| Explosive properties | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| Oxidising properties | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| | | |

| - | | - |
|--------------------------------------------|---|--------------------------------------------------------------------------------------------------------------------------------|
| 10.1 Reactivity | : | No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : | Stable under recommended storage and handling conditions (see Section 7). |
| 10.3 Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : | When exposed to high temperatures may produce hazardous decomposition products. |
| 10.5 Incompatible materials | : | Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| 10.6 Hazardous decomposition products | : | Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. |
| Deferries Contine 7: LANDLIN | ~ | AND STORAGE and Section & EXPOSURE CONTROL S/RERSONAL |

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

C1

SECTION 11: Toxicological information

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---------------------------------------------|--------------------|---------|------|----------|
| No data available | | | | |
| No data available | | | | |
| rritation/Corrosion | | | | |
| No data available | | | | |
| | Not available. | | | |
| <u>Sensitisation</u> No data available | | | | |
| Conclusion/Summary | Not available. | | | |
| Mutagenicity | | | | |
| No data available | | | | |
| <u>Carcinogenicity</u> No data available | | | | |
| Reproductive toxicity | | | | |
| No data available | | | | |
| <u>Teratogenicity</u> | | | | |
| No data available | | | | |
| Specific target organ toxicity | (cingle expective) | | | |

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------------------------------------------------------|------------|-------------------|------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | Category 3 | - | Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------------------------------------------------------|------------|-------------------|---------------------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | Category 1 | - | central nervous system (CNS) |

Aspiration hazard

| Product/ingredient name | Result |
|-------------------------------------------------------------------------|--------------------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | ASPIRATION HAZARD - Category 1 |

Other information

: Not available.

C1

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | | Dose | | Inoculum |
|-------------------------|-------------------|--------|------------|------|--------|------------|
| No data available | | | | | | |
| Conclusion/Summary | : Not available. | • | | • | | • |
| Product/ingredient name | Aquatic half-life | | Photolysis | | Biodeg | radability |
| No data available | | | | | | |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| No data available | | | |

| 12.4 Mobility in soil | |
|--------------------------------------------------------|------------------|
| Soil/water partition coefficient (K _{oc}) | : Not available. |
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

| Product/ingredient name | PBT | Р | В | Т | vPvB | vP | vB | |
|-------------------------|-----|-----|-----|-----|------|-----|-----|--|
| Cleanser/Thinner No.1 | N/A | N/A | N/A | Yes | N/A | N/A | N/A | |

12.6 Other adverse effects

: No known significant effects or critical hazards.

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13: Disposal considerations

| 13.1 Waste treatment metho | ods | |
|-----------------------------------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <u>Product</u> | | |
| Methods of disposal | : | The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
| Hazardous waste | : | Yes. |
| European waste catalogue (EWC) | : | waste paint and varnish containing organic solvents or other hazardous substances 08 01 11* |

SECTION 13: Disposal considerations

| - | |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Disposal considerations | Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority. |
| <u>Packaging</u> | |
| Methods of disposal | The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
| Disposal considerations | : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. |
| European waste catalogue (EWC) | packaging containing residues of or contaminated by hazardous substances 15 01 10* |
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |

| SECTION 14: Transport information | | | | |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|--|
| | ADR/RID | IMDG | ΙΑΤΑ | |
| 14.1 UN number | UN1263 | UN1263 | UN1263 | |
| 14.2 UN proper shipping name | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL. Marine pollutant (Med. Aliphatic Hydrocarbon Solvent) | PAINT RELATED MATERIAL | |
| 14.3 Transport Hazard Class(es)/ Label(s) | | | 3 | |
| 14.4 Packing group | 111 | III | 111 | |
| 14.5 Environmental hazards | Yes. | Yes. | Yes. The environmentally hazardous substance mark is not required. | |
| Additional information | The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Tunnel code</u> D/E | The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency schedules</u> F-E, S-E | The environmentally hazardous substance mark may appear if required by other transportation regulations. | |

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 14: Transport information

14.7 Transport in bulk according to IMO instruments : Not applicable.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations

VOC content (2010/75/EU) : 100 w/w 774 q/I

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

| 15.2 Chemical safety | : No Chemical Safety Assessment has been carried out. |
|----------------------|-------------------------------------------------------|
| | |

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| Abbreviations and acronyms | ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

SECTION 16: Other information

| | Key literature references |
|----------------------------------------------------------------------------------------|---------------------------|
| sources for data ADR = The European Agreement concerning the International Carriage of | and sources for data |
| Dangerous Goods by Road | |
| IATA = International Air Transport Association | |
| IMDG = International Maritime Dangerous Goods | |
| Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by | |
| Commission Regulation (EU) 2015/830 | |
| Directive 2012/18/EU, and relative amendments & additions | |
| Directive 2008/98/EC, and relative amendments & additions | |
| Directive 2009/161/EU, and relative amendments & additions | |
| CEPE Guidelines | |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classif | ication | Justification |
|----------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 | | On basis of test data Calculation method Calculation method Calculation method Calculation method |
| Full text of abbreviated H statements | H304 May b H336 May c H372 Cause expos | nable liquid and vapour. le fatal if swallowed and enters airways. ause drowsiness or dizziness. es damage to organs through prolonged or repeated ure. to aquatic life with long lasting effects. |
| Full text of classifications [CLP/GHS] | : Aquatic Chronic 2 Asp. Tox. 1 Flam. Liq. 3 STOT RE 1 STOT SE 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
| Date of printing | : 15, Jun, 2022. | |
| Date of issue/ Date of revision | : 15, Jun, 2022 | |
| Date of previous issue | : 14, Jan, 2022 | |
| | : If there is no previous v information. | alidation date please contact your supplier for more |
| Version | : 1.01 | |

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become make themselves aware of and understand the data contained in this SDS and any hazards that may be associated with the product. This information is provided in good faith and believed to be accurate as of the effective date mentioned herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can may change later the composition, hazards and risks of the product. Products shall should not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to, the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for the use of the product are not under the manufacturer's control of the manufacturer; the

SECTION 16: Other information

customer/buyer/user is responsible to for determine determining the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS, without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be held responsible for SDSs obtained from any other source.