

## SAFETY DATA SHEET

# 515/Q113 - 2 PACK ZINC PHOSPHATE PRIMER - BASE FOR RED & WHITE

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking			
1.1. Product identifier			
Product name	515/Q113 - 2 PACK ZINC PHOSPHATE PRIMER - BASE FOR RED & WHITE		
Product number	515/Q113/24 & 1 - BASE		
1.2. Relevant identified uses of	of the substance or mixture and uses advised against		
Identified uses	Paint.		
1.3. Details of the supplier of the supplicit states and the supplicit states are supplied as the supplicit states are supplicit states are supplied as the supplicit states are supplicit. The supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit. The supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit	the safety data sheet		
Supplier	TEAL & MACKRILL LIMITED LOCKWOOD STREET HULL HU2 0HN +44(0)1482 320194(T) +44(0)1482 219266(F) info@teamac.co.uk		
Contact person	Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above		
1.4. Emergency telephone nu	mber		
Emergency telephone	+44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)		
	10844		
SDS No.	10844		
SDS No. SECTION 2: Hazards identific			
	ation		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008)	eation tance or mixture		
SECTION 2: Hazards identific 2.1. Classification of the subs	tance or mixture		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008)	eation tance or mixture		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008) Physical hazards	eation tance or mixture Flam. Liq. 3 - H226		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008) Physical hazards Health hazards	eation tance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008) Physical hazards Health hazards Environmental hazards	tance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411 The product contains a small amount of sensitising substance. May cause skin sensitisation		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008) Physical hazards Health hazards Environmental hazards	tance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411 The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008) Physical hazards Health hazards Environmental hazards Human health Physicochemical	tance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411 The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.		
SECTION 2: Hazards identific 2.1. Classification of the subs Classification (EC 1272/2008) Physical hazards Health hazards Environmental hazards Human health Physicochemical 2.2. Label elements	tance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411 The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.		

1/16

Hazard statements	H312+H332 Harmful in contact with skin or if inhaled. H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	<ul> <li>P102 Keep out of reach of children.</li> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P261 Avoid breathing vapour/ spray.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P273 Avoid release to the environment.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.</li> <li>Rinse skin with water or shower.</li> <li>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P501 Dispose of contents/ container in accordance with national regulations.</li> </ul>
Contains	XYLENE, 2-METHYLPROPAN-1-OL
Supplementary precautionary statements	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish. P403+P235 Store in a well-ventilated place. Keep cool.

## 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

3.2. Mixtures		
XYLENE		10-30%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01- 2119488216-32-xxxx
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC or 1999/45/EC) Xn;R20/21,R65. Xi;R36/37/38. R10.	
2-METHYLPROPAN-1-OL		5-10%
CAS number: 78-83-1	EC number: 201-148-0	REACH registration number: 01- 2119484609-23-XXXX
Classification		
Flam. Liq. 3 - H226		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H335, H336		

1-METHOXY-2-PROPANOL		5-10%	
CAS number: 107-98-2	EC number: 203-539-1	REACH registration number: 01- 2119457435-35-0000	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) R10 R67		
TRIZINC BIS(ORTHOPHOSPHATE) 1-59			
CAS number: 7779-90-0	EC number: 231-944-3	REACH registration number: 01- 2119485044-40-0000	
M factor (Acute) = 1	M factor (Chronic) = 1		
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) N;R50/53		
The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.			
SECTION 4: First aid measure	es		
4.1. Description of first aid measures			
General information	General information Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.		
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any		

discomfort continues. Place unconscious person on their side in the recovery position and<br/>ensure breathing can take place.IngestionGive a few small glasses of water or milk to drink. Never give anything by mouth to an

unconscious person. Do not induce vomiting. Get medical attention if any discomfort continues.

Skin contactRemove affected person from source of contamination. Rinse immediately with plenty of<br/>water. Remove contaminated clothing. Get medical attention if irritation persists after washing.

 Eye contact
 Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific recommendations. If in doubt, get medical attention promptly.

## SECTION 5: Firefighting measures

5.1. Extinguishing media		
Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	

5.2. Special hazards arising fro	om the substance or mixture		
Specific hazards	Toxic gases or vapours.		
5.3. Advice for firefighters			
Protective actions during firefighting	Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water.		
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.		
SECTION 6: Accidental releas	e measures		
6.1. Personal precautions, pro	tective equipment and emergency procedures		
Personal precautions	Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.		
6.2. Environmental precaution	<u>S</u>		
Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.		
6.3. Methods and material for	containment and cleaning up		
Methods for cleaning up	Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.		
6.4. Reference to other section	ns		
Reference to other sections	For personal protection, see Section 8.		
SECTION 7: Handling and sto	rage		
7.1. Precautions for safe handling			
Usage precautions	Avoid inhalation of vapours. Avoid spilling. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.		
7.2. Conditions for safe storag	e, including any incompatibilities		
Storage precautions	Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep containers upright.		
7.3. Specific end use(s)			
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.		
Usage description	Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon		
	as possible.		

## 5.2. Special hazards arising from the substance or mixture

8.1. Control parameters

### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

## 2-METHYLPROPAN-1-OL

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m<sup>3</sup>

### 1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m<sup>3</sup> Sk

#### **TRIZINC BIS(ORTHOPHOSPHATE)**

Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup> WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

### XYLENE (CAS: 1330-20-7)

DNEL	Consumer - Oral; Long term systemic effects: 1.6 mg/kg/day Consumer - Dermal; Long term systemic effects: 108 mg/kg/day Consumer - Inhalation; Long term systemic effects: 14.8 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 180 mg/kg/day Industry - Inhalation; Long term systemic effects: 77 mg/m <sup>3</sup> Industry - Inhalation; Short term local effects: 289 mg/m <sup>3</sup>
PNEC	<ul> <li>Fresh water; 0.327 mg/l</li> <li>marine water; 0.327 mg/l</li> <li>Intermittent release; 0.327 mg/l</li> <li>Sediment (Freshwater); 12.46 mg/kg</li> <li>Sediment (Marinewater); 12.46 mg/kg</li> <li>Soil; 2.31 mg/kg</li> <li>STP; 6.58 mg/kg</li> </ul>
	2-METHYLPROPAN-1-OL (CAS: 78-83-1)
DNEL	Workers - Inhalation; Long term local effects: 310 mg/m <sup>3</sup> Consumer - Inhalation; Short term local effects: 55 mg/m <sup>3</sup>
	1-METHOXY-2-PROPANOL (CAS: 107-98-2)
DNEL	Workers - Inhalation; Short term local effects: 553.5 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 183 mg/kg/day Workers - Inhalation; Long term systemic effects: 369 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 78 mg/kg/day Consumer - Inhalation; Long term systemic effects: 43.9 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 33 mg/kg/day
PNEC	<ul> <li>Fresh water; 10 mg/l</li> <li>marine water; 1 mg/l</li> <li>Intermittent release; 100 mg/l</li> <li>STP; 100 mg/l</li> <li>Sediment (Freshwater); 52.3 mg/kg</li> <li>Sediment (Marinewater); 5.2 mg/kg</li> <li>Soil; 4.59 mg/kg</li> </ul>

## TRIZINC BIS(ORTHOPHOSPHATE) (CAS: 7779-90-0)

DNEL	- Inhalation; : 1.0 soluble Zn mg/m³
	Consumer - Oral; Long term systemic effects: 0.83 mg/kg/day
	- Inhalation; : 5.0 insoluble Zn mg/m³
	Consumer - Inhalation; Long term systemic effects: 2.5 mg/m <sup>3</sup>
	Professional - Inhalation; Long term systemic effects: 5 mg/m <sup>3</sup>
	Consumer - Dermal; Long term systemic effects: 83 mg/kg/day
	Professional - Dermal; Long term systemic effects: 83 mg/kg/day
PNEC	- Fresh water; 0.02 Zn mg/l
	- marine water; 0.006 Zn mg/l
	- Sediment (Freshwater); 117.8 mg/kg
	- Sediment (Marinewater); 56.5 Zn mg/kg
	- Soil; 35.6 Zn mg/kg

- STP; 0.1 Zn mg/l

## 8.2. Exposure controls

Protective equipment







<u> </u>	
Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.
Personal protection	Unprotected persons should be kept away from treated areas.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
Hand protection	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Viton rubber (fluoro rubber). Thickness: > 0.2 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. or Polyvinyl alcohol (PVA). Thickness: 0.2 - 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.
Other skin and body protection	Wear appropriate clothing to prevent reasonably probable skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
Respiratory protection	Respiratory protection may be required if excessive airborne contamination occurs. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3).
SECTION 9: Physical and ch	emical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid	
Colour	Grey. or Red.	
Odour	Aromatic. Solvent.	
Odour threshold	No information available.	
рН	Not applicable.	
Melting point	Not applicable.	
Initial boiling point and range	137 (Xylene)°C	
Flash point	> 23°C < 60°C Closed cup.	
Evaporation rate	Not determined.	
Evaporation factor	Not determined.	
Flammability (solid, gas)	Not determined.	
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.1 (xylene) g/100 g Upper flammable/explosive limit: 7.0 (xylene) g/100 g	
Other flammability	Not determined.	
Vapour pressure	1.1 (Xylene) kPa @ °C	
Vapour density	heavier than air	
Relative density	~1.10 - 1.30 depending on colour @ @ 20C°C	
Bulk density	Not applicable.	
Solubility(ies)	Soluble in the following materials: Aromatic solvents.	
Partition coefficient	Not determined.	
Auto-ignition temperature	270 (Xylene)°C	
Decomposition Temperature	Not determined.	
Viscosity	1.0 - 4.0 (ICI Cone & Plate) P @ 25°C	
Explosive properties	Not determined.	
Explosive under the influence of a flame	Not considered to be explosive.	
Oxidising properties	Does not meet the criteria for classification as oxidising.	
9.2. Other information		
Volatility	approx. 40% when mixed with activator	
Volatile organic compound	EU: (cat A/j): 500 g/l 2010. This product contains a maximum VOC content of <500 (when mixed) g/litre.	
SECTION 10: Stability and rea	activity	
10.1. Reactivity		
Reactivity	There are no known reactivity hazards associated with this product.	
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recommended.	
10.3. Possibility of hazardous reactions		

Possibility of hazardous reactions	Will not occur
10.4. Conditions to avoid	
Conditions to avoid	Not known.
10.5. Incompatible materials	
Materials to avoid	Strong acids. Alkalis - inorganic. Amines. Mercaptans (thiols).
10.6. Hazardous decompositio	on products
Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
SECTION 11: Toxicological int	formation
11.1. Information on toxicologi	cal effects
Toxicological effects	No data recorded.
Acute toxicity - dermal ATE dermal (mg/kg)	1,100.0
Acute toxicity - inhalation ATE inhalation (vapours mg/l)	11.0
Aspiration hazard Aspiration hazard	Kinematic viscosity <= 20.5 mm2/s.
General information	The product contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	May cause inhalation hypersensitivity (occupational asthma) in sensitive individuals.
Ingestion	Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Irritating to skin. May cause sensitisation by skin contact.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
Acute and chronic health hazards	May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.
Route of exposure	Inhalation Skin absorption. Ingestion. Skin and/or eye contact.
Medical considerations	Skin disorders and allergies.
Toxicological information on in	gredients.

## XYLENE

Acute toxicity - oral	
Acute toxicity oral (LD50	3,523.0
mg/kg)	
Species	Rat

ATE oral (mg/kg)	3,523.0
Acute toxicity - dermal	
ATE dermal (mg/kg)	1,100.0
Acute toxicity - inhalation	
ATE inhalation (vapours mg/l)	11.0
Serious eye damage/irritati	on
Serious eye damage/irritation	Severely irritating to skin. Irritation of eyes is assumed. No testing is needed.
Respiratory sensitisation	
Respiratory sensitisation	Not sensitising.
Skin sensitisation	
Skin sensitisation	Not sensitising.
Carcinogenicity	
Carcinogenicity	There is no evidence that the product can cause cancer.
Reproductive toxicity	
Reproductive toxicity - fertility	This substance has no evidence of toxicity to reproduction.
Aspiration hazard	
Aspiration hazard	Kinematic viscosity <= 20.5 mm2/s.
Inhalation	Harmful by inhalation.
Ingestion	Pneumonia may be the result if vomited material containing solvents reaches the lungs.
Skin contact	Harmful in contact with skin.
Eye contact	May cause severe eye irritation.
Target organs	Central nervous system Liver
	2-METHYLPROPAN-1-OL
Acute toxicity - oral	
Acute toxicity oral (LD <sub>50</sub> mg/kg)	2,830.0
Species	Rat
ATE oral (mg/kg)	2,830.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅ mg/kg)	2,100.0
Species	Rat
ATE dermal (mg/kg)	2,100.0

Skin corrosion/irritation	
Animal data	Non Corrosive to skin.
Skin sensitisation	
Skin sensitisation	Not sensitising.
Germ cell mutagenicity	
Genotoxicity - in vivo	Data lacking.
Carcinogenicity	
Carcinogenicity	No evidence of carcinogenicity in animal studies
Reproductive toxicity	
Reproductive toxicity - development	Data lacking.
Inhalation	Irritating to respiratory system.
Eye contact	May cause severe eye irritation.
	1-METHOXY-2-PROPANOL
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	4,016.0
Species	Rat
ATE oral (mg/kg)	4,016.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	2,100.0
Species	Rat
ATE dermal (mg/kg)	2,100.0
Skin corrosion/irritation	
Animal data	Non Corrosive to skin.
Respiratory sensitisation	
Respiratory sensitisation	Not sensitising.
Germ cell mutagenicity	
Genotoxicity - in vivo	Data lacking.
Carcinogenicity	
Carcinogenicity	No evidence of carcinogenicity in animal studies
Reproductive toxicity	
Reproductive toxicity - development	Data lacking.
Specific target organ toxicit	y - repeated exposure
STOT reported evenesure	Not determined

STOT - repeated exposure Not determined.

# 515/Q113 - 2 PACK ZINC PHOSPHATE PRIMER - BASE FOR RED & WHITE

## TRIZINC BIS(ORTHOPHOSPHATE)

	Acute toxicity - oral	
	Acute toxicity oral (LD₅₀ mg/kg)	5,100.0
	Species	Rat
	ATE oral (mg/kg)	5,100.0
	Acute toxicity - inhalation	
	Notes (inhalation LC₅₀)	Not irritating
	Skin corrosion/irritation	
	Animal data	Not irritating.
	Serious eye damage/irritati	on
	Serious eye damage/irritation	Not irritating.
	Respiratory sensitisation	
	Respiratory sensitisation	Not sensitising.
	Skin sensitisation	
	Skin sensitisation	Not sensitising.
	Germ cell mutagenicity	
	Genotoxicity - in vitro	Does not contain any substances known to be mutagenic.
	Carcinogenicity	
	Carcinogenicity	There is no evidence that the product can cause cancer.
	Reproductive toxicity	
	Reproductive toxicity - fertility	This substance has no evidence of toxicity to reproduction.
	Specific target organ toxicity - single exposure	
	STOT - single exposure Not classified as a specific target organ toxicant after a single exposure	
	Specific target organ toxicit	y - repeated exposure
	STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
	General information	No specific health hazards known.
<b>SECTION 1</b>	2: Ecological information	
Ecotoxicity	There ar	e no data on the ecotoxicity of this product.
Ecological i	nformation on ingredients.	
		XYLENE
	Ecotoxicity	The product is not expected to be hazardous to the environment.
12.1. Toxici	<u>v</u>	
Toxicity	Aquatic	Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

#### Ecological information on ingredients.

XYLENE Acute aquatic toxicity Acute toxicity - fish LC₅₀, 96 hours: 2.6 mg/l, Fish Acute toxicity - aquatic EC50, 48 hours: 3.62 mg/l, Daphnia magna invertebrates Acute toxicity - aquatic IC50, 72 hours: 3.2 mg/l, Algae plants 2-METHYLPROPAN-1-OL Acute aquatic toxicity Acute toxicity - fish LC50, 96 hours: 1430 mg/l, Fish Acute toxicity - aquatic EC50, 48 hours: 1100 mg/l, Daphnia magna invertebrates Acute toxicity - aquatic EC50, 72 hours: 593 mg/l, Pseudokirchneriella subcapitata plants Acute toxicity -IC<sub>50</sub>, 16 hours: >1000 mg/l, Activated sludge microorganisms 1-METHOXY-2-PROPANOL Acute aquatic toxicity Acute toxicity - fish Based on available data the classification criteria are not met. Acute toxicity - aquatic EC<sub>50</sub>, 48 hours: 23300 mg/l, Daphnia magna invertebrates Acute toxicity - aquatic EC50, : >1000 mg/l, Algae plants Acute toxicity -IC<sub>50</sub>, 3 hours: >1000 mg/l, Activated sludge microorganisms TRIZINC BIS(ORTHOPHOSPHATE) Acute aquatic toxicity  $0.1 < L(E)C50 \le 1$ LE(C)50 M factor (Acute) 1 LC50, 96 hours: Oncorhynchus mykiss 0.14 - 0.26 Zn2+ mg/l, Fish Acute toxicity - fish Acute toxicity - aquatic EC<sub>50</sub>, 48 hours: Daphnia magna 0.04 - 0.86 Zn2+ mg/l, Daphnia magna invertebrates Acute toxicity - aquatic EC<sub>50</sub>, 72 hours: 0.136 - 0.15 Zn2+ mg/l, Selenastrum capricornutum plants IC50, 72 hours: Desmodesmus subspicatus <0.3 mg/l, Algae Chronic aquatic toxicity NOEC 0.01 < NOEC ≤ 0.1 Degradability Non-rapidly degradable

M factor (Chronic)

12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

1

Ecological information on ingredients.

#### XYLENE

Persistence and The product is readily biodegradable. degradability

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

#### **XYLENE**

Partition coefficient

#### **TRIZINC BIS(ORTHOPHOSPHATE)**

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

**Mobility** The product is insoluble in water. Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB** This product does not contain any substances classified as PBT or vPvB. assessment

log Kow: 3.12 - 3.2

Ecological information on ingredients.

#### XYLENE

**Results of PBT and vPvB** This substance is not classified as PBT or vPvB according to current EU criteria. assessment

#### TRIZINC BIS(ORTHOPHOSPHATE)

**Results of PBT and vPvB** This substance is not classified as PBT or vPvB according to current EU criteria. assessment

### 12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

#### **TRIZINC BIS(ORTHOPHOSPHATE)**

Other adverse effects Not available.

SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information	Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. DO NOT reuse containers containing residual product without commercial cleaning
Waste class	When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

## **SECTION 14: Transport information**

General	This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR
	and IMDG.

### 14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

## 14.2. UN proper shipping name

Proper shipping name	PAINT OR PAINT RELATED MATERIAL
(ADR/RID)	

Proper shipping name (IMDG) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT OR PAINT RELATED MATERIAL

3

14.3. Transport hazard class(es)	
ADR/RID class	3
IMDG class	3

#### **Transport labels**



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS	F-E, S-E

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16
	December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	<ul> <li>ATE: Acute Toxicity Estimate.</li> <li>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</li> <li>CAS: Chemical Abstracts Service.</li> <li>DNEL: Derived No Effect Level.</li> <li>GHS: Globally Harmonized System.</li> <li>IATA: International Air Transport Association.</li> <li>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</li> <li>IMDG: International Maritime Dangerous Goods.</li> <li>LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).</li> <li>PBT: Persistent, Bioaccumulative and Toxic substance.</li> <li>PNEC: Predicted No Effect Concentration.</li> <li>REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</li> <li>vPvB: Very Persistent and Very Bioaccumulative.</li> <li>EC<sub>50</sub>: 50% of maximal Effective Concentration.</li> </ul>
Classification abbreviations and acronyms	Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Eye Dam. = Serious eye damage Eye Irrit. = Eye irritation Resp. Sens. = Respiratory sensitisation Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure

Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 To include additional colours
Issued by	Technical Dept. (P.E.)
Revision date	05/11/2019
Revision	6.1
Supersedes date	28/11/2018
SDS number	10844
SDS status	Approved.
Hazard statements in full	<ul> <li>H226 Flammable liquid and vapour.</li> <li>H312 Harmful in contact with skin.</li> <li>H315 Causes skin irritation.</li> <li>H318 Causes serious eye damage.</li> <li>H332 Harmful if inhaled.</li> <li>H335 May cause respiratory irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> <li>H400 Very toxic to aquatic life.</li> <li>H410 Very toxic to aquatic life with long lasting effects.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> </ul>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.