



## SAFETY DATA SHEET

### 440/F158 - RED OXIDE PRIMER

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name 440/F158 - RED OXIDE PRIMER

Product number 440/F158/65

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

Uses advised against No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

Supplier TEAL & MACKRILL LIMITED  
LOCKWOOD STREET  
HULL  
HU2 0HN

+44(0)1482 320194(T)

+44(0)1482 219266(F)

info@teamac.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, email:  
info@teamac.co.uk

##### 1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 10589

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)


Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336

Environmental hazards Not Classified

##### 2.2. Label elements

Pictogram



Signal word Warning

## 440/F158 - RED OXIDE PRIMER

|   |   |
|---|---|
| <b>Hazard statements</b>                      | H226 Flammable liquid and vapour.<br>H336 May cause drowsiness or dizziness.  |
| <b>Precautionary statements</b>               | P101 If medical advice is needed, have product container or label at hand.<br>P102 Keep out of reach of children.<br>P261 Avoid breathing vapour/ spray.<br>P271 Use only outdoors or in a well-ventilated area.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.<br>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.<br>P501 Dispose of contents/ container in accordance with national regulations. |
| <b>Supplemental label information</b>         | EUH066 Repeated exposure may cause skin dryness or cracking.  |
| <b>Contains</b>                               | HYDROCARBONS, C9-C11, <2% AROMATICS   |
| <b>Supplementary precautionary statements</b> | P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br>P403+P233 Store in a well-ventilated place. Keep container tightly closed.  |

### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

|  |  |
|--|--|
| <b>Calcium Carbonate</b>   | <b>30-60%</b>  |
| CAS number: 1317-65-3  | EC number: 215-279-6   |
| <b>Classification</b><br>Not Classified  | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>-                    |
| <b>HYDROCARBONS, C9-C11, &lt;2% AROMATICS</b>  | <b>10-30%</b>  |
| CAS number: —  | EC number: 919-857-5   |
|  | REACH registration number: 01-2119463258-33-XXXX                         |
| <b>Classification</b><br>Flam. Liq. 3 - H226<br>STOT SE 3 - H336<br>Asp. Tox. 1 - H304 | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>Xn;R65. R10,R66,R67. |
| <b>Red Iron Oxide</b>  | <b>1-5%</b>  |
| CAS number: 1309-37-1  |  |
| <b>Classification</b><br>Not Classified  | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>-                    |
| <b>Barium Sulphate</b>   | <b>1-5%</b>  |
| CAS number: 7727-43-7  | EC number: 231-784-4   |
|  | REACH registration number: 01-2119491274-35-0001                         |
| <b>Classification</b><br>Not Classified  | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>-                    |

## 440/F158 - RED OXIDE PRIMER

|                          |   |  |     |
|--------------------------|---|--|-----|
| 2-METHYLPENTANE-2,4-DIOL |   |  | <1% |
| CAS number: 107-41-5     | EC number: 203-489-0                      |  |     |
| Classification           | Classification (67/548/EEC or 1999/45/EC) |  |     |
| Skin Irrit. 2 - H315     | Xi;R36/38                                 |  |     |
| Eye Irrit. 2 - H319      |   |  |     |

|                      |   |  |     |
|----------------------|---|--|-----|
| PHTHALIC ANHYDRIDE   |   |  | <1% |
| CAS number: 85-44-9  | EC number: 201-607-5                      | REACH registration number: 01-2119457017-41-0000 |     |
| Classification       | Classification (67/548/EEC or 1999/45/EC) |  |     |
| Acute Tox. 4 - H302  | Xn;R22 R42/43 Xi;R37/38,R41               |  |     |
| Skin Irrit. 2 - H315 |   |  |     |
| Eye Dam. 1 - H318    |   |  |     |
| Resp. Sens. 1 - H334 |   |  |     |
| Skin Sens. 1 - H317  |   |  |     |
| STOT SE 3 - H335     |   |  |     |

|                                 |   |  |     |
|---------------------------------|---|--|-----|
| Dipropylene Glycol Methyl Ether |   |  | <1% |
| CAS number: 34590-94-8          | EC number: 252-104-2                      | REACH registration number: 01-2119450011-60-XXXX |     |
| Classification                  | Classification (67/548/EEC or 1999/45/EC) |  |     |
| Not Classified                  | -   |  |     |

|                            |   |  |     |
|----------------------------|---|--|-----|
| 2,6-Di-tert-butyl-p-cresol |   |  | <1% |
| CAS number: 128-37-0       | EC number: 204-881-4                      | REACH registration number: 01-2119565113-46-xxxx |     |
| M factor (Acute) = 1       |   |  |     |
| Classification             | Classification (67/548/EEC or 1999/45/EC) |  |     |
| Aquatic Acute 1 - H400     | N;R50/53.                                 |  |     |
| Aquatic Chronic 1 - H410   |   |  |     |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments**      The product contains organic solvents.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

|                            |  |
|----------------------------|--|
| <b>General information</b> | Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.   |
| <b>Inhalation</b>          | Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. |

## 440/F158 - RED OXIDE PRIMER

|                                   |   |
|-----------------------------------|---|
| <b>Ingestion</b>                  | Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. |
| <b>Skin contact</b>               | Rinse with water.   |
| <b>Eye contact</b>                | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.   |
| <b>Protection of first aiders</b> | First aid personnel should wear appropriate protective equipment during any rescue.   |

### 4.2. Most important symptoms and effects, both acute and delayed

|                            |   |
|----------------------------|---|
| <b>General information</b> | See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.                |
| <b>Inhalation</b>          | Prolonged inhalation of high concentrations may damage respiratory system. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. |
| <b>Ingestion</b>           | Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.                                       |
| <b>Skin contact</b>        | Prolonged contact may cause dryness of the skin. Discoloration of the skin.   |
| <b>Eye contact</b>         | May cause temporary eye irritation.   |

### 4.3. Indication of any immediate medical attention and special treatment needed

|                             |                        |
|-----------------------------|------------------------|
| <b>Notes for the doctor</b> | Treat symptomatically. |
|-----------------------------|------------------------|

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                                       |  |
|---------------------------------------|--|
| <b>Suitable extinguishing media</b>   | Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. |
| <b>Unsuitable extinguishing media</b> | Do not use water jet as an extinguisher, as this will spread the fire.   |

### 5.2. Special hazards arising from the substance or mixture

|                                      |   |
|--------------------------------------|---|
| <b>Specific hazards</b>              | FLAMMABLE. Solvent vapours may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up. |
| <b>Hazardous combustion products</b> | Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.  |

### 5.3. Advice for firefighters

|  |   |
|--|---|
| <b>Protective actions during firefighting</b>        | Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. |
| <b>Special protective equipment for firefighters</b> | Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.  |

## 440/F158 - RED OXIDE PRIMER

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Provide adequate ventilation.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

**Advice on general occupational hygiene** Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

**Storage class** Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

#### 7.3. Specific end use(s)

## 440/F158 - RED OXIDE PRIMER

|                            |   |
|----------------------------|---|
| <b>Specific end use(s)</b> | The identified uses for this product are detailed in Section 1.2.   |
| <b>Usage description</b>   | Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. |

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **Calcium Carbonate**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

##### **Red Iron Oxide**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

Short-term exposure limit (15-minute): WEL 10 mg/m<sup>3</sup>  
as Fe

##### **Barium Sulphate**

Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m<sup>3</sup> respirable dust

##### **2-METHYLPENTANE-2,4-DIOL**

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 25 ppm 123 mg/m<sup>3</sup>

##### **PHTHALIC ANHYDRIDE**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup>(Sen)

Short-term exposure limit (15-minute): WEL 12 mg/m<sup>3</sup>(Sen)

##### **Dipropylene Glycol Methyl Ether**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 308 mg/m<sup>3</sup>  
Sk

##### **2,6-Di-tert-butyl-p-cresol**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

Sk = Can be absorbed through skin.

#### HYDROCARBONS, C9-C11, <2% AROMATICS

##### **DNEL**

Consumer - Oral; Long term systemic effects: 300 mg/kg/day

Industry - Inhalation; Long term systemic effects: 1500 mg/m<sup>3</sup>

Industry - Dermal; Long term systemic effects: 300 mg/kg/day

Consumer - Dermal; Long term systemic effects: 300 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 900 mg/m<sup>3</sup>

##### **PNEC**

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

#### Dipropylene Glycol Methyl Ether (CAS: 34590-94-8)

## 440/F158 - RED OXIDE PRIMER

|             |   |
|-------------|---|
| <b>DNEL</b> | Industry - Dermal; Long term : 65 mg/kg/day               |
|             | Industry - Inhalation; Long term : 310 mg/m <sup>3</sup>  |
|             | Consumer - Dermal; Long term : 15 mg/kg/day               |
|             | Consumer - Inhalation; Long term : 37.2 mg/m <sup>3</sup> |
|             | Consumer - Oral; Long term : 1.67 mg/kg/day               |

|             |                                    |
|-------------|------------------------------------|
| <b>PNEC</b> | Fresh water; 19 mg/l               |
|             | marine water; 1.9 mg/l             |
|             | STP; 4168 mg/l                     |
|             | Sediment (Freshwater); 70.2 mg/kg  |
|             | Sediment (Marinewater); 7.02 mg/kg |
|             | Soil; 2.74 mg/kg                   |
|             | Intermittent release; 19 mg/l      |

### 2,6-Di-tert-butyl-p-cresol (CAS: 128-37-0)

|             |  |
|-------------|--|
| <b>DNEL</b> | Industry - Dermal; : 0.5 mg/kg/day     |
|             | Industry - Inhalation; : 3.5 mg/kg/day |

|             |                                |
|-------------|--------------------------------|
| <b>PNEC</b> | - Fresh water; 0.000199 mg/l   |
|             | - Sediment; 0.0996 mg/l        |
|             | - Soil; 0.04769 mg/l           |
|             | - marine water; 0.0000199 mg/l |

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

### Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.31 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

### Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

## 440/F158 - RED OXIDE PRIMER

|  |   |
|--|---|
| <b>Hygiene measures</b>                | Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.   |
| <b>Respiratory protection</b>          | Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Gas filter, type A2. |
| <b>Environmental exposure controls</b> | Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.   |

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |                                  |
|---|----------------------------------|
| <b>Appearance</b>                                   | Viscous liquid. Coloured liquid. |
| <b>Colour</b>                                       | Red.                             |
| <b>Odour</b>  | Organic solvents.                |
| <b>Odour threshold</b>                              | Not determined.                  |
| <b>pH</b>   | Technically not feasible.        |
| <b>Melting point</b>                                | Not determined.                  |
| <b>Initial boiling point and range</b>              | Not determined.                  |
| <b>Flash point</b>                                  | 38 approx. °C Closed cup.        |
| <b>Evaporation rate</b>                             | Not determined.                  |
| <b>Evaporation factor</b>                           | Not determined.                  |
| <b>Upper/lower flammability or explosive limits</b> | : 0.8                            |
| <b>Other flammability</b>                           | Not determined.                  |
| <b>Vapour pressure</b>                              | Not determined.                  |
| <b>Vapour density</b>                               | heavier than air                 |
| <b>Relative density</b>                             | 1.55 approx. @ @ 20°C            |
| <b>Solubility(ies)</b>                              | Insoluble in water               |
| <b>Partition coefficient</b>                        | No information available.        |
| <b>Auto-ignition temperature</b>                    | Not determined.                  |
| <b>Decomposition Temperature</b>                    | Not determined.                  |
| <b>Viscosity</b>                                    | 4.5 (Rotathinner) P @ 25°C       |
| <b>Explosive properties</b>                         | Not determined.                  |



## 440/F158 - RED OXIDE PRIMER

**Explosive under the influence of a flame** Not considered to be explosive.

**Oxidising properties** Not determined.

### 9.2. Other information

**Volatile organic compound** This product contains a maximum VOC content of <500 g/litre.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** See the other subsections of this section for further details.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** The following materials may react strongly with the product: Oxidising agents.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.

### 10.5. Incompatible materials

**Materials to avoid** Oxidising materials. Acids - oxidising.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** There is no data available on the mixture itself. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

#### Carcinogenicity

**IARC carcinogenicity** None of the ingredients are listed or exempt.

#### Inhalation

Prolonged inhalation of high concentrations may damage respiratory system. During application and drying, solvent vapours will be emitted. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

#### Ingestion

Symptoms following overexposure may include the following: Nausea, vomiting. Diarrhoea.

#### Skin contact

The product contains organic solvents. May be absorbed through the skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

#### Eye contact

May cause temporary eye irritation.

#### Medical considerations

Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

### Toxicological information on ingredients.

**440/F158 - RED OXIDE PRIMER****HYDROCARBONS, C9-C11, <2% AROMATICS****Acute toxicity - oral**

Acute toxicity oral (LD<sub>50</sub> mg/kg) 5,100.0

Species Rat

ATE oral (mg/kg) 5,100.0

**Acute toxicity - dermal**

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 5,100.0

Species Rabbit

ATE dermal (mg/kg) 5,100.0

**Acute toxicity - inhalation**

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 5,100.0

Species Rat

ATE inhalation (vapours mg/l) 5,100.0

**Skin corrosion/irritation**

Skin corrosion/irritation Not irritating.

**Serious eye damage/irritation**

Serious eye damage/irritation Not irritating.

**Respiratory sensitisation**

Respiratory sensitisation Not sensitising.

**Skin sensitisation**

Skin sensitisation Not sensitising.

**Germ cell mutagenicity**

Genotoxicity - in vitro Chromosome aberration: Negative. This substance has no evidence of mutagenic properties.

**Carcinogenicity**

Carcinogenicity Based on available data the classification criteria are not met.

**Reproductive toxicity**

Reproductive toxicity - fertility Fertility: -, Inhalation, Rat This substance has no evidence of toxicity to reproduction.

Reproductive toxicity - development Developmental toxicity: -, Inhalation, Rat This substance has no evidence of toxicity to reproduction.

**Specific target organ toxicity - repeated exposure**

STOT - repeated exposure Not available.

**Aspiration hazard**

**440/F158 - RED OXIDE PRIMER**

|                          |   |
|--------------------------|---|
| <b>Aspiration hazard</b> | Kinematic viscosity <= 20.5 mm <sup>2</sup> /s.                                 |
| <b>Inhalation</b>        | Vapours may cause drowsiness and dizziness. Central nervous system depression.  |
| <b>Ingestion</b>         | Harmful: danger of serious damage to health by prolonged exposure if swallowed. |
| <b>Skin contact</b>      | Product has a defatting effect on skin. May cause allergic contact eczema.      |
| <b>Eye contact</b>       | No specific health hazards known.   |
| <b>Route of exposure</b> | Inhalation Dermal   |

**SECTION 12: Ecological information**

**Ecotoxicity** There is no data available on the mixture itself. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly.

**12.1. Toxicity****Ecological information on ingredients.****HYDROCARBONS, C9-C11, <2% AROMATICS****Acute aquatic toxicity**

|   |  |
|---|--|
| <b>Acute toxicity - fish</b>                  | LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)<br>Substance did not cause acute toxicity to fish                 |
| <b>Acute toxicity - aquatic invertebrates</b> | Substance did not cause acute toxicity to the freshwater invertebrates<br>EC <sub>50</sub> , 48 hours: >1000 mg/l, Daphnia magna   |
| <b>Acute toxicity - aquatic plants</b>        | EC <sub>50</sub> , > 72 hours: 1000 mg/l, Freshwater algae<br>Substance did not cause acute toxicity to the freshwater green algae |
| <b>Acute toxicity - microorganisms</b>        | EC <sub>50</sub> , >: 100 mg/l, Activated sludge   |

**Chronic aquatic toxicity**

|   |  |
|---|--|
| <b>Chronic toxicity - fish early life stage</b> | NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout) |
| <b>Chronic toxicity - aquatic invertebrates</b> | NOEC, 28 days: 0.23 mg/l, Daphnia magna                        |

**12.2. Persistence and degradability**

**Persistence and degradability** There are no data on the degradability of this product.

**Ecological information on ingredients.****HYDROCARBONS, C9-C11, <2% AROMATICS**

|                                      |   |
|--------------------------------------|---|
| <b>Persistence and degradability</b> | The product is readily biodegradable.   |
| <b>Phototransformation</b>           | Oxidises rapidly by photo-chemical reactions in air   |
| <b>Biodegradation</b>                | - 80 Degradation (%): 28 days<br>Test - 301F Ready Biodegradability - Manometric Respiratory Test |

**12.3. Bioaccumulative potential**

**Bioaccumulative potential** No data available on bioaccumulation.

## 440/F158 - RED OXIDE PRIMER

**Partition coefficient** No information available.

### Ecological information on ingredients.

#### HYDROCARBONS, C9-C11, <2% AROMATICS

**Bioaccumulative potential** The product contains potentially bioaccumulating substances.

**Partition coefficient** log Pow: 5 - 6.7

### 12.4. Mobility in soil

**Mobility** Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

### Ecological information on ingredients.

#### HYDROCARBONS, C9-C11, <2% AROMATICS

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Readily absorbed into soil.

**Adsorption/desorption coefficient** Not available.

**Surface tension** 24.5 mN/m @ 20°C

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### Ecological information on ingredients.

#### HYDROCARBONS, C9-C11, <2% AROMATICS

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

**Other adverse effects** None known.

### Ecological information on ingredients.

#### HYDROCARBONS, C9-C11, <2% AROMATICS

**Other adverse effects** Not known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

## 440/F158 - RED OXIDE PRIMER

|                         |  |
|-------------------------|--|
| <b>Disposal methods</b> | Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.   |
| <b>Waste class</b>      | When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging). |

### SECTION 14: Transport information

|                |   |
|----------------|---|
| <b>General</b> | For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section. |
|----------------|---|

#### 14.1. UN number

|                  |      |
|------------------|------|
| UN No. (ADR/RID) | 1263 |
| UN No. (IMDG)    | 1263 |
| UN No. (ICAO)    | 1263 |

#### 14.2. UN proper shipping name

|                                |  |
|--------------------------------|--|
| Proper shipping name (ADR/RID) | PAINT, Contains Low Aromatic White Spirit, Class 3, PG III, (38 °C c.c.) |
|--------------------------------|--|

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

#### 14.3. Transport hazard class(es)

|               |   |
|---------------|---|
| ADR/RID class | 3 |
| IMDG class    | 3 |

#### Transport labels



#### 14.4. Packing group

|                       |     |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group    | III |
| ICAO packing group    | III |

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

#### 14.6. Special precautions for user

## 440/F158 - RED OXIDE PRIMER

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**EmS** F-E, S-E

**Tunnel restriction code** (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78  
and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Commission Regulation (EU) No 2015/830 of 28 May 2015.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### Inventories

#### EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

## SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.  
IATA: International Air Transport Association.  
ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.  
IMDG: International Maritime Dangerous Goods.  
CAS: Chemical Abstracts Service.  
ATE: Acute Toxicity Estimate.  
LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.  
LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).  
EC<sub>50</sub>: 50% of maximal Effective Concentration.  
PBT: Persistent, Bioaccumulative and Toxic substance.  
vPvB: Very Persistent and Very Bioaccumulative.

### Classification abbreviations and acronyms

Acute Tox. = Acute toxicity  
Aquatic Acute = Hazardous to the aquatic environment (acute)  
Aquatic Chronic = Hazardous to the aquatic environment (chronic)  
Asp. Tox. = Aspiration hazard  
Flam. Liq. = Flammable liquid  
STOT RE = Specific target organ toxicity-repeated exposure  
STOT SE = Specific target organ toxicity-single exposure

**440/F158 - RED OXIDE PRIMER**

|   |   |
|---|---|
| <b>Classification procedures according to Regulation (EC) 1272/2008</b> | STOT SE 3 - H336, STOT RE 1 - H372: Calculation method. Aquatic Chronic 3 - H412: Calculation method. Flam. Liq. 3 - H226: Expert judgement.  |
| <b>Training advice</b>  | Read and follow manufacturer's recommendations. Only trained personnel should use this material.  |
| <b>Revision comments</b>  | Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.   |
| <b>Issued by</b>  | Technical Dept. (P.E.)  |
| <b>Revision date</b>  | 20/06/2019  |
| <b>Revision</b>   | 9.1   |
| <b>Supersedes date</b>  | 25/07/2018  |
| <b>SDS number</b>   | 10589   |
| <b>SDS status</b>   | Approved.   |
| <b>Hazard statements in full</b>  | H226 Flammable liquid and vapour.<br>H302 Harmful if swallowed.<br>H304 May be fatal if swallowed and enters airways.<br>H315 Causes skin irritation.<br>H317 May cause an allergic skin reaction.<br>H318 Causes serious eye damage.<br>H319 Causes serious eye irritation.<br>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H400 Very toxic to aquatic life.<br>H410 Very toxic to aquatic life with long lasting effects.<br>EUH208 Contains 2-BUTANONE OXIME. May produce an allergic reaction. |
| <b>Signature</b>  | Initials _____  |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.