



PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

According to Regulation (EC) No 1907/2006, Annex II Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER
Product number 130/M200 AND P105/ - HARDENER
UFI UFI: D7CP-K2E6-300F-6NEY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses HARDENER FOR TWO COMPONENT Primer. and Crack and hole filler

1.3. Details of the supplier of the safety data sheet

Supplier	COO-VAR Lockwood Street HULL UK HU2 0HN +441482328053 (T) +441482219266 (F) info@coo-var.co.uk	TEAL & MACKRILL EU B.V. Zandvoortstraat 69 1976 BN IJMUIDEN THE NETHERLANDS +441482328053 (T) +441482219266 (F) info@coo-var.co.uk
Contact person	Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above	
Manufacturer	TEAL & MACKRILL LIMITED LOCKWOOD STREET HULL HU2 0HN +44(0)1482 320194(T) +44(0)1482 219266(F) info@teamac.co.uk	

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)
SDS No. 10796

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Org. Perox. C - H242
Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 1B - H360
Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 3 - H412

2.2. Label elements

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Hazard pictograms



Signal word

Danger

Hazard statements

H242 Heating may cause a fire.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H360 May damage fertility or the unborn child.
 H400 Very toxic to aquatic life.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust.
 P264 Wash contaminated skin thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

BENZOYL PEROXIDE, Dicyclohexyl phthalate

Supplementary precautionary statements

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P405 Store locked up.
 P420 Store separately.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BENZOYL PEROXIDE		30-60%
CAS number: 94-36-0	EC number: 202-327-6	
M factor (Acute) = 10		
Classification Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Acute 1 - H400	Classification (67/548/EEC or 1999/45/EC) E;R3 O;R7 Xi;R36 R43	
Dicyclohexyl phthalate		30-60%
CAS number: 84-61-7	EC number: 201-545-9	
Classification Skin Sens. 1 - H317 Repr. 1B - H360 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) -	

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Silicon dioxide	1-5%
CAS number: —	
Classification	Classification (67/548/EEC or 1999/45/EC)
Not Classified	-

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. NOTE! Effects may be delayed. Keep affected person under observation. If medical advice is needed, have product container or label at hand. Get medical attention immediately.
Inhalation	Move affected person to fresh air at once. Consult a physician for specific advice. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention immediately.
Skin contact	In case of skin contact wash off with plenty of water (do not allow to dry). Continue to rinse for at least 15 minutes. Remove contaminated clothing immediately and wash skin with soap and water. Wash contaminated clothing before reuse. Get medical attention if irritation persists after washing.
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions. Get medical attention if irritation persists after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	May cause an allergic skin reaction. May cause severe eye irritation. May damage the unborn child.
----------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Symptomatic treatment is advised
-----------------------------	----------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide. Alcohol-resistant foam.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapours which may auto ignite. Burns violently. Flash back possible over considerable distance. Vapours may form explosive mixtures with air. The product will float on water and can be reignited on surface water. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Contain and collect extinguishing water. Do not discharge into drains or watercourses or onto the ground. Dispose of waste and residues in accordance with local authority requirements.
---	--

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Do not use water jet as an extinguisher, as this will spread the fire. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Avoid breathing dust. Avoid generation and spreading of dust. Remove sources of ignition. Follow precautions for safe handling described in this safety data sheet. Never return spills to original container for re-use. Collect and dispose of spillage as indicated in Section 13.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapours which may auto ignite. Clear spills immediately. To clean the floor and all objects contaminated with this material, use plenty of water. Absorb spillage with sand or other inert absorbent. Isolate waste and do not re-use. Use only non-sparking tools. Refer to local regulations for information on disposal/ recovery/ recycling.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Use engineering controls to reduce air contamination to permissible exposure level. Do not breathe dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Take precautionary measures against static discharge. Never return spills to original container for re-use. Provide adequate general and local exhaust ventilation. Confinement must be avoided. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not eat, drink or smoke when using this product. Wash thoroughly after dealing with a spillage. For personal protection, see Section 8. Persons with a history of skin sensitisation problems should not be employed in a situation where skin contact with this product could occur, nor should those with asthma or similar disorders be exposed to the vapour or spray mist. Use explosion-proof electrical equipment. Keep away from combustible materials.
Advice on general occupational hygiene	Keep away from food and drink. When using do not eat, drink or smoke. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Keep container tightly closed and at temperature not exceeding 30°C. Store away from the following materials: Acids. Alkalis. Reducing agents. heavy metal compounds(e.g. accelerators, driers, metal soaps.) Do not allow to dry out.
Storage class	Oxidiser storage.

7.3. Specific end use(s)

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Dicyclohexyl phthalate

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL 15 mg/m³

Silicon dioxide

Long-term exposure limit (8-hour TWA): WEL 2.4 mg/m³ resp.dust

Short-term exposure limit (15-minute): WEL 6 mg/m³ total dust

WEL = Workplace Exposure Limit.

BENZOYL PEROXIDE (CAS: 94-36-0)

DNEL Workers - Inhalation; Long term systemic effects: 11.75 mg/m³
 Workers - Dermal; Long term systemic effects: 6.6 mg/m³
 Consumer - Inhalation; Long term systemic effects: 2.9 mg/m³
 Consumer - Dermal; Long term systemic effects: 3.3 mg/m³
 Consumer - Oral; Long term systemic effects: 1.65 mg/m³

PNEC Fresh water; 0.000602 mg/l
 marine water; 0.000060 mg/l
 Intermittent release; 0.000602 mg/l
 STP; 0.35 mg/l
 Sediment (Freshwater); 0.338 mg/l
 Soil; 0.0758 mg/l

Dicyclohexyl phthalate (CAS: 84-61-7)

DNEL Workers - Inhalation; Long term systemic effects: 35.2 mg/m³
 Workers - Inhalation; Short term systemic effects: 35.2 mg/m³
 Workers - Dermal; Short term systemic effects: 0.5 mg/kg
 Workers - Dermal; Long term systemic effects: 0.5 mg/kg
 Consumer - Inhalation; Short term systemic effects: 0.87 mg/m³
 Consumer - Inhalation; Long term systemic effects: 0.87 mg/m³
 Consumer - Dermal; Long term systemic effects: 0.25 mg/kg
 Consumer - Oral; Long term systemic effects: 0.25 mg/kg

PNEC Fresh water; 0.00362 mg/l
 Intermittent release; 0.0326 mg/l
 marine water; 0.000362 mg/l
 Sediment (Freshwater); 1.06 mg/kg
 Sediment (Marinewater); 0.106 mg/kg
 STP; 10 mg/l
 Soil; 0.21 mg/kg

8.2. Exposure controls

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of dust. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturers' performance data suggest that the optimum glove for use should be: Butyl rubber. Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Thickness: 0.5 mm

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Launder clothes before reuse.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Particulate filter, type P1.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	White / off-white.
Odour	Slight.
Initial boiling point and range	Do not heat°C @
Flash point	above the SADT value°C
Relative density	1.23 @ @ 20 C°C
Solubility(ies)	Insoluble in water
Auto-ignition temperature	SADT 55 C see section 10.°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under the prescribed storage conditions.
------------	---

10.2. Chemical stability

Stability	Stable under the prescribed storage conditions.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Dust may form explosive mixture with air.
------------------------------------	---

10.4. Conditions to avoid

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Conditions to avoid Contact with incompatible substances can cause decomposition at or below the SADT. Confinement must be avoided. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Avoid contact with rust, iron, copper. Contact with incompatible materials such as acids, alkalies, heavy metals and reducing agents will result in hazardous decomposition.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin contact Skin irritation should not occur when used as recommended. May cause sensitisation by skin contact.

Eye contact Irritating to eyes.

Route of exposure Inhalation Skin absorption. Skin and/or eye contact.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 2.0 (poecilla reticulata.) - Dibenzoyl peroxide mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 2.91 mg/l, Daphnia magna

Acute toxicity - microorganisms EC₅₀, ~: 35 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered. Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Disposal methods	Do not discharge into drains or watercourses or onto the ground. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	Ideally this component should be mixed with the appropriate resin base and allowed to react fully producing a solid non hazardous waste.

SECTION 14: Transport information

General	This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.
----------------	---

14.1. UN number

UN No. (ADR/RID)	3106
UN No. (IMDG)	3106
UN No. (ICAO)	3106

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	Organic peroxide type d, solid; (Dibenzoyl peroxide)
--------------------------------	--

Proper shipping name (IMDG)	Organic peroxide type d, solid; (Dibenzoyl peroxide)
-----------------------------	--

Proper shipping name (ICAO)	Organic peroxide type d, solid; (Dibenzoyl peroxide)
-----------------------------	--

14.3. Transport hazard class(es)

ADR/RID class	5.2
ADR/RID classification code	P1
ADR/RID label	Organic Peroxides. Keep away from heat.
IMDG class	5.2
ICAO class/division	5.2

Transport labels



14.4. Packing group

ADR/RID packing group	Not assigned by regulation
IMDG packing group	Not assigned by regulation
ICAO packing group	Not assigned by regulation

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-J, S-R
-----	----------

130/M200&P105 - C.S.P. MORTAR/PRIMER - HARDENER

Hazard Identification Number 539
(ADR/RID)

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.
Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material.

Revision comments Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Correction to classification Addition of EU supplier information Unique Formula Identifier (UFI) added

Issued by Technical Dept. (N.O.)

Revision date 18/01/2021

Revision 8.1

Supersedes date 20/10/2020

SDS number 10796

SDS status Approved.

Hazard statements in full H241 Heating may cause a fire or explosion.
H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360 May damage fertility or the unborn child.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Signature Initials_____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.