

# COO-VAR®

## PAINTS, PRIMERS AND SPECIALISED COATINGS

### SAFETY DATA SHEET

#### 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

Product number 103/Q228/1 - BASE

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses BASE FOR TWO COMPONENT PRIMER

Uses advised against NOT SUITABLE FOR FOR USE IN HOMEWORKER (DIY) APPLICATIONS

##### 1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR  
Lockwood Street  
Hull  
HU2 0HN  
+44 (0) 1482 328053(T)  
+44 (0) 1482 219266(F)  
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

##### 1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 11075

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317


Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) -

Human health The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

Physicochemical When handled correctly, undamaged units represent no danger.

##### 2.2. Label elements

**103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE****Hazard pictograms****Signal word**

Warning

**Hazard statements**

H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H317 May cause an allergic skin reaction.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.  
 P101 If medical advice is needed, have product container or label at hand.  
 P261 Avoid breathing vapour/ spray.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P332+P313 If skin irritation occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P501 Dispose of contents/ container in accordance with national regulations.

**Contains**

REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700), PHENOL FORMALDEHYDE POLYMER GLYCIDYL ETHER, OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

**Supplementary precautionary statements**

P403+P235 Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

This product does not contain any substances classified as PBT or vPvB.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

<b>REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW&lt;=700)</b>		<b>30-60%</b>
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-0006
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

<b>PHENOL FORMALDEHYDE POLYMER GLYCIDYL ETHER</b>		<b>10-30%</b>
CAS number: 28064-14-4		
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Skin Irrit. 2 - H315	Xi;R36/38. N;R51/53. R43.	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		
<b>OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS</b>		<b>5-10%</b>
CAS number: 68609-97-2		REACH registration number: 01-2119485289-22-0005
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Skin Irrit. 2 - H315	R43 Xi;R38	
Skin Sens. 1 - H317		
<b>SOLVENT NAPHTHA, LIGHT AROMATIC( content of benzene &lt;0.1%)</b>		<b>1-5%</b>
CAS number: 64742-95-6		EC number: 265-199-0
		REACH registration number: 01-2119455851-35
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
STOT SE 3 - H335, H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Remove affected person from source of contamination. Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	Get medical attention promptly if symptoms occur after washing.
----------------------------	---

## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific recommendations. If in doubt, get medical attention promptly.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Non flammable at room temperature, but will burn. Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Toxic gases or vapours.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Avoid inhalation of vapours. Avoid spilling. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep containers upright.

#### 7.3. Specific end use(s)

## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.2.
<b>Usage description</b>	Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

#### REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700) (CAS: 25068-38-6)

<b>DNEL</b>	Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day Workers - Inhalation; Long term systemic effects: 12.25 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 8.33 mg/kg/day Workers - Inhalation; Short term systemic effects: 12.25 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 0.75 mg/kg/day Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day Consumer - Dermal; Long term systemic effects: 3.571 mg/kg/day
<b>PNEC</b>	- Fresh water; Long term 0.006 mg/l - Sediment (Freshwater); Long term 0.996 mg/l - STP; Long term 10 mg/l - Soil; Long term 0.196 mg/l - marine water; 0.0006 mg/l - Sediment (Marinewater); 0.0996 mg/l - Water; 0.0018 mg/l

#### 8.2. Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

##### Personal protection

Unprotected persons should be kept away from treated areas.

##### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

##### Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Butyl rubber. Thickness: > 0.5 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. or Nitrile rubber. Thickness: > 0.4 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 240 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

##### Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

<b>Hygiene measures</b>	Use engineering controls to reduce air contamination to permissible exposure level. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
<b>Respiratory protection</b>	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	Clear liquid.
<b>Odour</b>	Slight.
<b>Odour threshold</b>	Not determined.
<b>pH</b>	Technically not feasible.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	>150°C @ 760 mm Hg
<b>Flash point</b>	96°C Closed cup.
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not determined.
<b>Other flammability</b>	Not determined.
<b>Vapour pressure</b>	<0.01 kPa @ °C
<b>Vapour density</b>	heavier than air
<b>Relative density</b>	~ 1.11 @ 20°C
<b>Solubility(ies)</b>	Immiscible with water
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	Kinematic viscosity > 20.5 mm <sup>2</sup> /s.
<b>Explosive properties</b>	Not determined.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not determined.

#### 9.2. Other information

<b>Volatile organic compound</b>	This product contains a maximum VOC content of 198 (mixed unit) g/litre.
----------------------------------	--

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
-------------------	---

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
------------------	---

## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not occur

### 10.4. Conditions to avoid

**Conditions to avoid** Not known.

### 10.5. Incompatible materials

**Materials to avoid** Strong acids. Alkalis - inorganic. Amines. Mercaptans (thiols).

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

**General information** No specific health hazards known.

**Inhalation** May cause respiratory system irritation.

**Ingestion** Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

**Skin contact** Irritating to skin. May cause sensitisation by skin contact.

**Eye contact** Irritating to eyes.

**Acute and chronic health hazards** May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.

**Route of exposure** Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

**Medical considerations** Skin disorders and allergies.

### Toxicological information on ingredients.

#### REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 15,000.0

**Species** Rat

**ATE oral (mg/kg)** 15,000.0

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 23,000.0

**Species** Rat

**ATE dermal (mg/kg)** 23,000.0

## SECTION 12: Ecological information

## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

**Ecotoxicity** There are no data on the ecotoxicity of this product.

### Ecological information on ingredients.

#### REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)

**Ecotoxicity** The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

### 12.1. Toxicity

#### Ecological information on ingredients.

#### REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)

##### Acute aquatic toxicity

**Acute toxicity - fish** LC50, 96 hours: 2.0 mg/l, Leuciscus idus (Golden orfe)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 1.8 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: 11 mg/l, Freshwater algae

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not determined.

### 12.4. Mobility in soil

**Mobility** The product is non-volatile.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** Not determined.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

**General information** Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. DO NOT reuse containers containing residual product without commercial cleaning



## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

<b>Waste class</b>	When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)
--------------------	--

### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

#### 14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains EPOXY RESIN, Class 9, PG III, MARINE POLLUTANT)

**Proper shipping name (IMDG)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains EPOXY RESIN, Class 9, PG III, MARINE POLLUTANT)

**Proper shipping name (ICAO)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains EPOXY RESIN, Class 9, PG III, MARINE POLLUTANT)

#### 14.3. Transport hazard class(es)

ADR/RID class 9

IMDG class 9

ICAO class/division 9

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6. Special precautions for user

EmS F-A S-F

## 103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE

Tunnel restriction code (E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation**

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).  
 Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet**

ATE: Acute Toxicity Estimate.  
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 CAS: Chemical Abstracts Service.  
 DNEL: Derived No Effect Level.  
 GHS: Globally Harmonized System.  
 IATA: International Air Transport Association.  
 ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.  
 IMDG: International Maritime Dangerous Goods.  
 LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).  
 PBT: Persistent, Bioaccumulative and Toxic substance.  
 PNEC: Predicted No Effect Concentration.  
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.  
 vPvB: Very Persistent and Very Bioaccumulative.  
 EC<sub>50</sub>: 50% of maximal Effective Concentration.

**Classification abbreviations and acronyms**

Aquatic Acute = Hazardous to the aquatic environment (acute)  
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)  
 Asp. Tox. = Aspiration hazard  
 Eye Dam. = Serious eye damage  
 Eye Irrit. = Eye irritation  
 Resp. Sens. = Respiratory sensitisation  
 Skin Corr. = Skin corrosion  
 Skin Irrit. = Skin irritation  
 Skin Sens. = Skin sensitisation  
 STOT RE = Specific target organ toxicity-repeated exposure  
 STOT SE = Specific target organ toxicity-single exposure

**Revision comments**

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revisions to Sections (2),(3),(8),(15), and (16) - re-classification of resin components. Corrections to Section 14, Transport Information

**103/Q228 - OIL TOLERANT PRIMER CLEAR - BASE**

<b>Issued by</b>	Technical Dept. (P.E.)
<b>Revision date</b>	12/11/2019
<b>Revision</b>	5.1
<b>Supersedes date</b>	08/02/2019
<b>SDS number</b>	11075
<b>SDS status</b>	Approved.
<b>Hazard statements in full</b>	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
<b>Signature</b>	Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.