



Acrolon™ 7300

High solids acrylic polyurethane finish

Acrolon™ 7300 is an acrylic polyurethane finish for high performance protective coating systems. Available globally, Acrolon™ 7300 can be supplied with a gloss or semi gloss finish in a full range of colours. It provides a high quality finish with excellent gloss and colour retention while reducing VOC emissions due to its high solids content. Boasting extensive third party approvals it is recommended for use across oil and gas, power and infrastructure applications or any other industry facing harsh exposure whilst demanding high durability.



Features & benefits

- Higher solids than average in the market place.
- Global availability.
- Gloss and semi-gloss shades in a single formula.
- Available in a wide range of colours.
- Suitable for shop or site application.
- Fast to handle.
- Excellent aesthetics (smooth film).
- Covering all scenarios of atmospheric corrosion protection of uninsulated steel.
- ISO 12944:2018 approved: C2 to C5 corrosivity categories up to very high durability (>25 years).
- ISO 12944:2018-9 (former ISO 20340) approved: CX corrosivity to maximum durability (>15 years).
- Norsok M-501 Rev 6 approved: System 1 (atmospheric exposure).

Industries covered

Steel fabrication for both shop and on-site with multiple end uses:

- Steel structures
- Offshore platforms
- Storage tanks external areas
- Marine applications
- Steel bridges
- High performance architecture applications.

Key application properties

	Curing times			Pot life			Mix ratio	Volume solids
	@ 10°C	@ 25°C	@ 35°C	@ 10°C	@ 25°C	@ 35°C		
Dry to touch	1.5 hrs	50 mins	40 mins	2.5 hr	2 hrs	1.5 hrs	3:1	68%
Dry to handle	27 hrs	6 hrs	3 hrs					(ASTM D2697-91)

Superior protection

Acrolon™ 7300 provides excellent colour and gloss retention, keeping your structures looking attractive for years, even in highly corrosive environments. It is designed for constructions where a reliable combination of corrosion protection and colour gloss resistance is required.

Extensive certification and approvals coverage

Acrolon™ 7300 is Sherwin-Williams global polyurethane finish of choice for protective and marine applications.

It has been tested to Norsok M-501 Rev 6, ISO 12944:2018 and a range of other local standards.

Acrolon™ 7300 is also approved as a top coat over Sherwin-Williams FIRETEX® range of intumescent passive fire protection coatings, both for cellulosic and hydrocarbon fire scenarios.

Fast throughput

Acrolon™ 7300 develops a damage resistant film suitable for handling in as little as six hours at 25°C depending on the environment, helping to improve productivity.

The polyester modified acrylic resin keeps elasticity on curing avoiding brittleness after drying, often the cause of damage on handling and transportation.

Formulated to lower health and safety impact

Acrolon™ 7300 formulation based is a high solids polyester modified resin, providing performance with low VOC emission and is tin-free and crystalline silica-free reducing health and safety impact.



To learn more, contact us

Europe & Africa: +44 (0)1204 521771 sales.uk@sherwin.com

Middle East & India: +971 4 8840200 sales.me@sherwin.com

North America: +1 800 524 5979

Asia: +8 621 5158 7798

www.protectiveemea.sherwin-williams.com