

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol



SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name	Tracing Plus Line Marker Acrylic Paint Aerosol
Product Inclusion	The document applies to all colour variants within the range of Tracing Plus Line Marker Acrylic Paint Aerosol.
Container Size	750ml

1.2. Relevant identified uses of the substance of mixture and uses advised against

Identified Uses	No specific uses identified
Uses advised against	No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier	Meon Ltd. Railside Northarbour Spur Portsmouth PO6 3TU +44 (0) 23 9220 0606 mail@meonuk.com
-----------------	---

1.4. Emergency Telephone Number

Emergency telephone	+44 (0) 808 118 1922
----------------------------	----------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosol, Category 1 (Aerosol 1, H222 - H229).

May produce an allergic reaction (EUH208).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label Elements

Mixture for aerosol application

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms



GHS02

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

Signal word	Danger
H-statement(s)	H222: Extremely flammable aerosol. H229 Pressurised container: May burst if heated.
P-statement(s)	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
Other information	Reserved for professional users. Do not use in a confined space. Not to be used for any usage other than those specified.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006. The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients

Ingredient		Classification (EC) 1272/2008	Concentration
DIMETHYL ETHER	INDEX: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8 REACH: 01-2119472128-37-xxxx	GHS02, GHS04 Wng Flam. Liq. 3, H226	25 \leq x % < 50
2-METHOXY-1-METHYLETHYL ACETATE	INDEX: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH: 01-2110475791-29-xxxx	GHS02 Wng Flam. Liq. 3, H226	10 \leq x % < 25
1-METHOXY-2-PROPANOL	INDEX: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH: 01-2119457435-35	GHS02, GH07 Wng Flam. Liq. 3, H226 STOT SE 3, H336	10 \leq x % < 25
TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER $\leq 10 \mu\text{M}$]	INDEX: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5	GHS08 Wng Carc. 2, H351	10 \leq x % < 25
FATTY ACIDS, C18, UNSATD., DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE	CAS: 162627-17-0 EC: 605-296-0 REACH: 01-2119970640-38-0000	GHS07 Skin Sens. 1A: H317	0 \leq x % < 25

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

Specific concentration limits:			
FATTY ACIDS, C18,UNSATD., DIMERS,REACTION PRODUCTS WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE	CAS: 162627-17-0 EC: 605-296-0 REACH: 01-2119970640-38-0000	Skin Sens. 1A: H317 C>=0.1%	

Information on ingredients:

(Full text of H-phrases: see section 16)

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter = 10 µm.

SECTION 4: First aid measures

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

4.1. Description of first aid measures

In case of eye contact	Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
In case of skin contact	In the event of an allergic reaction, seek medical attention.
In case of inhalation	In the event of an allergic reaction, seek medical attention.
In case of ingestion	In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Keep the person exposed at rest. Do not force vomiting. Seek medical attention, showing the label. If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Flammable. Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable extinguishing media

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Extinguishing media which must not be used for safety reasons

- water jet

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

5.2. Special hazards arising from the substance or mixture

Specific hazards during firefighting

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for firefighting.

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non-first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: Handling and storage

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions on safe handling

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

7.2. Conditions for safe storage, including any incompatibilities

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific and uses

No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
115-10-6	1920	1000	-	-	-
108-65-6	275	50	550	100	Peau
107-98-2	375	100	568	150	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010)

CAS	TWA	STEL	Ceiling	Definition	Criteria
107-98-2	100 ppm	150 ppm	-	-	-
13463-67-7	10 mg/m3			A4	

- Germany - AGW (BAuA - TRGS 900, 08/08/2019)

CAS	VME	VME	Excess	Notes
115-10-6		1000 ppm 1900 mg/m3		8 (II)
108-65-6		50 ppm 270 mg/m3		1 (I)
107-98-2		100 ppm 370 mg/m3		2 (I)

- Denmark (2007)

CAS	TWA	VSTEL	Loftvaerdi	Anm
115-10-6	1000 ppm 1920 mg/m3		E	
108-65-6	50 ppm 275 mg/m3		EH	
107-98-2	50 ppm 185 mg/m3		EH	
13463-67-7	-ppm 6 mg/m3		K	

- France (INRS - ED984 :2008)

CAS	VME-ppm	VME-mg/m3	VLE-ppm	VLE-mg/m3	Notes	TMP No
115-10-6	1000	1920	-	-	-	-
108-65-6	50	275	100	550	-	-
107-98-2	50	188	100	375	*	84
13463-67-7	-	10	-	-	-	-

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

- Finland (HTP-värden 2018)

CAS	TWA	STEL	Ceiling	Definition	Criteria
115-10-6	1000 ppm 2000 mg/m ³				
108-65-6	50 ppm 270 mg/m ³	100 ppm 550 mg/m ³			
107-98-2	100 ppm 370 mg/m ³	150 ppm 560 ppm			

- Norway (Administrative norms for pollution of the atmosphere, May 2007)

CAS	TWA	STEL	Ceiling	Definition	Criteria
115-10-6	200 ppm			E	
108-65-6	50 ppm			HE	
107-98-2	50 ppm			HE	
13463-67-7	5 mg/m ³				

- Netherlands / MAC-waarde (10 december 2014)

CAS	TWA	STEL	Ceiling	Definition	Criteria
115-10-6	950 mg/m ³	1500 mg/m ³			
108-65-6	550 mg/m ³				
107-98-2	375 mg/m ³	563 mg/m ³		Huid	
13463-67-7	10 mg/m ³	-	-	-	-

- Switzerland (SUVAPRO 2019)

CAS	TWA	STEL	Ceiling	Definition	Criteria
115-10-6	950 mg/m ³	1500 mg/m ³			
108-65-6	550 mg/m ³				
107-98-2	375 mg/m ³	563 mg/m ³		Huid	
13463-67-7	10 mg/m ³	-	-	-	-

- Sweden (AFS 2007:2)

CAS	TWA	STEL	Ceiling	Definition	Criteria
115-10-6	500 ppm 950 mg/m ³	800 ppm 1500 mg/m ³		V	
107-98-2	50 ppm 275 mg/m ³	100 ppm 550 mg/m ³		H	
108-65-6	50 ppm 190 mg/m ³	150 ppm 568 mg/m ³		H	
13463-67-7	5 mg/m ³				

- UK / WEL (Workplace exposure limits, EH40/2005, 2007)

CAS	TWA	STEL	Ceiling	Definition	Criteria
115-10-6	400 ppm 766 mg/m ³	500 ppm 958 mg/m ³			
108-65-6	50 ppm 274 mg/m ³	100 ppm 548 mg/m ³	SK		
107-98-2	100 ppm 375 mg/m ³	150 ppm 560 mg/m ³	SK		
13463-67-7	4 mg/m ³				

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

8.2. Exposure controls

Personal protection measures,	Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.
Hand Protection	Wear suitable protective gloves in the event of prolonged or repeated skin contact. Type of gloves recommended: - Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR)) - PVA (Polyvinyl alcohol)
Eye Protection	Avoid contact with eyes. Use eye protectors designed to protect against liquid splashes Before handling, wear safety goggles in accordance with standard EN166.
Skin and body Protection	Work clothing worn by personnel shall be laundered regularly. After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state	Viscous liquid.
Colour	Not specified.
Odour	Not specified.
pH	Not applicable.
Boiling Point [°C]	Not specified
Vapour pressure (50°C)	Not applicable.
Density	< 1
Water solubility	Insoluble
Melting point/melting range	Not specified
Self-ignition temperature	Not specified.
Decomposition point/decomposition range	Not specified
Chemical combustion heat	Not specified
Inflammation time	Not specified
Deflagration density	Not specified
Inflammation distance	Not specified
Flame height	Not specified
Flame duration	Not specified

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- heating
- Heat

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- Carbon monoxide (CO)
- Carbon dioxide (CO₂)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1 Substances

No toxicological data available for the mixture.

11.1.2. Mixture

Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12: Ecological information

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

SECTION 13: Disposal considerations

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste; do not dispose of waste into the environment.

Soiled packaging

Empty container completely. Keep label(s) on container.
Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste)

16 05 04 * gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transport information

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

Classification



2.1

14.4. Packing group

14.5. Environmental hazards

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	Label	Ident.	Provis.	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959		E0	-SW1 SW22	SG69
IATA	Class	2°Label	Pack gr.	Passenger	Passenger	Cargo	Cargo	Note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL3/78 and the IBC Code

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- **Container information:**

No data available.

- **Particular provisions:**

No data available.

- **German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws):**

WGK 1: Slightly hazardous for water.

- **Swiss ordinance on the incentive tax on volatile organic compounds:**

108-65-6 acétate de 1-méthoxy-2-propyle

78-93-3 butanone (méthyléthylcétone)

107-98-2 1-méthoxypropane-2-ol (éther 1-méthyle d'alpha-propylène glycol)

115-10-6 éther diméthyle (oxyde de diméthyle)

15.2. Chemical safety assessment

No data available.

301101 - Tracing Plus Line Marker Acrylic Paint Aerosol

SECTION 16: Other information

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.