

PRODUCT DATA SHEET Centrecoat Aquafloor Anti-Slip Floor Paint

Description

Centrecoat Aquafloor Anti-Slip is a water based floor coating containing fine aggregate to give a safer anti slip surface. Utilising a tough polyurethane/acrylic binder system and P.T.F.E., Aquafloor Anti-Slip to reduce dirt retention and improve the cleaning characteristics, a major problem with textured floorings.

Centrecoat Aquafloor Anti-Slip is formulated as an anti slip floor coating in kitchens, food preparation areas, garages, industrial walkways, light mechanical areas and most concrete and wooden areas where safety is a prime consideration. Benefits from being low odour (water based and no strong solvents) eliminating odour contamination of foodstuff.

Colour and Finish

Available in a wide range of colours. Matt finish.

Application

Mix thoroughly before use to ensure aggregate is kept in suspension. Apply via brush or roller. Apply two coats.

Technical Data

Volume Solids: 60%Specific Gravity: 1.5 - 1.6

Touch Dry: 2 hours at 20°C
Overcoatable: 4 - 6 hours at 20°C
Fully Cured: 10 - 14 days at 20°C

Coverage

Approx 8 - 10 m2 per litre depending on substrate and application method.

Clean Up

Clean up tools and equipment after use with water.

Storage

Store between 5 and 25°C.

Shelf Life

6 months in unopened, original containers.

Packaging

Available in 2.5, 5 and 10 Litres