



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on March 30, 2022.

Zingametall BVBA
Rozenstraat 4
9810 Eke
Belgium
32 93 856 881

Facility: Eke, Belgium

Protective (Barrier) Materials

Trade Designation	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
Coatings - Pipe ^[1]			
ZINGA	>= 762 mm	C. HOT	GALV
Coatings - Tank ^[1]			
ZINGA	>= 5,678 L	C. HOT	GALV

[1] Coating Notes:
 Colors: Grey or Grey with Aluminium shine
 Number Of Coats: 1-2
 Maximum Field Use Dry Thickness(in mils): 6
 Maximum Thinner: Up to 20% ZINGASOLV by mass
 Recoat Cure Time and Temperature: 3 hours at 20°C
 Final Cure Time/Temperature: 24 hours at 20°C
 Special Comments: Substrate should be grit blasted to an SA 2.5, Medium G. Once cured,saturate the coating for 2 hours with water. Saturation is the continuous rinsing of the coating with running water. After 2 hours evacuate the system and let dry for 24 hours. The next day saturate the coating for 2 hours, and then evacuate the system and let dry for 24 hours. The following day rinse for 2 hours with water and then let dry for another 24 hours.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.