Safety Data Sheet SILANCOLOR PRIMER PLUS

Safety Data Sheet dated: 19/10/2022 - version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: SILANCOLOR PRIMER PLUS

Trade code: 907J0995

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Not available Uses advised against: Not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

SECTION 2: Hazards identification





2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P261 Avoid breathing mist/vapours/spray.
P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P321 Specific treatment (see supplementary instructions on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention.

Print date 19/10/2022 Production Name SILANCOLOR PRIMER PLUS Page n. 1 of 12

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH208 Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -

isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Contains:

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: SILANCOLOR PRIMER PLUS

Hazardous components within the meaning of the CLP regulation and related classification:							
Concentra tion (% w/w)	Name	Ident. Numb.	Classification	Registration Number			
≥0.1 - <0.25 %	4,5-dichloro-2-octyl-2H-isothiazol- 3-one	EC:264-843-8	Acute Tox. 2, H330 Acute Tox. 4, H302 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Corrosive to the respiratory tract., M-Chronic:100, M-Acute:100				
			Specific Concentration Limits: $0.025\% \le C < 5\%$: Skin Irrit. 2 H315 $0.025\% \le C < 3\%$: Eye Irrit. 2 H319 $C \ge 0.0015\%$: Skin Sens. 1A H317	,			
			Acute Toxicity Estimate: ATE - Oral: 567mg/kg bw				
≥0.1 - <0.25 %	2-(2-butoxyethoxy)ethanol	CAS:112-34-5 EC:203-961-6 Index:603-096- 00-8	Eye Irrit. 2, H319	01-2119475104-44-XXXX			
≥0.01 - <0.016 %	terbutryn	CAS:886-50-0 EC:212-950-5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, H302 Skin Sens. 1B, H317, M- Chronic:100, M-Acute:100				
			Specific Concentration Limits: $C \ge 3\%$: Skin Sens. 1B H317				
≥0.01 - <0.016 %	2-octyl-2H-isothiazol-3-one	EC:247-761-7	Acute Tox. 2, H330 Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:100, M-Acute:100, EUH071				

Print date 19/10/2022 **Production Name** SILANCOLOR PRIMER PLUS Page n. 2 of 12 Specific Concentration Limits: C ≥ 0.0015%: Skin Sens. 1A H317

Acute Toxicity Estimate: ATE - Oral: 125mg/kg bw ATE - Dermal: 311mg/kg bw

<0.0015 % reaction mass of: 5-chloro-2methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - Index:613-167- H301 Skin Corr. 1C, H314 Skin isothiazol-3-one [EC no. 220-239- 00-5 6] (3:1)

EC:611-341-5

CAS:55965-84-9 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, Sens. 1A, H317 Acute Tox. 2, H310 Acute Tox. 2, H330 Eye Dam. 1, H318, M-Chronic: 100, M-Acute: 100

> Specific Concentration Limits: C ≥ 0.6%: Skin Corr. 1C H314 $0.06\% \le C < 0.6\%$: Skin Irrit. 2 H315

C ≥ 0.6%: Eye Dam. 1 H318 $0.06\% \le C < 0.6\%$: Eye Irrit. 2

H319

C ≥ 0.0015%: Skin Sens. 1A H317

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Print date 19/10/2022 Production Name SILANCOLOR PRIMER PLUS 3 of 12 Page n.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OFL value

List of components wit	h OEL va	lue							
	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
2-(2- butoxyethoxy)ethanol CAS: 112-34-5	DFG	GERMANY	С			100.5	15		
	ACGIH				10				hematologic, kidney and liver effects
	Nationa	I SWEDEN		68	10				
	EU			67.5	10	101.2	15	Indicative	
	Nationa	I FRANCE		68	10	101.2	15		
	Nationa	I SPAIN		67.5	10	101.2	15		
	Nationa	I GREECE		67.5	10	101.2	15		
	Nationa	I DENMARK		68	10				
	Nationa	I FINLAND		68	10				
	Nationa	I GERMANY		67	10				
	Nationa	I PORTUGAL		67.5	10	101.2	15		
	Nationa	I NORWAY		68	10	102	15		
	Nationa	I BELGIUM		67.5	10	101.2	15		
	NDS	POLAND		67					
	NDSCh	POLAND				100			
	CHE	SWITZERLAND				101	15		
	NDS	NETHERLANDS	;	50		100			
	Nationa	I CZECH REPUBLIC		100					

Print date 19/10/2022 Production Name SILANCOLOR PRIMER PLUS Page n. 4 of 12

National	HUNGARY		67.5		101.2	
National	ESTONIA		67.5	10		
National	LATVIA		67.5	10	101.2	15
National	CZECH REPUBLIC	С			100	
National	SLOVAKIA	С			101.2	
National	SLOVAKIA		67.5	10		
National	SLOVENIA		67.5	10	101.25	15
National	UNITED KINGDOM		67.5	10	101.2	15
National	BULGARIA		67.5	10	101.2	15
National	ROMANIA		67.5	10	101.2	15
TUR	TURKEY		67.5	10	101.2	15
National	LITHUANIA		67.5	10	101.2	15
National	CROATIA		67.5	10	101.2	15
DFG	GERMANY	С			54	10
National	GERMANY		0.05			
CHE	SWITZERLAND				0.1	
National	SLOVENIA		0.05		0.05	

Predicted No Effect Concentration (PNEC) values

2-octyl-2H-isothiazol-3-

CAS: 26530-20-1

one

	PNEC Limit	Exposure Route	Exposure Frequency Remark
2-(2- butoxyethoxy)ethanol CAS: 112-34-5	1.1 mg/l	Fresh Water	
	0.11 mg/l	Marine water	
	4.4 mg/kg	Freshwater sediments	
	0.44 mg/kg	Marine water sediments	

0.32 mg/kg Soil 200 mg/l

Microorganisms in sewage treatments

11 mg/l Intermittent release

Derived No Effect Level. (DNEL)

	Worker Worker Consu Industr Profess mer y ional	Exposure Route	Exposure Frequency Remark
2-(2- butoxyethoxy)ethanol CAS: 112-34-5	83 mg/kg	Human Dermal	Long Term, systemic effects
	101 mg/m3	Human Inhalation	Short Term, local effects
	67.5 mg/m3	Human Inhalation	Long Term, systemic effects
	67.5 mg/m3	Human Inhalation	Long Term, local effects

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton. Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Print date 19/10/2022 SILANCOLOR PRIMER PLUS Production Name Page n. 5 of 12 Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: liquid Color: transparent Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: Not available

Initial boiling point and boiling range: 100 °C (212 °F)

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: 7.00

Viscosity: 20.00 cPs

Kinematic viscosity: Not available Solubility in water: dispersible Solubility in oil: no data available

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: Not available Vapour density: Not available **Particle characteristics:** Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available Explosive properties: == No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

Print date 19/10/2022 Production Name SILANCOLOR PRIMER PLUS Page n. 6 of 12

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the mixture:

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation The product is classified: Skin Irrit. 2(H315) c) serious eye damage/irritation The product is classified: Eye Irrit. 2(H319) d) respiratory or skin sensitisation The product is classified: Skin Sens. 1A(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

4,5-dichloro-2-octyl-2H- a) acute toxicity

isothiazol-3-one

ATE - Oral: 567 mg/kg bw

LC50 Inhalation Dust Rat = 0.16 mg/l

LD50 Oral Rat = 567 mg/kg

2-(2a) acute toxicity LD50 Skin Rabbit = 2700 mg/kg

butoxyethoxy)ethanol

LD50 Oral Rat = 5660 mg/kg

LD50 Skin Rabbit > 10200 mg/kg terbutryn a) acute toxicity

> LC50 Inhalation Rat > 8 g/m3 4h LD50 Oral Rat = 2045 mg/kg LD50 Skin Rabbit > 10200 mg/kg

2-octyl-2H-isothiazol-3a) acute toxicity ATE - Oral: 125 mg/kg bw

one

ATE - Dermal: 311 mg/kg bw LD50 Oral Rat = 318 mg/kg LD50 Skin Rabbit = 311 mg/kg

LC50 Inhalation Dust Rat = 0.58 mg/l 4h

reaction mass of: 5a) acute toxicity LC50 Inhalation Rat = 2.36 mg/l 4h

chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2methyl-2H -isothiazol-3one [EC no. 220-239-6] (3:1)

LD50 Skin Rabbit = 660 mg/kg LD50 Oral Rat = 53 mg/kg

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

Print date 19/10/2022 **Production Name** SILANCOLOR PRIMER PLUS 7 of 12 Page n.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of components with eco-to	xicological prop	erties
Component	Ident. Numb.	Ecotox Infos
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	CAS: 64359-81- 5 - EINECS: 264-843-8 - INDEX: 613- 335-00-8	a) Aquatic acute toxicity: EC50 Daphnia = mg/L 48
		a) Aquatic acute toxicity: EC50 Algae = mg/L 72
		a) Aquatic acute toxicity: LC50 Fish = mg/L 96
		b) Aquatic chronic toxicity: NOEC Daphnia = mg/L
		b) Aquatic chronic toxicity: NOEC Fish = mg/L
2-(2-butoxyethoxy)ethanol	CAS: 112-34-5 - EINECS: 203- 961-6 - INDEX: 603-096-00-8	a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus = 1300 mg/L 96h EPA
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna > 100 mg/L 48h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus > 100 mg/L 96h IUCLID
terbutryn	CAS: 886-50-0 - EINECS: 212- 950-5	a) Aquatic acute toxicity: EC50 Daphnia = 6.4 mg/L 48
		a) Aquatic acute toxicity: EC50 Algae = 0.0067 mg/L 72
		a) Aquatic acute toxicity: LC50 Fish = 1.9 mg/L 96
		b) Aquatic chronic toxicity: NOEC Daphnia = 0.05 mg/L - 21d
		b) Aquatic chronic toxicity: NOEC Fish = 0.073 mg/L - 28d
2-octyl-2H-isothiazol-3-one	CAS: 26530-20- 1 - EINECS: 247-761-7 - INDEX: 613- 112-00-5	a) Aquatic acute toxicity: EC50 Daphnia = 0.42 mg/L 48
		a) Aquatic acute toxicity: EC50 Algae = 0.084 mg/L 72
		a) Aquatic acute toxicity: LC50 Fish = 0.036 mg/L 96
		a) Aquatic acute toxicity: LC50 Fish = 0.18 mg/L 96
		b) Aquatic chronic toxicity: NOEC Daphnia = $0.002 \text{ mg/L} - 21 \text{ d}$
		b) Aquatic chronic toxicity: NOEC Fish = 0.022 mg/L - 28 d
		b) Aquatic chronic toxicity: NOEC Algae = 0.004 mg/L 72
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H isothiazol-3-one [EC no. 220-239-6] (3:1)		a) Aquatic acute toxicity: EC50 Daphnia = 0.12 mg/L 48
		a) Aquatic acute toxicity: LC50 Fish = 0.22 mg/L 96
		a) Aquatic acute toxicity: EC50 Algae = 0.048 mg/L 72
		b) Aquatic chronic toxicity: NOEC Algae = 0.0012 mg/L 72
		b) Aquatic chronic toxicity: NOEC Fish = 0.098 mg/L - 28 d
		b) Aquatic chronic toxicity: NOEC Daphnia = 0.004 mg/L - 21 d

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

19/10/2022 SILANCOLOR PRIMER PLUS Print date Production Name Page n. 8 of 12 N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >=0.1%.

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7 Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA) :

Not Applicable

Sea (IMDG):

Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): 22 g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category Lower-tier threshold according to Annex 1, part 1 (tonnes)

(tonnes) Products belongs to category E2 200 500

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Upper-tier threshold

Restrictions related to the product: 3

Restrictions related to the substances contained: 55, 75

SVHC Substances:

SVHC substances not present in a concentration ≥ 0.1% (w/w)

National regulations

Produktregisteret Norge: 304055 Produktregister Danmark: 4127552

MAL-kode: 00-3 (1993)

German Water Hazard Class (WGK)

Class 1: slightly hazardous for water.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H311	Toxic in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
Code	Hazard class and hazard category Description	n

		- · · · · · · · · · · · · · · · · · · ·
3.1/2/Inhal	Acute Tox. 2	Acute toxicity (inhalation), Category 2
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3
3.1/3/Oral	Acute Tox. 3	Acute toxicity (oral), Category 3

Print date 19/10/2022 **Production Name** SILANCOLOR PRIMER PLUS 10of Page n.

3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1	Skin Corr. 1	Skin corrosion, Category 1
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
EUH071		EUH071

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1A	Calculation method
4.1/C2	Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

 ${\sf GefStoffVO:\ Ordinance\ on\ Hazardous\ Substances,\ Germany.}$

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

Print date 19/10/2022 Production Name SILANCOLOR PRIMER PLUS Page n. 11of 12

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

* Sheet model entirely changed in compliance to regulatory update.

Print date 19/10/2022 Production Name SILANCOLOR PRIMER PLUS Page n. 12of 12