



REBOUND SPORT 2000 PAINT - WSF CERTIFIED

**WORLD
SQUASH**

ACCREDITED
PRODUCT 2018

Rebound Plaster
Rebound 'Sport 2000' Squash Court Paint

APPLICATION SHEET

APPLICATION OF REBOUND SPORT 2000

REBOUND SPORT 2000 as per all Rebound Products is formulated for full exterior use in all weathers.

Adhesion is of a standard which allows use on panel systems and even upon metal and glass substrates.

Based on advanced technology also inhibits stains bleeding through the substrate, high opacity blocks previous substrate colouring/markings.

The bespoke matte finish is WSF certified to give full true-play characteristics.

PREPARATION

Ensure all surfaces to be painted are clean, dry and free from grease and loose or flaking material, or any other contaminants that may impair adhesion. Any faults in the substrate, particularly those that can lead to moisture penetration must be rectified or can affect the finish quality. Any existing crazes or flaking paint, dirt, grease or other surface contaminants should be removed. If your substrate has been previously painted, rub down with a fine waterproof abrasive paper and then rinse thoroughly. Bare substrates should also be abraded in a similar manner to allow improved adhesion. Please avoid inhaling any sanding dust and

always wear a face mask if fine sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

Hard wall plasters/panels should be lightly sanded with a coarse glass-paper.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Stir the product thoroughly to ensure it is fully homogenous, do not contaminate. For best results apply by brush, roller or spray. Application tool type and quality may influence the finished appearance. Apply liberally and avoid overspreading. Not to be applied below 8°C. **REBOUND SPORT 2000** will be touch dry after 1 hour, and additional coats can be applied after 3-4 hours. Ensure good ventilation during drying and application.

Porous surfaces should be sealed with a first coat of **REBOUND SPORT 2000** with up to 20% clean water. Allow fresh plaster to dry to < 15% moisture content.

It is recommended that the application of 2 coats is generally sufficient, though more may be required dependant on the nature and porosity of the substrate.

Please read the Product Data Sheets (available below) before you place an order and prior to application of the product. The content of this website is our best recommendation and is not advice. Coverage rates quoted are approximate, you agree that coverage depends on the condition of the substrate, surface absorption, texture and application method. We ALWAYS recommend a trial area is coated to ensure the product meets your requirements before use.

APPLICATION

Typical Coverage (per coat)	9m ² per litre
Touch Dry	1 Hour
Application	Brush, Roller, Spray

The figures stated above are approximate. Please ensure you refer to all datasheets.