SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : OWATROL PID 60
Product code : owpid60.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint

1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A.: Siège Social.
Address : 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE.
Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84.
reglementaire@durieu.com
www.durieu.com

1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE:Ireland National Poisons Information Centre: +353 (0) 1 8379964

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Repeated exposure may cause skin dryness or cracking (EUH066).
May produce an allergic reaction (EUH208).
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

EUH208	Contains FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Hazard statements :

H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statements - Prevention :

P260	Do not breathe dust vapours.
P262	Do not get in eyes, on skin, or on clothing.
P273	Avoid release to the environment.

Precautionary statements - Response :

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary statements - Disposal :

P501	Dispose of contents / container in accordance with local regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table
The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 1317653 CAS: 1317-65-3 EC: 215-279-6 CARBONATE DE CALCIUM		[1]	10 <= x % < 25
INDEX: 649-356-00-4 CAS: 64742-95-6 EC: 265-199-0 REACH: 01-2119455851-35 SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.	GHS08 Dgr Asp. Tox. 1, H304	P	10 <= x % < 25
INDEX: 299 CAS: 64742-48-9 EC: 919-857-5 REACH: 01-2119463258-33-XXXX HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH:066		10 <= x % < 25
INDEX: PCP186 CAS: 64742-48-9 EC: 918-481-9 REACH: 01-2119457273-39-XXXX HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304 EUH:066		10 <= x % < 25
INDEX: 298 CAS: 1189173-42-9 EC: 918-811-1 REACH: 01-2119463583-34-XXXX HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE	GHS09, GHS07, GHS08 Dgr Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066		2.5 <= x % < 10
INDEX: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17-0014 TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER <= 10 µM]	GHS08 Wng Carc. 2, H351	[1] [10]	2.5 <= x % < 10
INDEX: 600 EC: 905-588-0 REACH: 01-2119488216-32-XXXX XYLÈNE (MASSE DE RÉACTION DE [ORTHO-XYLÈNE, MÉTA-XYLÈNE, LE PARA-XYLÈNE & L'ÉTHYLBENZÈNE])	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373		1 <= x % < 2.5

INDEX: 603-003-00-0 CAS: 71-23-8 EC: 200-746-9 PROPAN-1-OL	GHS02, GHS05, GHS07 Dgr Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336	[1]	0.1 <= x % < 1
INDEX: 008 CAS: 34590-94-8 EC: 252-104-2 REACH: 01-2119450011-60-XXXX (2-METHOXYMETHYLETHOXY)PROPANOL		[1]	0.1 <= x % < 1
INDEX: PCP16A CAS: 162627-17-0 EC: 605-296-0 REACH: 01-2119970640-38-XXXX FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE	GHS07 Wng Skin Sens. 1, H317		0.1 <= x % < 1
INDEX: 066 CAS: 14808-60-7 EC: 238-878-4 QUARTZ(SIO2)		[1]	0.1 <= x % < 1
INDEX: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH: 01-2119457435-35 1-METHOXY-2-PROPANOL	GHS02, GHS07 Wng Flam. Liq. 3, H226 STOT SE 3, H336	[1]	0.1 <= x % < 1
INDEX: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32 XYLENE	GHS02, GHS07 Wng Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315	C [1]	0 <= x % < 0.1
INDEX: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH: 01-2119489370-35 ETHYLBENZENE	GHS02, GHS07, GHS08 Dgr Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 Asp. Tox. 1, H304	[1]	0 <= x % < 0.05
INDEX: 603-053-00-3 CAS: 107-41-5 EC: 203-489-0 REACH: 01-2119539582-35 2-METHYLPENTANE-2,4-DIOL	GHS07 Wng Eye Irrit. 2, H319 Skin Irrit. 2, H315	[1]	0 <= x % < 0.05
INDEX: 350 CAS: 128-37-0 EC: 204-881-4 REACH: 01-2119565113-46-XXXX 2,6-DI-TERT-BUTYL-P-CRESOL	GHS09 Wng Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	[1]	0 <= x % < 0.05

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 298		inhalation: ATE = 4.688 mg/l

CAS: 1189173-42-9 EC: 918-811-1 REACH: 01-2119463583-34-XXXX HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE		4h (vapours)
INDEX: 603-053-00-3 CAS: 107-41-5 EC: 203-489-0 REACH: 01-2119539582-35 2-METHYLPENTANE-2,4-DIOL	Skin Irrit. 2: H315 >=10% Eye Irrit. 2: H319 C>= 10%	

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter <= 10 µm.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Ce produit n'est pas classé comme inflammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)
- water with AFFF (Aqueous Film Forming Foam) additive

Unsuitable methods of extinction

In the event of a fire, do not use :

- jets d'eau directs

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging :

- Vats
- Buckets

Suitable packaging materials :

- Coated steel

Unsuitable packaging materials :

- Plastic

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :	
34590-94-8	308	50	-	-	Peau	
107-98-2	375	100	568	150	Peau	
1330-20-7	221	50	442	100	Peau	
100-41-4	442	100	884	200	Peau	

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :

1317-65-3	-	10	-	-	-	-
13463-67-7	-	10	-	-	-	-
71-23-8	200	500	-	-	-	84
34590-94-8	50	308	-	-	*	84
14808-60-7	-	0.1 A	-	-	-	25
107-98-2	50	188	100	375	*	84
1330-20-7	50	221	100	442	*	4 Bis. 84. *
100-41-4	20	88.4	100	442	*	84
107-41-5	-	-	25	125	-	84
128-37-0	-	10	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
1317-65-3	4 mg/m³					
13463-67-7	4 mg/m³					
71-23-8	200 ppm 500 mg/m³	250 ppm 625 mg/m³		Sk		
34590-94-8	50 ppm 308 mg/m³			Sk		
14808-60-7	0.3 mg/m3	-	-	-	R	
107-98-2	100 ppm 375 mg/m³	150 ppm 560 mg/m³		Sk		
1330-20-7	50 ppm 220 mg/m³	100 ppm 441 mg/m³		Sk. BMGV		
100-41-4	100 ppm 441 mg/m³	125 ppm 552 mg/m³		Sk		
107-41-5	25 ppm 123 mg/m³	25 ppm 123 mg/m³				
128-37-0	10 mg/m³					

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

XYLÈNE (MASSE DE RÉACTION DE [ORTHO-XYLÈNE, MÉTA-XYLÈNE, LE PARA-XYLÈNE & L'ÉTHYLBENZÈNE])

Final use:	**Consumers.**
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	1.6 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	108 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	174 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term local effects.
DNEL :	289 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	77 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	180 mg of substance/m3

Predicted no effect concentration (PNEC):

XYLÈNE (MASSE DE RÉACTION DE [ORTHO-XYLÈNE, MÉTA-XYLÈNE, LE PARA-XYLÈNE & L'ÉTHYLBENZÈNE])

Environmental compartment:	Fresh water.
PNEC :	0.1 mg/l
Environmental compartment:	Sea water.
PNEC :	0.01 mg/l

Environmental compartment:	Fresh water sediment.
PNEC :	13.7 mg/l
Environmental compartment:	Marine sediment.
PNEC :	1.37 mg/l
Environmental compartment:	Waste water treatment plant.
PNEC :	9.6 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.
Use eye protectors designed to protect against liquid splashes
Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.
Gloves must be selected according to the application and duration of use at the workstation.
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

- Body protection

Avoid skin contact.
Wear suitable protective clothing.
Suitable type of protective clothing :
In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.
In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.
Work clothing worn by personnel shall be laundered regularly.
After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Type of FFP mask :
Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.
Category :
- FFP2
Type of mask with combined filters :
Wear a half mask in accordance with standard EN140.
Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :
- A1 (Brown)
- AX (Brown)
Particle filter according to standard EN143 :
- P2 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state :	Fluid liquid.

Colour

Unspecified

Odour

Odour threshold :	Not stated.

Melting point

Melting point/melting range :	Not specified.

Freezing point

Freezing point / Freezing range :	Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	Not specified.

Flammability

Flammability (solid, gas) :	Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :	Not stated.
Explosive properties, upper explosivity limit (%) :	Not stated.

Flash point

Flash Point Interval :	60°C < FP <= 93°C

Auto-ignition temperature

Self-ignition temperature :	Not specified.

Decomposition temperature

Decomposition point/decomposition range :	Not specified.

pH

pH :	Not relevant.
pH (aqueous solution) :	Not stated.

Kinematic viscosity

Viscosity :	Not stated.

Solubility

Water solubility :	Insoluble.
Fat solubility :	Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water :	Not stated.

Vapour pressure

Vapour pressure (50°C) :	Not relevant.

Density and/or relative density

Density :	> 1

Relative vapour density

Vapour density :	Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

11.1.1. Substances

Acute toxicity :

FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3- PROPANEDIAMINE AND 1,3-PROPANEDIAMINE (CAS: 162627-17-0)

Oral route : LD50 > 10000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 2 mg/kg
Species : Rat
Autres lignes directrices

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 2000 mg/kg
Species : Rabbit
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (Vapours) : LC50 = 4.688 mg/l
Species : Rat
OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)
Duration of exposure : 4 h

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 5000 mg/kg
Species : Rabbit
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (Vapours) : LC50 > 5000 mg/l
Species : Rat
OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

Germ cell mutagenicity :

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)
No mutagenic effect.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)
No mutagenic effect.

Carcinogenicity :

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

Carcinogenicity Test : Negative.
No carcinogenic effect.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Carcinogenicity Test : Negative.
No carcinogenic effect.

Reproductive toxicant :

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

No toxic effect for reproduction
OCDE Ligne directrice 414 (Étude de la toxicité pour le développement prénatal)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

No toxic effect for reproduction
OCDE Ligne directrice 414 (Étude de la toxicité pour le développement

prénatal)

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 128-37-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
CAS 100-41-4 : IARC Group 2B : The agent is possibly carcinogenic to humans.
CAS 1330-20-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
CAS 14808-60-7 : IARC Group 1 : The agent is carcinogenic to humans.
CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.
The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

Fish toxicity :	Species : Perca fluviatilis
Crustacean toxicity :	EC50 <= 10 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 = 11 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h

FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3- PROPANEDIAMINE AND 1,3-PROPANEDIAMINE (CAS: 162627-17-0)

Fish toxicity :	LC50 = 150 mg/l Species : Leuciscus idus Duration of exposure : 48 h Autres lignes directrices
Crustacean toxicity :	EC50 > 100 mg/l Species : Daphnia magna Duration of exposure : 48 h OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
Algae toxicity :	ECr50 > 100 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Fish toxicity :	LC50 = 1000 mg/l Species : Oncorhynchus mykiss Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 1000 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 = 1000 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3- PROPANEDIAMINE AND 1,3-PROPANEDIAMINE (CAS: 162627-17-0)

Biodegradability : Non-rapidly degradable.

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 * packaging containing residues of or contaminated by dangerous substances

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Maritime transport in bulk according to IMO instruments

-

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

- Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 430 g/l.
The permitted European levels of VOC in the ready-to-use product (category IIAi) are 600 g/l maximum in 2007 and 500 g/l maximum in 2010.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.
The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.
It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.
The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer .
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
ATE : Acute Toxicity Estimate
DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
STEL : Short-term exposure limit
TWA : Time Weighted Averages
TMP : French Occupational Illness table
TLV : Threshold Limit Value (exposure)
AEV : Average Exposure Value.
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.