

1504-3:2005

80

0086

# **DECLARATION OF PERFORMANCE**

# Sika MonoTop®- 615

02 03 02 04 001 0 000006 1088

| 1. Product Type: Unique identification code of the product-type:  | Sika <sup>®</sup> MonoTop  |
|---|--|
| 2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):                    | 615 ( Batch No See packaging)  |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | 1-component class R3 mortar for the repair of concrete structures. EN 1504-3: 2005 Principles 3,7 - methods 3.1, 3.3, 7.1, 7.2 Conforming to the Annex ZA Table ZA.1   |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):                            | Sika MonoTop <sup>®</sup> Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom   |
| 5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):  | Not Relevant (see 4)   |
| 6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:        | System 2+  |
| 7. Notified body (hEN): In case of the declaration of performance (DoP)concerning a construction product covered by a harmonised standard:                  | Notified factory production control certification body No. 0086 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 541325 |

Refurbishment
Declaration of Performance
Edition 02.2013
Identification no. 02 03 02 04 001 0 000006
Version no. 01

| In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued: | (see 7) |
|--|---------|
|--|---------|

### 9. Declared performance

| Essential characteristics        | Performance                  | Test Standard | Harmonised technical specification |
|----------------------------------|------------------------------|---------------|------------------------------------|
| Compressive strength             | Class R3                     | EN 12190      |                                    |
| Chloride ion content             | ≤ 0.05%                      | EN 1015-7     |                                    |
| Adhesive bond                    | ≥ 1.5 MPa                    | EN 1542       |                                    |
| Restrained shrinkage / expansion | ≥ 1.5 MPa                    | EN 12617-4    | EN 1504-3: 2005                    |
| Carbonation resistance           | NPD*                         | EN 13296      |                                    |
| Elastic modulus                  | ≥ 15 Gpa                     | EN 13412      |                                    |
| Thermal compatibility            | NPD                          | EN13687       |                                    |
| Skid resistance                  | NPD                          | EN 13036-4    |                                    |
| Coefficient of thermal expansion | NPD                          | EN 1770       |                                    |
| Capillary absorption             | ≤ 0.5 kg/m²/h <sup>0.5</sup> | EN 13057      |                                    |
| Reaction to fire                 | A1                           | EN 13501-1    |                                    |
| Dangerous substances             | NPD                          |               |                                    |

<sup>\*</sup>Not required if the repair product includes a surface protection system with proven protection against carbonation (EN 1504-2) or is a PC mortar



Refurbishment Declaration of Performance Edition 02.2013 Identification no. 02 03 02 04 001 0 000006 Version no. 01

#### 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

R&D Manager

Technical Manager

02, 2013

## **Ecology, Health and Safety Information (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

#### Legal note

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Phone +44 1707 394444 Telefax +44 1707 329129

www.sika.co.uk email: sales@uk.sika.com





cate No. EMS 4308 Certificate No. FM 12504