

DOOR SURVEY FORM

Contractor Name	
Contact Telephone	
Email Address	

Building Owner	
Site Address	
Contact Email	

Protection Required For Doors							
30 Minutes		60 Minutes					
Class 1		Class 0		Class B		Class C	

About the Door (tick all that apply)			
Softwood		Hardwood	Other please describe
Fire Rated		Glazed	
Solid		Hollow	
Composite		Panelled	

Current Finish							
New/Bare		Painted		Varnish		Stained	Unknown sealed
Waxed		Lacquer		Laminated		Veneer	Factory Finished

Type of Finish Required			
Painted		Clear Finish	Stained Finish
			Bare

Colour(s) Required	
--------------------	--

Is the Project			
Dry Internal		Damp Internal	External
			High Wear and Tear

If you ticked External or Damp Internal. Is the area for protecting			
Prone to damp or moisture ingress		Open to the elements	A Swimming Pool
Under construction		Coastal	Kitchen or Bathroom

NOTES:

To help us provide the correct specification please complete as much detail as possible on both pages. If you have different levels of protection please complete an enquiry form for each. Please note that Class 1, 0, B, or C are not the same as 30 and 60 minutes fire resistance.

-  01462 421 333
-  promain.co.uk
-  info@promain.co.uk



Door			
What is the measurement for the thickest part of the door			mm
What is the measurement of the thinnest part (panel) of the door			mm
How is the door glazed			
Is there an intumescent strip	In the door		In the frame
Surrounding Frame and Wall			
Has the wall been assessed for Fire Resistance			
Has the door frame been assessed for Fire Resistance			
Is the required compartmentation 30 or 60 minutes			
How is the wall constructed			
Concrete		Dry Lining	
Brick		Lath & Plaster	
Total Number of Doors (Complete a separate form for each different type of door)			
Survey Completed By			
Company Name			
Specification Issued By			
Specification Date			
Specifications are valid for 6 months from the specification date.			
Specification Number			

DOORS

It is important to note that most modern internal doors cannot be upgraded to achieve 30 minutes Fire Resistance.

However, where installation of fire rated door sets is not an option due to listed building status or similar Thermoguard Timbercoat Insulating Basecoat and Thermoguard 2K Fire Varnish Basecoat with the correct topcoat are capable of upgrading doors under specific circumstances.

- Doors would be that can afford to lose 2mm to charring and
- Solid, joint-free doors with compressed core and a reasonable thickness (6 mm +), veneer faces bonded to either side of the core. These can be flush doors or pressed to create a moulded look.
- Well-seasoned, old or sturdy doors with 35mm + thick frames and panels 10mm + thick.

If you are unsure if your doors fulfil this criteria complete this form and return to Thermoguard Technical on technical@thermoguard.co.uk or call 01142 768008 Option 2 to discuss your project

Contact information submitted will only be used for the purposes of specification and certification.

 01462 421 333

 promain.co.uk

 info@promain.co.uk

