

Description

Centrecoat Etch Primer is a single pack etch primer that is scientifically formulated to give enhanced in-can stability. It is suitable for the painting of ferrous and non-ferrous metals. As it is designed to form the basis of a multi-coat paint system it offers only temporary exterior protection. It is not recommended for use on aluminium and aluminium alloys.

Preparation

The surfaces to be primed should be sound and clean, free from grease, oil, rust, scale, dirt, etc.

Application

Suitable for conventional air, airless spray or dip application.

Mix thoroughly before use. Apply an even coat. Do not apply or dry when air or surface temperature is below 10°C or in high humidity or where condensation is likely to occur (i.e. Surface temperature must always be a minimum of 3°C above dew point). Painting should only be carried out under good atmospheric conditions and clement weather. Preparation, painting and drying should never be undertaken: when the air temperature falls below the minimum temperature for the coating, or during fog, mist, snow, or when rain is imminent, or when the surface to be painted is wet with condensation or when condensation may occur during the drying period.

Thin with up to 25% [Centrecoat Etch Primer Thinner](#) for the recommended applications.

Technical Data

- ▶ Touch Dry: 5 minutes at 20°C
- ▶ Hard Dry: 30 minutes at 20°C
- ▶ Overcoatable: Anytime after 30 minutes at 20°C

Coverage Rate

Approx 12 sq. metres per litre at 10 microns DFT.

Shelf Life

6 months when stored under cover, in original unopened containers at normal room temperatures.

Packaging

Available in 5 Litres