

DECLARATION OF PERFORMANCE N. CPR-GB1/0085

- 1) Unique identification code of the product-type: **ULTRALITE S2**
- 2) Intended uses: **Improved cementitious adhesive for ceramic, stone and ideal for thin porcelain tiles**
- 3) Manufacturer: **MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD- www.mapei.co.uk**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 12004:2007+A1:2012**

Notified bodies: **Technische Universitat Munchen N.0797 & Building Research Institute, N. 1488**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire: Bond strength:	Class A2 – s1, d0 expressed as: - initial tensile adhesion strength $\geq 1,0$ N/mm²
Durability against: - climate/heat ageing action: - water/humidity action: - freeze-thaw cycles:	expressed as: - tensile adhesion strength after heat ageing $\geq 1,0$ N/mm² - tensile adhesion strength after water immersion $\geq 1,0$ N/mm² - tensile adhesion strength after freeze-thaw cycles $\geq 1,0$ N/mm²
Release of dangerous substances:	NPD

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Paul Hodgetts – Quality Manager

Halesowen, 30/05/2024



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website

Revision 2 notes:	Product unchanged, changes to system 3 (RtF), deleted commission sentence
--------------------------	--

ULTRALITE S2
CE MARKING
Annex to DoP N. CPR-GB1/0085



 0797 1488	 MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD www.mapei.co.uk
17 CPR-GB1/0085 EN 12004 ULTRALITE S2 <i>Improved cementitious adhesive for ceramic, stone and ideal for thin porcelain tiles</i>	
Reaction to fire: Bond strength: Durability against: - climate/heat ageing action: - water/humidity action: - freeze-thaw cycles: Release of dangerous substances:	Class A2 – s1, d0 expressed as: - initial tensile adhesion strength $\geq 1,0 \text{ N/mm}^2$ expressed as: - tensile adhesion strength after heat ageing $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after water immersion $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after freeze-thaw cycles $\geq 1,0 \text{ N/mm}^2$ NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values can be omitted by the CE marking*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*