

**RUST-OLEUM®**  
INDUSTRIAL



## FILLCOAT® FIBRES WATERPROOFING

# Stops leaks instantly, crack-bridging

- Repairs holes and cracks up to 2mm instantly
- Excellent adhesion to various substrates
- Can be applied in all weather conditions
- Direct repair of gutters, roofs, chimney stacks, pipes and more
- Bitumen-free formula



KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

# FILLCOAT® FIBRES WATERPROOFING

## DESCRIPTION

Instantly waterproof elastic paint with crack-bridging fibres for roofs, non-walkable terraces, gutters, ridge-pieces, chimney stacks, pipes, etc. The product has better UV resistance and improved hydrophobic properties.

## RECOMMENDED USE

Waterproof finish of roofs, non-walkable terraces, gutters, ridge-pieces, chimney stacks, pipes, etc. Product is recoatable with Dacfill, Coating PRT or Dacfill HZ.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,01  
Gloss Level: Satin  
Solids Content in weight: 52%  
Solids content in volume: 43%

## DRY TIMES BY 20° C/RH 50%

Touch dry: 4 h  
Dry to recoat: 3 - 14 days with the same product. 6 weeks with a paint  
Fully cured: 3 weeks

## RECOMMENDED WET FILM THICKNESS

1000 µm

## RECOMMENDED DRY FILM THICKNESS

430 µm

## THEORETICAL CONSUMPTION

1 m<sup>2</sup>/L at 430 µm dry

## PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## SURFACE PREPARATION

Remove dust, mud, grease, moss and withered leaves carefully. The spots to be repaired are cleaned with a hard broom and sponged. After cleaning, Fillcoat Fibres can be applied directly on bituminous substrates, hard PVC, polyester, zinc, aluminium, glass, tiles, etc. Porous materials (concrete, stone, wood) must first be dried and pre-treated with a coat of Primer 44HS. In case of repeatedly repaired spots, important or active cracks, apply Fillcoat Fibres crosswise over the cracks or fissures.

## DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

## APPLICATION CONDITIONS

Can be applied during all weather conditions, except for snow.

## APPLICATION & THINNING: BRUSH

Do not dilute.

## CLEANING OF EQUIPMENT / SPILLS

Thinner 22 or white spirit.

## REMARKS

Never apply Fillcoat Fibres to polystyrene insulation or onto new concrete (concrete should be at least 2 year old). Do not apply Fillcoat Fibres as priming coat under Dac Hydro Alu.

## SAFETY DATA

VOC level: 485 g/l  
VOC ready mix: 485 g/l  
VOC category: A/i  
VOC limit: 500 g/l  
Grenelle: Exterior  
Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the can.

## SHELF LIFE

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 10/06/2024

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu