

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CONVENTIONAL PAINT THINNER

Product code: TW35

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Bradite Paints
Ogwen Valley Works
Bethesda
Gwynedd
LL57 4YP
United Kingdom

Tel: +44 (0)1248 600315

Fax: +44 (0)1248 602782

Email: sales@bradite.com

1.4. Emergency telephone number

Emergency tel: +44 (0)1248 600315
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Flam. Liq. 3: H226

Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS08: Health hazard



SAFETY DATA SHEET
CONVENTIONAL PAINT THINNER

Page: 2

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P331: Do NOT induce vomiting.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),
HYDROTREATED HEAVY

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and pain.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

[cont...]

SAFETY DATA SHEET
CONVENTIONAL PAINT THINNER

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

Storage quantity limits: 250 L

7.3. Specific end use(s)

Specific end use(s): PC9a: Coatings and paints, thinners, paint removers.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Workplace exposure limits:

Respirable dust

State	8 hour TWA		15 min. STEL	
	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	150 ppm	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

SAFETY DATA SHEET
CONVENTIONAL PAINT THINNER

Page: 4

8.2. Exposure controls

- Engineering measures:** Ensure there is sufficient ventilation of the area.
- Respiratory protection:** Respiratory protection not required.
- Hand protection:** Protective gloves.
- Eye protection:** Tightly fitting safety goggles.
- Skin protection:** Protective clothing.
- Environmental:** Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State:** Liquid
- Colour:** Colourless
- Odour:** Characteristic odour
- Evaporation rate:** Slow
- Oxidising:** Non-oxidising (by EC criteria)
- Solubility in water:** Not miscible
- Also soluble in:** Most organic solvents.
- Viscosity:** Non-viscous
- Boiling point/range°C:** 149 - 213
- Melting point/range°C:** No data available.
- Flammability limits %: lower:** 0.6
- upper:** 6.0
- Flash point°C:** 43
- Part.coeff. n-octanol/water:** 5 - 6.7 (log Pow)
- Autoflammability°C:** 250
- Vapour pressure:** 300 Pa @ 20 deg C
- Relative density:** 0.78
- pH:** Not applicable.
- VOC g/l:** 775

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Sources of ignition.

[cont...]

SAFETY DATA SHEET
CONVENTIONAL PAINT THINNER

Page: 5

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/l

Relevant hazards for substance:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Slightly bioaccumulable.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Floats on water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET
CONVENTIONAL PAINT THINNER

Page: 6

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Solvent reclamation/regeneration.

Waste code number: 08 01 11

Disposal of packaging: Retain for recovery.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET
CONVENTIONAL PAINT THINNER

Page: 7

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.