



TRACING PLUS - ACRYLIC LINE MARKER AEROSOL PAINT 750ML



High quality acrylic line marking paint with a satin finish, superb for interior walkways and other health and safety markings. Typical uses for this product are any type of interior delineation, such as line, walkway and stencil marking, also hazard zoning and lean management.

FEATURES AND BENEFITS:

- High covering opacity ensures quality line
- Crisp line formed by unique nozzle
- Fast drying
- Satin finish makes it easier to clean



White



Yellow



Black



Blue



Green



Orange



Red



CALL FREE: 0808 118 1922



MEONUK.COM

PREPARATION:**SURFACE PREPARATION:**

All surfaces must be free of any dust, damp or contamination.

Concrete:

Before applying Tracing Plus on new concrete, wait for 3 to 4 weeks to allow the concrete to dry (DTU standard) and the acid evaporation. Greater amounts of aerosol will be required for line marking on coarser concrete.

Asphalt:

It is advisable to wait at least 15 days before marking on a new asphalt coating to avoid damage to the paint. Depending on the climate conditions after laying the asphalt, this period may have to be extended by one or two weeks.

Painted Surfaces:

Tracing Plus is suitable for most floor coatings, however a compatibility test is always recommended prior to applying markings.

MIXING:

Shake the can vigorously upside down to mix the paint thoroughly (even after balls rattle).

APPLICATION:

Manually or with our application equipment (**Meon 4-Wheel Trolley**, **Meon 2-Wheel Applicator** or **Meon Pistol Handle Applicator**). Use upside down and adjust height of application in accordance with your required line width.

BEFORE USE:

Shake the can vigorously upside down to mix the paint thoroughly even after balls have been heard clearly.

The surface to be painted must be well prepared for an excellent adherence of the paint. Clean surface to be free of dust, dirt and grease. At the time of application, surface must be dry and temperature not less than 5°C for optimal performance.

For a good quality line, the first application must be a thin coat. The second and possibly third must be carried out more slowly so that a good deposit of paint is achieved.

AFTER USE:

Purge can in upright position (until only gas is released), to clean the valve and diffuser.

Do not apply when the air or surface temperature is below 5°C or less than 3°C above dew point, or if this is likely to occur during the curing period.

Do not apply when there is rain, mist, fog, or snow imminent; when humidity is high or the surface is wet with condensation or likely to be during the drying period.

CURING:

Touch Dry: 5 to 10 mins @ 15°C.

Traffic Time: 15-20 min @ 15°C

TECHNICAL:**COVERAGE:**

Typically 80m line @ 50mm per 750ml can.

AFTERCARE AND MAINTENANCE:

To ensure the best cleanable finish, lines can be covered by **Meon Protect Line** varnish to increase time lasting and resistance to dirt. Use water and mild detergent to wash line.

STORAGE:**STORAGE CONDITIONS:**

The aerosols must be kept from 5 to 25°C and from 50 to 60% relative humidity. Do not expose to temperatures above 50°C. To be kept out of any source of ignition, heat or direct sunlight.

SHELF LIFE:

12 months when stored under cover, in original unopened containers, in accordance with Storage Condition guidelines listed above.

SIZES AVAILABLE:

Available in 750ml aerosols - 6 cans / box.

HEALTH AND SAFETY:

Familiarise yourself with the material safety data sheets before using this product. If you need a copy please call our technical team on 023 9220 0606.

**MEON UK**

TEL: +44 (0)808 118 1922

EMAIL: mail@meonuk.com

WEB: meonuk.com

MEON IRELAND

TEL: +353 (0)1 840 7647

EMAIL: info@meonireland.com

WEB: meon.ie