



EXTERIOR



COMPO-CLEAN

CLEANER DEGREASER FOR COMPOSITE WOODS

Product description	COMPO-CLEAN is a composite wood cleaner that quickly and easily removes all types of dirt (grease, stains, moss, pollution...). Ready to use, COMPO-CLEAN works straight from the bottle, simply apply, scrub and rinse with water. Can be used on vertical and horizontal surfaces - cladding, decking...
Properties	<ul style="list-style-type: none"> • Waterbased - Environmentally friendly. • Removes surface and ground in dirt. • Fast acting - from 5 minutes depending on the condition of the surface being cleaned. • Gel formula - Does not run. Easy to apply. • Does not contain solvents or paraffin. Will not attack plastic pool liners, stone, glass...
Basic uses	<ul style="list-style-type: none"> • Exterior use. • All types of composite wood. • Vertical and horizontal surfaces. • Ideal for grooved decking.
Technical data	<p>Colour: Yellow-orange. Solvent: Water. Specific gravity (at 20°C): 1.04 ± 0.05. Viscosity: Semi-fluid gel.</p> <p>Flash point: Not flammable. Shelf life: 1 year in original unopened container. Container size: 1L. VOC: < 1 g/l.</p>
Preparation	Always test a small area first. Protect all areas not to be cleaned, plants, shrubs etc including and especially aluminum parts. Wear suitable protection - gloves (rubber/nitrile), goggles or visor, clothing.
Application tools	Quality synthetic or nylon brush. Brush or roller (medium to long pile). Hose or pressure washer.
Good application practice	Shake or stir well before application. Do not dilute. Apply between +5°C to +35°C. Do not apply in direct sunlight or on hot wood. Always work the entire length of a board to a logical break. On vertical surfaces, clean from bottom to top and rinse from top to bottom to avoid streaking.
Application	Apply a thick layer of COMPO-CLEAN to the area to be cleaned. Large areas, should be cleaned in smaller sections. Leave the product to work for 5 minutes (longer if necessary depending on the nature of the dirt and contamination). Scrub with a stiff nylon or synthetic brush. Rinse with plenty of fresh clean water using the highest pressure source available or use a power washer (max 50 bars). If required repeat above procedure - difficult/stubborn staining. Allow surface to dry 2/3 good drying days before applying chosen finish.
Coverage	5-10 m ² /litre. Actual coverage will vary depending on application method, type, texture, age and porosity of the surface.
Clean-up	Water.
Storage	Store unused portion in in tightly closed plastic or glass container. Do not store in metal containers. Keep from freezing and high temperatures.
General Information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. OWATROL International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local OWATROL Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	May 2012.

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

08/12 - RCSTours 331 998 484

