



QP CAT

Availability		
Quantity per pallet	500	500
Packaging unit	10 x 0,1 kg	0,25 kg
Type of container	Carton	Can
Container code	01	84
Art. no.		
6249	■	■

Range of use ■ Accelerator in the Remmers QP System

Property profile ■ Accelerates full hardening

Possible system products > QP Top Plus (6240)
> QP Color Top Plus (6223)

Production of the mixture ■ **Mixing**
Add the entire quantity of the hardener (component B) to the basic compound (component A).
[ZBK_B_56]
Mix thoroughly with a slow-speed electric mixer (approx. 300 - 400 rpm).
Mix for at least 3 minutes.
Insufficient mixing is indicated by streaks forming.

Directions For professional users only!

■ **Conditions for use**
[ZBK_B_50]

The times given are reduced at higher temperatures and increased at lower temperatures, in particular in combination with high humidity.

Notes Unless otherwise specified, all of the values and application rates given above have been determined under laboratory conditions (20 °C) using standard colours. Slight deviations from these values may arise if the product is worked with on site.

[H_B_103]

[H_B_101]

[H_B_102]

Use sufficiently experienced personnel to ensure that surfaces are as even as possible.




Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

Tools / Cleaning

[ZBK_B_50]

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



Safety data / Regulations

For professional users only!

Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

Personal protective equipment

This information can be obtained from the current Safety Data Sheets and/or the relevant professional associations.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.