



PARACEM® DECO PRIMER

Water-based primer based on acrylic dispersions. Neutralises differences in the absorption characteristics of the substrate.

- Reinforces the substrate and reduces absorption
- Neutralises differences in absorption characteristics
- Prevents differences in the glossiness of the topcoat
- Very good hiding characteristics
- Improves topcoat adhesion

PARACEM® DECO PRIMER

DESCRIPTION

Water-based primer based on acrylic dispersions. Neutralises differences in the absorption characteristics of the substrate.

RECOMMENDED USE

Indoors, on various porous, unpainted surfaces (for example brick, slab work, concrete) before finishing them off with water-based paints

TECHNICAL DATA

Density:	± 1,35 (white - wit - blanc)
Gloss Level:	Matt
Gloss level at 60°:	Matt: 5%
Solids content in volume:	45% (white - wit - blanc)
Solids Content in weight:	58% (white - wit - blanc)

DRYING TIMES AT 20°C/RH 50%

Touch dry:	1,5 hours
Dry to recoat:	2-3 hours
Fully cured:	1 week

RECOMMENDED WET FILM THICKNESS

100 µm

RECOMMENDED DRY FILM THICKNESS

45 µm

THEORETICAL CONSUMPTION

8 - 10 m²/l

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application (see DIN 53220).

SURFACE PREPARATION

Clean the substrate and remove all grease. Paracem Deco Primer may be directly applied over lightly porous substrates and old, cleaned paint layers if they are in good condition. Highly porous substrates, smooth plaster and water-resistant gypsum board: use Pegafix in 1 or 2 layers of Paracem Deco Primer. Use Pegaprim Isofix or Pegamat RL to insulate water spots or nicotine stains.

DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION CONDITIONS

Apply at a temperature of minimum 5°C and a R.H. of maximum 80%

APPLICATION & THINNING: BRUSH

Apply undiluted.

APPLICATION & THINNING: ROLLER

Apply undiluted.

APPLICATION & THINNING: AIRLESS SPRAY

Apply undiluted.

Nozzle: 011 - 015 / Pressure: 180 - 200 bar.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Apply undiluted.

CLEANING OF EQUIPMENT / SPILLS

Water

SAFETY DATA

VOC level:	30 g/l
VOC ready mix:	30 g/l
VOC category:	A/g
VOC limit:	30 g/l
Flashpoint:	Not flammable
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

2 years from date of production when kept in unopened cans, original packaging, stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/09/2018

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zeltem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu