

RUST-OLEUM
— INDUSTRIAL —



ULTRA MASONRY MATT



Very high-quality paint for exterior walls

- S.R.E.P. technology
- High water vapour permeability
- Dirt-repellent and rainproof
- Scrub-resistant, Class 1 (DIN EN 13300)
- Optimum flow

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

ULTRA MASONRY MATT

DESCRIPTION

Very high-quality, matt paint for exterior walls based on a silicone resin emulsion. The S.R.E.P. technology (Silicon Resin Emulsion Paint) gives this product dirt-repellent properties and high water vapour permeability/rain-sealing performance. Scrub-resistance to Class 1, excellent resistance to weathering and alkalinity and resistant to the effects of changing weather conditions. Ideally suited for a long-lasting finish where the demands are high. For exterior use.

RECOMMENDED USE

Mainly intended for external walls that need to meet high standards in relation to moisture retention due to its superior water vapour permeability. Suitable surfaces are: existing wall paint layers, cement and plasterwork, concrete, brick, etc.

RECOMMENDED SYSTEM

General: The surface must have a load-bearing capacity and must be fully set, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. When using externally, remove all algae and moss.

New, untreated substrates

- Prime highly absorbent surfaces in their entirety using Stabilising primer.
- Thoroughly clean powdery surfaces. Prime with Stabilising primer after allowing to dry.
- Paint to cover after allowing to dry.

Existing intact coats of wall paint

- Clean using Paint cleaner.
- Paint to cover after allowing to dry.

Existing, non-load-bearing coats of wall paint

- Remove loose parts.
- Thoroughly wash powdery coats and allow to dry.
- Carry out any repairs.
- Prime with Stabilising primer.
- Paint to cover after allowing to dry.

Contamination caused by nicotine, damp, rust or soot

- Clean thoroughly using Paint cleaner.
- Treat surface/contamination using Sealing primer.

The aforementioned systems form a general description of the most common surfaces. Please contact Rust-Oleum for specific applications and/or detailed advice.

TECHNICAL DATA

Density:	1.48
Gloss Level:	Matt
Gloss level at 85°:	6%
Solids content in volume:	40%

DRYING TIMES AT 20°C/RH 50%

Touch dry:	2 h
Dry to recoat:	6 h

RECOMMENDED WET FILM THICKNESS

200 µ

RECOMMENDED DRY FILM THICKNESS

80 µ

THEORETICAL CONSUMPTION

Approx. 5 m²/litre per coat for optimum protection

PRACTICAL CONSUMPTION

Actual consumption depends on the nature and the structure of the surface and the application method.

SURFACE PREPARATION

The surface must have a load-bearing capacity and must be fully set, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. When using externally, remove all algae and moss.

DIRECTIONS FOR USE

Stir thoroughly prior to use. Dilute the first coat on a untreated stable support with a maximum of 10% water. Apply in 1 or 2 coats using a suitable brush or paint roller. Always work wet-on-wet to prevent visible brush strokes. Retouch all lengths in the same direction. Do not retouch when drying.

APPLICATION CONDITIONS

Do not use at temperatures below +8°C. Only use when the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain or when frost is expected. Do not apply outdoors in direct sun. When using this product, always use the necessary personal protective equipment. Always ventilate in a suitable way during use.

Water and soap

SAFETY DATA

VOC level:	5 g/l
VOC category:	A/a
VOC limit:	30 g/l
Flashpoint:	Not flammable
Remarks regarding safety:	Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.

SHELF LIFE

Minimum of 12 months in tightly closed original packaging in a dry, cool and frost-free place.

Date issued: 20/06/2019

Available colours & pack sizes : Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer : The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu