



# PRODUCT DATA SHEET

## Centrecoat Aquamide

<b>DESCRIPTION:</b>	A two pack water based epoxy system, giving a high build, durable hard smooth finish.
<b>PERFORMANCE &amp; USE:</b>	Suitable for labs, warehouses, garages, factory walkways & any other areas of high traffic.
<b>COLOUR RANGE:</b>	Colour Card & Colour Matching
<b>FINISH:</b>	Gloss
<b>VOLUME SOLIDS:</b>	55%
<b>SPECIFIC GRAVITY:</b>	1.2-1.3
<b>STORAGE/LIFE:</b>	Store between 5 & 25°C. <b>Always replace lid after use.</b> 6 months in unopened containers.
<b>AVERAGE DRYING TIME:</b>	8 hours @ 20°C @ 60% RH
<b>OVERCOATING TIME:</b>	16 hours @ 20°C
<b>PACK SIZES:</b>	5 Litres (Composite mix—base and curing agent)
<b>THINNER/CLEANER:</b>	Water
<b>FLASHPOINT:</b>	N/A
<b>COVERAGE:</b>	Approx 8m <sup>2</sup> per litre depending on application & substrate
<b>METHOD OF APPLICATION:</b>	Brush or roller. Apply two coats . Please read accompanying Guidelines sheet (available online) before application.

Information given is based upon formulations in use at time of printing. We reserve the right to modify any product without notice although in the case of any major modification a new data sheet will be issued.