

PRODUCT DATA

MURFILL FLEECE (non woven)

DESCRIPTION

Polyester fibres.

RECOMMENDED USES

Reinforcement of the first coat of the Murfill-Waterproofing system on flat surfaces.

TECHNICAL DATA (according to the data given by the manufacturer)

Composition		:	100% polyester fibres
Quality		:	Non woven
Weight		:	50 g/m ²
Thickness		:	0,2 mm
Traction force in N/5 cm	By warp	:	± 110
	By weft	:	± 100
GRAB elongation in %	By warp	:	± 32
	By weft	:	± 35
Resistance to	UV	:	Good - behind glass 7 to 10 years
	Temperature	:	Good – 160°C
	Acids	:	Good
	Alkali	:	Good
Thermal retraction at 40°C		:	No tests, according to manufacturer < 1%
Dimensions	Widths	:	16 cm en 100 cm
	Roll length	:	100 m
Tolerances	Width	:	Geen
	Length	:	- 0 m + 1 m

Rust-Oleum Netherlands B.V.
Blaak 1, 4704 RJ
P.O. Box 138, 4700 AG
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zeltem
Halen, Belgium
T +32 (0)13 480 200
F +32 (0)13 480 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Lau-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 60
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu