

PRODUCT DATA

Dacfill SB Top Coat

DESCRIPTION

Liquid applied 1 component ultra high solids moisture activated elastomeric urethane coating. Topcoat for the Dacfill SB waterproofing system.

MAIN PROPERTIES

High build coating that provides a durable, long term waterproofing system. Dacfill SB is to be used as topcoat on Dacfill SB Embedment Coat.

RECOMMENDED USES

For all types of pitched and flat roofs. Used as waterproofing topcoat in reinforced and unreinforced Dacfill SB waterproofing membrane systems.

TECHNICAL DATA

Appearance:	Semi Gloss
Colour:	Dove Grey
Density:	1.28 kg/litre
Solids Content:	In volume: 80%
	In weight: Approx 85%
Recommended film thickness:	Wet film: 0.5 - 1.0 mm per coat (depending on system)
	Dry film: 0.4 - 0.8 mm per coat (depending on system)
VOC-content:	262 g/l max.
Ready-for-use mixture:	262g/l max.
Category:	A/i
EU Limit values:	600 g/l (2007) / 500 g/l (2010)

Drying times	20°C/50% r.h.
To touch:	4 hours
To recoat:	12 hours and within 7 days
Full hardness	16 hours
Note:	Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures

Coverage

Theoretical:	1 - 2m ² per litre per coat
Practical:	Dependant on surface profile, reinforcement where applicable etc.

SURFACE PREPARATION

Dacfill SB Topcoat is to be used as a topcoat on Dacfill SB Embedment Coat. Contact Technical Service department for further advice.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION & THINNING

Brush:	Possible, do not dilute.
Roller:	Possible, do not dilute.
Air-atomised spray:	Possible, do not dilute.
Airless spray:	Possible, do not dilute.
Cleanup:	Thinner 160.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com

PRODUCT DATA

Dacfill SB Top Coat

APPLICATION CONDITIONS

Minimum 5°C in well ventilated areas and fair conditions.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

12 months from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at maximum 25°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com