



Timberex Hard Wax Oil

*An Environmentally Friendly and Fast Drying Oil
for Floors and Wood Worktops*



Timberex Hard Wax Oil greatly enhances colours and grain and allows wood to age naturally into rich varying tones. Can be used on wood floors and worktops.

- Made from fast curing natural plant oils and wax
- Available in matt or satin finish
- Same day application and finish
- Easy to apply
- Easily refurbished
- Does not leave swirl marks



The Finest Natural Protection



Timberex Hard Wax Oil

*An Environmentally Friendly and Fast Drying Oil
for Floors and Wood Worktops*

DESCRIPTION

Timberex Hard Wax Oil is the result of the latest scientific research regarding the appropriate treatment for wood surfaces. Environmentally friendly, micro-porous, water repellent, dirt and wear resistant. Will not crack, peel, flake or blister. It is resistant against wine, beer, coffee, tea, fruit juices, and fizzy drinks. Safe to humans, animals and plants when dry.

OILS & HARD WAX

The oils penetrate deeply into the wood surface, protecting it from the inside and keeping it healthy and elastic, whilst the hard wax protects the surface making the wood hardwearing, non slip and easy to maintain. Timberex Hard Wax Oil becomes a permanent part of the wood and requires no sanding when renovating.

INGREDIENTS

Timberex Hard Wax Oil is based on a mixture of natural oils and waxes from plants such as Linseed and Soya and harmless odourless solvents. Carnauba wax is used to accelerate the drying of the oil and provide a beautiful finish. None of our products are harmful to neither human, animal or plant life. None of our products need to carry any warning symbols and follow strict UK and EU legislation. All Timberex Material Safety Datasheets are readily available to all our customers and can be downloaded from our website www.timberex.com or by contacting your local Timberex dealer or by contacting Timberex: Technical Hotline: 0032 13 460 200

AVAILABILITY

Available in 1, 2.5 and 5 litre tins.
Available in SATIN or MATT version.

COVERAGE

15m² - 20m² per litre.

STORAGE

Timberex Hard Wax Oil should be stored at 20°C - 30°C for 8 hours prior to use. Ensure that the oil is stirred prior and during use.

PREPARATION

The wood surface must be clean and dry. Any varnish or lacquer must be sanded off using grade 120 for the final sanding. Clean the surface using Timberex Bio-C. As soon as the surface is dry the application of Timberex Hard Wax Oil can begin. Please read the instructions carefully before application.

APPLICATION

Due to the fast curing nature of this product, application can be completed in one day. We always recommend to test on a small area if possible. Stir the product thoroughly before and during use to ensure consistent dispersion of the carnauba wax.

1. Apply a thin coat of Timberex Hard Wax Oil using a natural brisal brush or roller. Accidental splashes on surrounding areas should be removed immediately with a cloth.
2. Wait 3 hours before applying an additional coat using the same method as above.
3. After 15 minutes, remove any excess oil using a cotton cloth. Alternatively use a buffer with a red or white nylon pad.
4. Let the surface dry overnight while the oil hardens. The surface can be taken into light use the following day. The surface will gradually become more water-resistant over the following few days. Only vacuum the surface for the first five days, any liquid spillages should be removed immediately during this period.

CLEANING

Timberex Bio-C Cleaner is recommended for use on all oil treated surfaces. The cleaner is pH-neutral and will not leave any grey film on the surface. Use the right mixture and damp cloth for regular cleaning. Rule of thumb: The surface must be dry within 5-10 minutes or too much water has been used.

MAINTENANCE

Use Timberex Hard Wax Oil for rejuvenating the surface on a regular basis (Once a year or when needed). This will also gradually build more resistance to wear and tear, eliminating the need for re-sanding and re-application.

HEALTH & SAFETY

The product is not hazardous or dangerous to inhale. Ensure good ventilation when using the oil. All Material Safety Data sheets are available by contacting Timberex International direct or one of our dealers worldwide. These are also available for download from our website www.timberex.com

IMPORTANT INFORMATION

Applicators, cloths etc. impregnated with the product should be put in a bucket of water immediately after use to eliminate any risk of spontaneous combustion common in some natural drying oils based on linseed. Place the bucket outside the building. The contents must be disposed according to local regulations. The Company and its representatives are often asked to comment on the potential uses of Timberex products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Timberex International.



Timberex International
RUST-OLEUM MATHYS
Kolenbergstraat 23
B-3545 Zelem - Belgium
Tel: +32 (0)13 460 0200 - Fax: +32 (0) 13 460 0219
www.timberex.com

