

Centrecoat™

ProStrip



Technical Data Sheet

PRODUCT DESCRIPTION

Centrecoat ProStrip is a water based, low odour, easy to use white gel with a pleasant almond odour. Ideal for use by large contractors, painters & decorators, furniture restoration companies, flooring and decking contractors, artex removal specialists, Centrecoat ProStrip is strong yet much safer than conventional stripping solvents and provides an excellent methylene chloride replacement.

PROPERTIES

Water based and low odour.
Non-corrosive.
Non-ozone depleting and low VOC.
Safer – non-flammable.
Easy to apply gel.
Extra strong for tougher finishes.
Fast acting and slow drying.

RECOMMENDED APPLICATION METHODS

Apply a generous, even coat by brush, roller or airless spray.
Ideal for stripping paint, varnish, graffiti, Artex, stains, lacquer, etc.
Safe to use on wood, metal, brick, stone, fibreglass and more.
If leaving overnight cover with plastic to help the stripping process.
Never let the product dry out.

SUITABLE USES

External: Widely used for Buildings, Boats, Railings, Graffiti, Wood stain (decking ,sheds, etc).
Internal: Class O upgrade schemes, Staircases, Walls, Ceilings, Artex, Graffiti.

TECHNICAL

State:	Liquid
Colour:	White
Odour:	Barely perceptible
Evaporation rate:	Slow
Solubility in water:	Soluble
Viscosity:	Viscous

COVERAGE

Theoretical: 1 to 4 m² per litre.

APPLICATION TIMES

Approximate times for stripping:

Varnish:	5 – 30 minutes
Paint:	5 – 30 minutes
Two pack varnish :	30 – 60 minutes
Heavy multi layered paint:	90 minutes – overnight
Two pack lacquer:	30 minutes – 4 hours
Graffiti:	5 minutes – 4 hours

Times are dependent on number of coating layers, and therefore may be longer than stated.

PACKAGING

Centrecoat ProStrip is a single pack product.
Supplied in 1, 5 and 25 litre containers.
Store between 5 and 25°C.