

#### Description

Centrecoat R26 is a powerful and effective pretreatment for new tanilised timber prior to the application of paints or stains. Normally, without using this treatment, new tanilised wood would need to be weathered prior to coating. Centrecoat R26 works by removing the tannins from the surface of the wood so coatings can penetrate the wood deeper without the risk of failure.

Centrecoat R26 also benefits from being:

- A degreasing cleaner for wood
- Removes stubborn greasy stains and soiling
- Suitable for the heavy duty cleaning of wood decking, cladding and other exterior wood
- Continues to work for weeks after use

#### Advantages & Characteristics

- Effectively removes tannins from new timber
- Powerful and effective degreasing cleaner
- Does not alter the appearance of wood surfaces being cleaned • Fast acting and low odour
- Concentrated
- Biodegradable
- Removes organic soiling

#### Application

Always test apply on a small hidden portion of the substrate. Shake the container well before use.

To Use As Pretreatment For New Tanilised Timber:

Apply liberally and work in to the wood using a scrubbing brush. Allow to act for 5 - 10 minutes. Wash off with a hose

To Use As A Cleaner:

- Can be used neat on heavy contamination or can be diluted by adding 1 part product with up to 10 parts water depending on the staining to be removed
- For use as maintenance: 1 part to 20 parts water.
- Apply liberally using either a sprayer or brush and allow to act on lightly soiled surfaces for 1-2 minutes, on heavily soiled surfaces for 5-10 minutes
- For removing deep penetrating lubricating oil and stains, it may be necessary to apply the product twice allowing 10 minutes between applications
- Agitate with a firm bristle brush and rinse down thoroughly with clean water

#### Technical Data

- Colour: Pale Yellow
- Physical State at 20°C: Liquid
- Specific Gravity at 20°C: 1.02
- pH: 13.5
- Boiling Point: 100°C
- Density: 1.0 Kg/litre
- Solubility in Water: Fully soluble
- Flash Point: Non applicable

The above times are a guide only. These times can vary due to prevailing site conditions. The typical physical properties given above are derived from testing in a controlled laboratory environment. Results derived from testing field-applied samples may vary dependent upon site conditions.

#### Coverage Rate

Coverage depends on the porosity of the substrate. The values below are given only as an indication:

- 6-7m<sup>2</sup>/litre undiluted
- 10-15m<sup>2</sup>/litre diluted, depending on the surface

#### Clean Up / Thinning

Clean tools and equipment immediately after use with fresh water.

#### Storage

24 months following the production date when kept in the original unopened containers, stored in recommended conditions.

#### Shelf Life

Keep in a cool, dry place. Keep away from extreme cold, do not store in conditions below 5°C. 24 months following the production date when kept in the original unopened containers, stored in recommended conditions.

#### Packaging

Available in 5 Litres

#### Health and Safety

See Safety Data Sheet available from [Promain.co.uk](http://Promain.co.uk)

Wear protective gloves and glasses, and appropriate clothing whilst using the product. Do not dilute or mix with any other product. Do not apply during rain or frost and when surface and air temperature is < 5°C and > 30°C. Once cleaned it is recommended to protect the surface as soon as possible.

**KEEP OUT OF THE REACH OF CHILDREN & ANIMALS**