

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 1

Compilation date: 08/06/2015 Revision date: 23/01/2016 Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Product code: R104

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Paint and varnish remover. Restricted to industrial use and to professionals approved in certain EU member states-verify where use is allowed

1.3. Details of the supplier of the safety data sheet

Company name: Promain UK Limited

Promain House

C1 Pierson Court

Hitchin, Hertfordshire

SG4 0TY

Tel: +44 (0) 1462 421333

Email: info@promain.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1462 421333 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 2: H371; STOT SE 3: H335; STOT SE 3: H336; Acute Tox. 4: H302+312+332; Carc. 2: H351; Eye Irrit. 2: H319; STOT RE 2: H373; Skin Irrit. 2: H315

Most important adverse effects: Harmful if swallowed, in contact with skin or if inhaled. May cause damage to organs liver/blood through prolonged or repeated exposure. Causes serious eye irritation. Suspected of causing cancer . May cause respiratory irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.

H371: May cause damage to organs liver/blood through prolonged or repeated exposure.

H319: Causes serious eye irritation.

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 2

- H351: Suspected of causing cancer .
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS07: Exclamation mark
GHS08: Health hazard



Signal words: Warning

- Precautionary statements:** P102: Keep out of reach of children.
P202: Do not handle until all safety precautions have been read and understood.
P233: Keep container tightly closed.
P260: Do not breathe fumes/vapours.
P262: Do not get in eyes, on skin, or on clothing.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P315: Get immediate medical advice/attention.
P309+311: IF exposed or if you feel unwell: Call a POISON CENTER/doctor.
P405: Store locked up.
P501: Dispose of contents/container to a licenced waste contractor.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DICHLOROMETHANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-838-9	75-09-2	-	Carc. 2: H351	>45%

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 3

METHANOL

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	2.9-9.9%
-----------	---------	---	---	----------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove affected person from source of contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention promptly if symptoms occur after washing.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 4

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DICHLOROMETHANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	350 mg/m ³	1060 mg/m ³	-	-

METHANOL

UK	266 mg/m ³	333 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

DNEL/PNEC Values

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 5

Hazardous ingredients:

METHANOL

Type	Exposure	Value	Population	Effect
DNEL	Dermal - long term	40mg/kg/day	Workers	-
DNEL	Inhalation - Long term	260mg/m3	Workers	-
DNEL	Dermal - Short term	40mg/kg/day	Workers	-
DNEL	Inhalation - Short term	260 mg/m3	Workers	-
DNEL	Dermal - Long term	8 mg/kg/day	Consumers	-
DNEL	Inhalation - Long term	50 mg/m3	Consumers	-
DNEL	Dermal - Short term	8 mg/kg/day	Consumers	-
DNEL	Dermal - Short term	50 mg/m3	Consumers	-
DNEL	Oral - Short term	8 mg/kg/day	Consumers	-

8.2. Exposure controls

Engineering measures: Effective ventilation in processing areas, and for the drying of stripped articles: local exhaust ventilation at strip tanks supplemented by forced ventilation in those areas, to minimise exposure and to ensure compliance with relevant exposure limits. All handling to take place in well-ventilated area. Explosion-proof general and local exhaust ventilation.

Respiratory protection: Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely. Positive air supplied RPE is recommended.

Hand protection: Protective gloves.

Eye protection: Ensure eye bath is to hand. Wear eye/face protection. Wear approved chemical safety goggles at all times. Ensuring they are tightly fitted.

Skin protection: Wear suitable protective clothing and gloves. Gloves should be changed when permeation is likely. PVC has a breakthrough time of approximately 5 minutes for methylene chloride.

Environmental: An environmental assessment must be made to ensure compliance with local environmental legislation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Off-white

Odour: Strong DCM odour

Evaporation rate: Moderate

Solubility in water: Slightly soluble

Viscosity: Viscous

Boiling point/range°C: >35

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 6

Flash point°C: 60 - 93
Autoflammability°C: No data available.
Relative density: 1.25 +/- 0.5
VOC g/l: 970

upper: No data available.
Part.coeff. n-octanol/water: No data available.
Vapour pressure: 355 at 20 deg C
pH: Approx. 7

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DICHLOROMETHANE

ORL	MUS	LD50	4770	mg/kg
ORL	RAT	LD50	5350	mg/kg
SCU	MUS	LD50	6460	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 7

ORL	RAT	LD50	5628	mg/kg
-----	-----	------	------	-------

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: CARCINOGENICITY: Chronic inhalation studies in mice have shown increases in lung and liver tumours, when exposed to concentrations of methylene chloride well in excess of the occupational exposure limit.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
Methanol-Aquatic plants	96H EC50	22000	mg/l
Methanol-Aquatic plants	48H EC50	1000	mg/l
Methanol - Aquatic plants	48H LC50	10000	mg/l
DCM-FISH marine water	96H LC50	97	mg/l
DCM-Aquatic invertebrates:marine water	48H LC50	109	mg/l
DCM-Aquatic invertebrates:fresh water	48H LC50	27	mg/l
Methanol - Aquatic plants	96H EC50	22000	mg/l
DCM-FISH fresh water	96H LC50	193	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 8

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of waste and residues in accordance with local authority requirements. Confirm disposal procedures with environmental engineer and local regulations. Do not allow runoff to sewer, waterway or ground. Contact specialist disposal companies.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2810

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 6.1

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Restricted to industrial use and to professionals approved in certain EU member states-verify where use is allowed. EU decision number 455/1009/EC 6th May 2009. EU

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 9

Legislation: DECISION No455/2009/EC of the European Parliament and of the Council of 6 May 2009 Amendment to Annex I to Directive 76/769/EEC - Applicable to sales within the European Union. Industrial users require the following provisions : (a) to (e) below
(a) effective ventilation in all processing areas, in particular for the wet processing and the drying of stripped articles: local exhaust ventilation at strip tanks supplemented by forced ventilation in those areas, so as to minimise exposure and to ensure compliance, where technically feasible, with relevant occupational exposure limits; (b) measures to minimise evaporation from strip tanks comprising: lids for covering strip tanks except during loading and unloading; suitable loading and unloading arrangements for strip tanks; and wash tanks with water or brine to remove excess solvent after unloading. (c) measures for the safe handling of dichloromethane in strip tanks comprising: pumps and pipework for transferring paint stripper to and from strip tanks; and suitable arrangements for safe cleaning of tanks and removal of sludge; (d) personal protective equipment that complies with Directive 89/686/EEC comprising: suitable protective gloves, safety goggles and protective clothing; and appropriate respiratory protective equipment where compliance with relevant occupational exposure limits cannot be otherwise achieved; (e) adequate information, instruction and training for operators in the use of such equipment. National Regulations: Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

[cont...]

SAFETY DATA SHEET

Centrecoat R104 Strong Adhesive Remover & Paint Stripper

Page: 10

that no other routes of exposure cause the hazard>.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.