



Safety Data Sheet

Copyright, 2015, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-2356-5	Version number:	4.00
Revision date:	01/06/2015	Supersedes date:	10/07/2014
Transportation version number:	1.00 (30/07/2010)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Product Identification Numbers

GR-2001-0225-3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Skin Sensitization, Category 1A - Skin Sens. 1A; H317
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) |

Pictograms



Ingredient	CAS Nbr	% by Wt
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	0.1 - 1
1,2-Benzisothiazol-3(2H)-one	2634-33-5	< 0.1

HAZARD STATEMENTS:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260E	Do not breathe vapour or spray.
P262	Do not get in eyes, on skin, or on clothing.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P331	Do NOT induce vomiting.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

39% of the mixture consists of components of unknown acute oral toxicity.
39% of the mixture consists of components of unknown acute dermal toxicity.
49% of the mixture consists of components of unknown acute inhalation toxicity.
Contains 6% of components with unknown hazards to the aquatic environment.

EU VOC Directive (2004/42/EC) labelling: 2004/42/EC IIA(jWB)(140)

109 g/l

Notes on labelling

Nota P applied to CASRN 64742-95-6.

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Skin sensitization based on vendor test data of raw material.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Non-hazardous ingredients	Trade Secret		30 - 60	
Acrylic acid-butylacrylate-2-hydroxyethyl methacrylate-methyl methacrylate copolymer	Trade Secret		15 - 40	
NUC - Titanium Dioxide	13463-67-7	EINECS 236-675-5	1 - 10	
C.I. pigment yellow 110	5590-18-1	EINECS 226-999-5	1 - 5	
2-Dimethylaminoethanol	108-01-0	EINECS 203-542-8	1 - 5	Flam. Liq. 3, H226; Acute Tox. 3, H331; Acute Tox. 4, H312; Acute Tox. 4, H302; Skin Corr. 1B, H314; STOT SE 3, H335 (CLP)
Bismuth vanadium tetraoxide	14059-33-7	EINECS 237-898-0	1 - 5	STOT RE 2, H373 (Self Classified)
Solvent naphtha (petroleum), light aromatic	64742-95-6	EINECS 265-199-0	1 - 5	Asp. Tox. 1, H304 - Nota P (CLP) Flam. Liq. 3, H226 (Vendor) Skin Irrit. 2, H315; STOT SE 3, H336 (Self Classified)
1,2,4-Trimethylbenzene	95-63-6	EINECS 202-436-9	1 - 5	Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 2, H411 (CLP)
2-Butoxyethanol	111-76-2	EINECS 203-905-0	1 - 5	Acute Tox. 3, H331; Acute Tox. 3, H311; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 (CLP)
High molecular weight block copolymer w/pigment affinic group	Mixture		0.5 - 1.5	
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	EINECS 204-809-1	0.1 - 1	Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Chronic 2, H411 (Self Classified)
Mesitylene	108-67-8	EINECS 203-604-4	0.1 - 1	Flam. Liq. 3, H226; STOT SE 3, H335; Aquatic Chronic 2, H411 (CLP)
1,2-Benzisothiazol-3(2H)-one	2634-33-5	EINECS 220-120-9	< 0.1	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Acute 1, H400,M=10 (CLP)

Please see section 16 for the full text of any H statements referred to in this section

Please refer to section 15 for any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep from freezing. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2-Dimethylaminoethanol	108-01-0	UK HSC	TWA:7.4 mg/m ³ (2 ppm);STEL:22 mg/m ³ (6 ppm)	
Benzene, trimethyl- 2-Butoxyethanol	108-67-8 111-76-2	UK HSC UK HSC	TWA:125 mg/m ³ (25 ppm) TWA:123 mg/m ³ (25 ppm);STEL:246 mg/m ³ (50 ppm)	Skin Notation
NUC - Titanium Dioxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m ³ ;TWA(respirable):4 mg/m ³	
Benzene, trimethyl-	95-63-6	UK HSC	TWA:125 mg/m ³ (25 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
2-Butoxyethanol	111-76-2	UK EH40 BMGVs	Butoxyacetic acid	Creatinine in urine	EOS	240 mmol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)
EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Coveralls - Disposable
Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Liquid.
Appearance/Odour	Faint musty odour; Yellow colour
Odour threshold	<i>No data available.</i>
pH	8.5

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Boiling point/boiling range	≥ 100 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	≥ 65 °C [<i>Test Method: Closed Cup</i>]
Autoignition temperature	≥ 415 °C
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	4,600 Pa [<i>@ 20 °C</i>]
Relative density	1.15 g/m ³ [<i>Ref Std: WATER=1</i>]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.15 g/ml

9.2. Other information

Volatile organic compounds (VOC)	109 g/l [<i>Test Method: Estimated</i>] [<i>Details: EU Definition (Part A and B mix)</i>]
Volatile organic compounds (VOC)	99 g/l [<i>Test Method: Estimated</i>] [<i>Details: EU Definition (Part A and B mix thinned 10%)</i>]
Percent volatile	48 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Accelerators

Alcohols.

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause target organ effects after ingestion. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Blood effects: Signs/symptoms may include generalised weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and hemoglobinemia.

Prolonged or repeated exposure may cause target organ effects:

Blood effects: Signs/symptoms may include generalised weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and hemoglobinemia. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE ₂₀ - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

NUC - Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
NUC - Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
NUC - Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Bismuth vanadium tetraoxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Bismuth vanadium tetraoxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.2 mg/l
Bismuth vanadium tetraoxide	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Butoxyethanol	Dermal	Rabbit	LD50 400 mg/kg
2-Butoxyethanol	Inhalation-Vapor (4 hours)	Rat	LC50 2.2 mg/l
2-Butoxyethanol	Ingestion	Rat	LD50 560 mg/kg
Solvent naphtha (petroleum), light aromatic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Solvent naphtha (petroleum), light aromatic	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Solvent naphtha (petroleum), light aromatic	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Dimethylaminoethanol	Dermal	Rabbit	LD50 1,220 mg/kg
2-Dimethylaminoethanol	Inhalation-Vapor (4 hours)	Rat	LC50 6 mg/l
2-Dimethylaminoethanol	Ingestion	Rat	LD50 1,803 mg/kg
1,2,4-Trimethylbenzene	Dermal	Rabbit	LD50 > 3,160 mg/kg
1,2,4-Trimethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
1,2,4-Trimethylbenzene	Ingestion	Rat	LD50 3,400 mg/kg
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Dermal	Rat	LD50 > 2,000 mg/kg
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Ingestion	Rat	LD50 > 500 mg/kg
Mesitylene	Dermal	Rabbit	LD50 > 3,160 mg/kg
Mesitylene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
Mesitylene	Ingestion	Rat	LD50 3,400 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
NUC - Titanium Dioxide	Rabbit	No significant irritation
Bismuth vanadium tetraoxide	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Irritant
Solvent naphtha (petroleum), light aromatic	Rabbit	Irritant
2-Dimethylaminoethanol	Rabbit	Corrosive
1,2,4-Trimethylbenzene	Rabbit	Irritant
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Rabbit	No significant irritation
Mesitylene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
NUC - Titanium Dioxide	Rabbit	No significant irritation
Bismuth vanadium tetraoxide	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Severe irritant
Solvent naphtha (petroleum), light aromatic	Rabbit	Mild irritant
2-Dimethylaminoethanol	official classification	Corrosive
1,2,4-Trimethylbenzene	Rabbit	Mild irritant
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Rabbit	Corrosive
Mesitylene	Rabbit	Mild irritant

Skin Sensitisation

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Name	Species	Value
NUC - Titanium Dioxide	Human and animal	Not sensitising
2-Butoxyethanol	Guinea pig	Not sensitising
Solvent naphtha (petroleum), light aromatic	Guinea pig	Not sensitising
2-Dimethylaminoethanol	Mouse	Some positive data exist, but the data are not sufficient for classification
1,2,4-Trimethylbenzene	Guinea pig	Not sensitising
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Mouse	Sensitising
Mesitylene	Guinea pig	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
NUC - Titanium Dioxide	In Vitro	Not mutagenic
NUC - Titanium Dioxide	In vivo	Not mutagenic
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Dimethylaminoethanol	In Vitro	Not mutagenic
2-Dimethylaminoethanol	In vivo	Not mutagenic
1,2,4-Trimethylbenzene	In Vitro	Not mutagenic
Mesitylene	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
NUC - Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
NUC - Titanium Dioxide	Inhalation	Rat	Carcinogenic.
2-Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Solvent naphtha (petroleum), light aromatic	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-Butoxyethanol	Dermal	Not toxic to development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-Butoxyethanol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-Butoxyethanol	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
Solvent naphtha (petroleum), light aromatic	Inhalation	Not toxic to female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Solvent naphtha (petroleum), light aromatic	Inhalation	Not toxic to male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Solvent naphtha (petroleum), light aromatic	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 500 ppm	2 generation

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

2-Dimethylaminoethanol	Inhalation	Not toxic to development	Rat	NOAEL 0.3 mg/l	during gestation
2-Dimethylaminoethanol	Ingestion	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	LOAEL 300 mg/kg	during gestation
2-Dimethylaminoethanol	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.13 mg/l	9 days
2-Dimethylaminoethanol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	LOAEL 300 mg/kg/day	during gestation
1,2,4-Trimethylbenzene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1.5 mg/l	during gestation
Mesitylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1.5 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-Butoxyethanol	Dermal	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Inhalation	blood	May cause damage to organs	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
2-Butoxyethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	poisoning and/or abuse
Solvent naphtha (petroleum), light aromatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Solvent naphtha (petroleum), light aromatic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Solvent naphtha (petroleum), light aromatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Dimethylaminoethanol	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL 0.09 mg/l	90 days
1,2,4-Trimethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Mesitylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Mesitylene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
NUC - Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.010 mg/l	2 years
NUC - Titanium Dioxide	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure
Bismuth vanadium tetraoxide	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.02 mg/l	28 days
2-Butoxyethanol	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	All data are negative	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	blood	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.12 mg/l	90 days
2-Butoxyethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	14 weeks
2-Butoxyethanol	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-Dimethylaminoethanol	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.13 mg/l	9 days
2-Dimethylaminoethanol	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.37 mg/l	9 days
1,2,4-Trimethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

1,2,4-Trimethylbenzene	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	heart endocrine system immune system	All data are negative	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	14 days
1,2,4-Trimethylbenzene	Ingestion	liver immune system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
Mesitylene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
Mesitylene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months
Mesitylene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Mesitylene	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Inhalation	heart endocrine system immune system	All data are negative	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	14 days
Mesitylene	Ingestion	liver immune system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Solvent naphtha (petroleum), light aromatic	Aspiration hazard
1,2,4-Trimethylbenzene	Aspiration hazard
Mesitylene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
C.I. pigment yellow 110	5590-18-1		Data not available or insufficient for classification			
2-Dimethylamin oethanol	108-01-0	Green algae	Experimental	72 hours	EC50	35 mg/l

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

2-Dimethylaminoethanol	108-01-0	Water flea	Experimental	48 hours	EC50	99 mg/l
2-Dimethylaminoethanol	108-01-0	Fathead minnow	Experimental	96 hours	LC50	81 mg/l
Non-hazardous ingredients	Trade Secret		Field		NOEC	>1,001 mg/l
Bismuth vanadium tetraoxide	14059-33-7		Data not available or insufficient for classification			
Solvent naphtha (petroleum), light aromatic	64742-95-6		Data not available or insufficient for classification			
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Water flea	Experimental	48 hours	EC50	88 mg/l
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Fathead minnow	Experimental	96 hours	LC50	36 mg/l
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Green algae	Experimental	72 hours	EC50	82 mg/l
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Green algae	Experimental	72 hours	NOEC	1 mg/l
Acrylic acid-butylacrylate-2-hydroxyethyl methacrylate-methyl methacrylate copolymer	Trade Secret		Data not available or insufficient for classification			
Mesitylene	108-67-8	Water flea	Experimental	48 hours	EC50	6 mg/l
Mesitylene	108-67-8	Ricefish	Experimental	48 hours	LC50	8.6 mg/l
Mesitylene	108-67-8	Green algae	Experimental	48 hours	EC50	53 mg/l
Mesitylene	108-67-8	Water flea	Experimental	21 days	NOEC	0.4 mg/l
1,2,4-Trimethylbenzene	95-63-6	Water flea	Experimental	48 hours	EC50	3.6 mg/l
1,2,4-Trimethylbenzene	95-63-6	Fathead minnow	Experimental	96 hours	LC50	7.72 mg/l
1,2,4-Trimethylbenzene	95-63-6	Mysid Shrimp	Experimental	96 hours	EC50	2 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	EC50	>1,000 mg/l
2-Butoxyethanol	111-76-2	Rainbow trout	Experimental	96 hours	LC50	1,474 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	48 hours	EC50	1,550 mg/l

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

2-Butoxyethanol	111-76-2	Crustacea	Experimental	96 hours	EC50	89.4 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	21 days	NOEC	100 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	NOEC	130 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Crustacea	Experimental	48 hours	EC50	0.062 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	4.4 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Algae	Experimental	72 hours	EC50	0.15 mg/l
NUC - Titanium Dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
NUC - Titanium Dioxide	13463-67-7	Sheepshead Minnow	Experimental	96 hours	LC50	>240 mg/l
NUC - Titanium Dioxide	13463-67-7	Fish	Experimental	30 days	NOEC	>100 mg/l
NUC - Titanium Dioxide	13463-67-7	Water flea	Experimental	30 days	NOEC	3 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Non-hazardous ingredients	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bismuth vanadium tetraoxide	14059-33-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	64742-95-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acrylic acid-butylacrylate-2-hydroxyethyl methacrylate-methyl methacrylate copolymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
NUC -	13463-67-7	Data not	N/A	N/A	N/A	N/A

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Titanium Dioxide		available or insufficient for classification				
1,2,4-Trimethylbenzene	95-63-6	Experimental Photolysis		Photolytic half-life (in air)	11.8 hours (t _{1/2})	Other methods
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)
2-Butoxyethanol	111-76-2	Experimental Biodegradation	14 days	BOD	96 % weight	OECD 301C - MITI test (I)
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Experimental Biodegradation	28 days	CO2 evolution	5 % weight	OECD 301B - Modified Sturm or CO2
1,2,4-Trimethylbenzene	95-63-6	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301C - MITI test (I)
Mesitylene	108-67-8	Experimental Biodegradation	14 days	BOD	0 % weight	OECD 301C - MITI test (I)
2-Dimethylaminoethanol	108-01-0	Experimental Biodegradation	14 days	BOD	60.5 % weight	OECD 301C - MITI test (I)
C.I. pigment yellow 110	5590-18-1	Estimated Biodegradation	28 days	BOD	0 % weight	OECD 301F - Manometric respirometry

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
C.I. pigment yellow 110	5590-18-1	Estimated Bioconcentration		Bioaccumulation factor	38	Estimated: Bioconcentration factor
2-Dimethylaminoethanol	108-01-0	Experimental Bioconcentration		Log Kow	-0.55	Other methods
Non-hazardous ingredients	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bismuth vanadium tetraoxide	14059-33-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	64742-95-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acrylic acid-butylacrylate-2-hydroxyethyl methacrylate-methyl methacrylate copolymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Experimental Bioconcentration		Log Kow	2.8	Other methods
2-Butoxyethanol	111-76-2	Experimental Bioconcentration		Log Kow	0.83	Other methods
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	Other methods
NUC - Titanium Dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods
Mesitylene	108-67-8	Experimental BCF-Carp	70 days	Bioaccumulation factor	342	Other methods
1,2,4-Trimethylbenzene	95-63-6	Experimental BCF-Carp	56 days	Bioaccumulation factor	275	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

080299 Wastes not otherwise specified

SECTION 14: Transportation information

GR-2001-0225-3

Not hazardous for transportation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2-Butoxyethanol	111-76-2	Gr. 3: Not classifiable	International Agency for Research on Cancer
NUC - Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Revision Changes:

Section 8: Eye/face protection information information was modified.

Section 01: 1.3. Details of the supplier of the safety data sheet heading information was modified.

Section 15: Carcinogenicity information information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 15: Regulations - Inventories information was modified.

Copyright information was modified.

Label: Signal Word information was modified.

Label: CLP Percent Unknown information was modified.

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Label: CLP Percent Unknown information was modified.
Label: CLP Percent Unknown information was modified.
Label: CLP Percent Unknown information was modified.
Label: CLP Precautionary - Prevention information was modified.
CLP: Ingredient table information was modified.
Section 8: Occupational exposure limit table information was modified.
OEL Reg Agency Desc information was modified.
Section 3: Reference to section 15 for Nota info information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Additional Health Effects heading information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 11: Health Effects - Skin information information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 11: Health Effects - Ingestion information information was modified.
Section 6: Accidental release personal information information was modified.
Section 6: Accidental release clean-up information information was modified.
Section 7: Precautions safe handling information information was modified.
Section 7: Conditions safe storage information was modified.
Section 8: Personal Protection - Skin/hand information information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.
Section 11: Single exposure may cause target organ effects heading information was modified.
Section 11: Prolonged or repeated exposure may cause target organ effects heading information was modified.
Section 11: Prolonged or repeated exposure may cause standard phrases information was modified.
Section 2: EU VOC Directive (2004/42/EC) heading information was added.
Section 02: EU VOC Directive (2004/42/EC) labelling information was added.
Section 02: EU VOC Directive (2004/42/EC) labelling information was added.
Section 8: Occupational exposure limit table information was added.
Section 11: Aspiration Hazard table - Name heading information was added.
Section 11: Aspiration Hazard table - Value heading information was added.
Section 11: Respiratory Sensitization text information was added.
Section 11: Skin Sensitization table - Name heading information was added.
Section 11: Skin Sensitization table - Species heading information was added.
Section 11: Skin Sensitization table - Value heading information was added.
Section 11: Serious Eye Damage/Irritation table - Name heading information was added.
Section 11: Serious Eye Damage/Irritation table - Species heading information was added.
Section 11: Serious Eye Damage/Irritation table - Value heading information was added.
Section 11: Skin Corrosion/Irritation table - Name heading information was added.
Section 11: Skin Corrosion/Irritation table - Species heading information was added.
Section 11: Skin Corrosion/Irritation table - Value heading information was added.
Section 11: Germ Cell Mutagenicity table - Name heading information was added.
Section 11: Germ Cell Mutagenicity table - Route heading information was added.
Section 11: Germ Cell Mutagenicity table - Value heading information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure table - Name heading information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure table - Route heading information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure table - Target Organ(s) heading information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure table - Value heading information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure table - Species heading information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure table - Test Result heading information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure table - Exposure Duration heading information was added.

3M Scotchkote WB Urethane Dicol 170, Warning Yellow (Part A)

Section 11: Specific Target Organ Toxicity - single exposure table - Name heading information was added.
Section 11: Specific Target Organ Toxicity - single exposure table - Route heading information was added.
Section 11: Specific Target Organ Toxicity - single exposure table - Target Organ(s) heading information was added.
Section 11: Specific Target Organ Toxicity - single exposure table - Value heading information was added.
Section 11: Specific Target Organ Toxicity - single exposure table - Species heading information was added.
Section 11: Specific Target Organ Toxicity - single exposure table - Test Result heading information was added.
Section 11: Specific Target Organ Toxicity - single exposure table - Exposure Duration heading information was added.
Section 11: Reproductive and/or Developmental Effects table - Name heading information was added.
Section 11: Reproductive and/or Developmental Effects table - Route heading information was added.
Section 11: Reproductive and/or Developmental Effects table - Value heading information was added.
Section 11: Reproductive and/or Developmental Effects table - Species heading information was added.
Section 11: Reproductive and/or Developmental Effects table - Test Result heading information was added.
Section 11: Reproductive and/or Developmental Effects text information was added.
Section 11: Carcinogenicity table - Name heading information was added.
Section 11: Carcinogenicity table - Route heading information was added.
Section 11: Carcinogenicity table - Species heading information was added.
Section 11: Carcinogenicity table - Value heading information was added.
Section 8: glove data - Material heading information was added.
Section 8: glove data - Thickness heading information was added.
Section 8: glove data - Breakthrough Time heading information was added.
Section 8: glove data value information was added.
Section 03: Reference to H statement explanation in Section 016 information was added.
Section 8: Skin protection - recommended gloves information information was deleted.
Risk phrase information was deleted.
Safety phrase information was deleted.
Section 2: Contains heading information was deleted.
Section 2: Safety phrases heading information was deleted.
Section 16: List of relevant R-phrases information was deleted.
Section 2: Indication of danger heading information was deleted.
Section 16: List of relevant R phrase information information was deleted.
Section 2: Risk phrases heading information was deleted.
Section 2: Indication of danger information information was deleted.
Section 2: Label ingredient information information was deleted.
Section 2: Notes on labelling heading information was deleted.
Section 2: Label remarks information was deleted.
Section 11: Exposure Duration table heading information was deleted.
Section 11: Test Result table heading information was deleted.
Section 3: Reference to R and H statement explanation in Section 16 information was deleted.
Section 2: 2.2 & 2.3. DSD/DPD heading information was deleted.
Section 2: R phrase reference information was deleted.
Label: Graphic information was deleted.
Label: Graphic information was deleted.
Label: Graphic Text information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk