



Technical Data Sheet

Blackfriar Kitchen Wood Oil

Blackfriar Kitchen Wood Oil revives and enhances your wooden household products. It protects surfaces with a durable, water repellent finish and is simple and safe to use.

Performance characteristics –

- Interior use.
- Water repellent.
- Satin finish.
- EN71-3 tested.
- Ideal for wooden worktops, chopping boards and trolleys.

Preparation - Ensure surface to be oiled is smooth, clean, dry and free of contamination. For surfaces previously treated with oils or waxes clean back the surface to bare timber with fine wire wool and white spirit, working along the grain. Hard finishes such as varnish or paint must be completely removed with Blackfriar Professional Paint and Varnish Remover. If the wood is to be coloured, apply Blackfriar Wood Dye prior to the Kitchen Wood Oil.

Application - Ensure the product is thoroughly shaken prior to use. Apply oil liberally by brush or rag. Leave for a few minutes for the oil to absorb into the wood then wipe off any surplus with a clean lint free cloth. Apply a second coat if required.

Thinning - Maximum 10% white spirit.

Limitations - New wood should be oiled once a week for the first month and then every month thereafter. Extra oiling may be required on heavily used surfaces. The oil should not leave a taste once it has completely penetrated the surface and any odour should disappear after a few days.

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an

ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Take extra care as application cloths and soiled cleaning rags may self ignite without warning. Lay cloths out flat in single layers to dry, or wash out thoroughly in warm soapy water before disposal. Remove as much product from application equipment as possible before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Contains: Naphtha (petroleum), hydrotreated heavy.
Flammable liquid and vapour.

May cause drowsiness or dizziness.

Keep out of reach of children. Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour.

IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower. Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: Neodecanoic acid, cobalt salt and 2-butanone oxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 700g/l (2007) 700g/l (2010.) This product contains a maximum of 700g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.