

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-161/263SL/264 (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Epoxy coating.

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity , Category 4	H302: Harmful if swallowed.
Skin corrosion , Category 1B	H314: Causes severe skin burns and eye damage.
Skin sensitisation , Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity , Category 3	H412: Harmful to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Corrosive	R34: Causes burns.
Harmful	R20/22: Harmful by inhalation and if swallowed.
Sensitising	R43: May cause sensitisation by skin contact.
Dangerous for the environment	R52/53: Harmful to aquatic organisms, may cause

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

long-term adverse effects in the aquatic environment.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H302
H314
H317
H412

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273

Avoid release to the environment.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

Hazardous components which must be listed on the label:

- 202-859-9 benzyl alcohol
- 220-666-8 3-aminomethyl-3,5,5-trimethylcyclohexylamine
- 216-032-5 m-phenylenebis(methylamine)
- 202-013-9 2,4,6-tris(dimethylaminomethyl)phenol

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
benzyl alcohol 100-51-6 202-859-9 01-2119492630-38-XXXX	Xn; R20/22	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 25 - < 50
3-aminomethyl-3,5,5-trimethylcyclohexylamine 2855-13-2 220-666-8 01-2119514687-32-XXXX	C; R34 Xn; R21/22 R43 R52-R53	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1C; H314 Skin Sens.1A; H317 Aquatic Chronic3; H412	>= 10 - < 20
m-phenylenebis(methylamine) 1477-55-0 216-032-5 01-2119480150-50-XXXX	Xn; R20/22 C; R34 R43 R52/53	Acute Tox.4; H302 Acute Tox.4; H332 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 10 - < 20
Hydrocarbons, C9, aromatics 64742-95-6 265-199-0 01-2119455851-35-XXXX	Xn; R65 R10 Xi; R37 R66 R67 N; R51/53	Flam. Liq.3; H226 STOT SE3; H335, H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 5 - < 10
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2 202-013-9 01-2119560597-27-XXXX Contains: bis[(dimethylamino)methyl]phenol <= 15 %	C; R34 R52/53	Skin Sens.1B; H317 1B; H314 Aquatic Chronic3; H412	>= 2,5 - < 5

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.



Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.

Risks : Health injuries may be delayed.
corrosive effects
sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields
Eye wash bottle with pure water
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm),
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: light yellow
Odour	: amine-like
Odour Threshold	: No data available
Flash point	: ca. 68 °C
Ignition temperature	: not applicable
Lower explosion limit (Vol%)	: No data available
Upper explosion limit (Vol%)	: No data available
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: ca. 11 at 20 °C
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: 4,9996 hPa
Density	: ca. 1,03 g/cm ³ at 20 °C
Water solubility	: Note: insoluble
Partition coefficient: n-octanol/water	: No data available
Viscosity, dynamic	: ca. 100 mPa.s at 20 °C
Viscosity, kinematic	: > 20,5 mm ² /s at 40 °C
Relative vapour density	: No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

benzyl alcohol :

Acute oral toxicity : LD50 Oral rat: 1.230 mg/kg

Acute inhalation toxicity : LC50 rat: 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

3-aminomethyl-3,5,5-trimethylcyclohexylamine :

Acute oral toxicity : LD50 Oral rat: 1.030 mg/kg

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg
Method: Converted acute toxicity point estimate

m-phenylenebis(methylamine) :

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

Acute oral toxicity : LD50 Oral rat: 930 mg/kg
Acute inhalation toxicity : LC50 rat: 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 Dermal rat: > 3.100 mg/kg

Hydrocarbons, C9, aromatics :

Acute oral toxicity : LD50 Oral rat: > 2.000 mg/kg
Acute dermal toxicity : LD50 Dermal rabbit: > 2.000 mg/kg

Skin corrosion/irritation

Product

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Product

No data available

Respiratory or skin sensitisation

Product

May cause an allergic skin reaction.

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : No data available

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9, aromatics :

Toxicity to algae : 2,6 - 2,9 mg/l, 72 h, Pseudokirchneriella subcapitata (green algae)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues.
This material and its container must be disposed of in a safe



way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1760
14.2 Description of the goods : CORROSIVE LIQUID, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
14.3 Class : 8
14.4 Packing group : III
Classification Code : C9
Labels : 8
Tunnel restriction code : (E)
14.5 Environmentally hazardous : no

IATA

14.1 UN number : 1760
14.2 Description of the goods : Corrosive liquid, n.o.s.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
14.3 Class : 8
14.4 Packing group : III
Labels : 8
14.5 Environmentally hazardous : no

IMDG

14.1 UN number : 1760
14.2 Description of the goods : CORROSIVE LIQUID, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
14.3 Class : 8
14.4 Packing group : III
Labels : 8
EmS Number 1 : F-A
EmS Number 2 : S-B
14.5 Marine pollutant : no

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

IMDG

Alkalis

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :



Corrosive

R-phrases(s)	:	R20/22 R34 R43 R52/53	Harmful by inhalation and if swallowed. Causes burns. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S-phrases(s)	:	S26 S36/37/39 S45	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Hazardous components which must be listed on the label:

- 202-859-9 benzyl alcohol
- 220-666-8 3-aminomethyl-3,5,5-trimethylcyclohexylamine
- 216-032-5 m-phenylenebis(methylamine)

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

REACH Information: All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

VOC-CH (VOCV) : 7,36 %

VOC-EU (solvent) : 50,65 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R10	Flammable.
R20/22	Harmful by inhalation and if swallowed.
R21/22	Harmful in contact with skin and if swallowed.
R34	Causes burns.
R37	Irritating to respiratory system.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52	Harmful to aquatic organisms.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor®-161/263SL/264 (B)



Revision Date 02.12.2014

Version 1.4

Print Date 02.12.2014

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Corr.	Skin corrosion
Skin Sens.	Skin sensitisation
STOT SE	Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

|| Changes as compared to previous version !