

**DESCRIPTION**

Johnstone's Anti Slip Flortred paint is a single pack finish which is suitable for use on internal concrete, steel and wooden floors in light to medium traffic areas as well as exterior use to highlight walkways, car park spaces and other markings. Not suitable for use on large external areas. It provides a semi gloss finish with a light aggregate for slip resistance. Tested to BS7976 Parts 1-3 for slip resistance, Anti Slip Flortred achieves a 'Low Slip Potential' classification according to the H.S.E. in both dry and wet conditions.

**RECOMMENDED USES**

Light to medium traffic areas, where slip resistance is essential, eg. walkways, doorways, ramps & steps. For exterior use to highlight walkways, car park spaces and other markings. Not suitable for large external areas.

**SPECIAL PROPERTIES**

Resistant to mild chemicals, water, oil and grease spillage. Slip resistant.

**COLOUR RANGE**

Princess Grey, Dark Grey, Tile Red.

**FINISH**

Semi-gloss.

**VOLUME SOLID**

48%

**COVERAGE**

Johnstone's Anti Slip Flortred Paint will cover at the rate of approximately 11 square metres per litre depending on the nature and porosity of the surface being painted.

**DRYING TIME**

Recoat after 16–24 hours under normal drying conditions.

**TRANSPORTATION & STORAGE**

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

**THINNER**

TC2 Thinner and Cleaner.

**VOC CONTENT**

HIGH VOC CONTENT 25–50%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 500g/l (2010).  
This product contains max 500g/l VOC.

**FILM THICKNESS**

Wet: 90µm, dry: 40µm.

**SIZE**

5 Litre.

**PREPARATION**

All surfaces to be painted should be clean, dry and free from loose or flaking material. New concrete or cement should be allowed to mature for several months before painting. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For further advice contact Technical Advisory. For additional information and free Johnstones Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

**APPLICATION**

Stir well before use. Apply by brush or roller which should be fully loaded for best results. Apply paint evenly by brush and avoid overspreading. Touch dry in 4-6 hours. Recoatable after 16-24 hours. To ease application, the first coat maybe thinned with up to 5% by volume of TC2 Thinner and Cleaner. Allow to dry overnight before applying a second coat, if required.

**CLEANING**

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with TC2 Thinner and Cleaner. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

**PRECAUTIONS**

- **WARNING**
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.