

RUST-OLEUM
INDUSTRIAL



THINNER 22



KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

THINNER 22

DESCRIPTION

Thinner with strong diluting capacity, based on aromatic hydrocarbons.

RECOMMENDED USE

Dilution of synthetic enamels and varnishes for airless application. Degreasing of metals and most wood types. Cleaning of "spots" of acrylic paints or acrylic fixing paints (e.g. on glass).

Cleaning and/or Thinning solution for the following products:

- Coating PRT
- Fassiclor
- Fillcoat Waterproofing
- Fillcoat Fibres Waterproofing
- NOXYDE Pegarust
- Primer 44HS
- PVDF Primer
- Vernac

TECHNICAL DATA

Density: 0,87

DRYING TIMES AT 20°C/RH 50%

DIRECTIONS FOR USE

See 'Recommended Use'. On substrates that are not attacked by Thinner 22 (e.g. glass, stoving enamel), spots of acrylic impregnation products (e.g. Pegafix, Parafix) and acrylic paints can be easily removed with a rag soaked in Thinner 22.

REMARKS

Boiling range: 160 - 180°C. Kb-value: 90. Aromatic content: 99%

SAFETY DATA

VOC level: 1150 g/l
Flashpoint: 41 °C
Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 05/04/2018

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Postbus 138
4700 AC Roosendaal
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Rust-Oleum UK Ltd.
PO Box 261
Chester-le-Street
DH3 9EH United Kingdom
T : +44 (0)2476 717 329
F : +44 (0)2476 718 930
info@rust-oleum.eu

Rust-Oleum France S.A.S.
11, rue Jules Verne - B.P. 60039
95322 St-Leu-La-Forêt Cedex
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu