



Asipo Internal

PRODUCT DATA

Description

The Asipo range has been specially formulated for use in high risk areas where humidity and condensation can lead to the growth of mould and algae. Asipo Internal is a superior water-based decorative emulsion for combating internal problems of mould growth. This product provides long-term protection from mould and algae and is designed to stop contamination and discolouration. Asipo Internal is economic and easy to apply, providing a long lasting durable finish.

Sealing/Primer

On new plaster a sealant coat is recommended, this can be achieved by thinning the paint by 10% with water.

Area of use

Internal wall and ceiling areas

Substrates

Masonry and plaster

Packing

5 litres

Physical Constants

Colours:	White and Magnolia (special colours on request)
Finish:	Matt & Silk
Volume solids:	48%
Theoretical spreading rate:	12 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.25 - 1.4
Dry to touch:	2 hours (20°C)
Overcoating time:	4 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush or roller
Thinner:	Water
Cleaning of tools:	Water

Surface condition

The surface should be stable, firm, dry and free of dust sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

Please refer to the Material Safety Data Sheet for further information.

For additional guidance please contact your local Technical Sales Representative.

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.