



**SAFETY DATA SHEET**  
PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 1

Compilation date: 08/09/2004

Revision date: 28/02/2018

Revision No: 4

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** PERFORMANCE EXTRA ANTIFOULING PAINT

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Company name:** FLAG Paints Ltd  
8 Springfield Road  
Springfield Industrial Estate  
Burnham on Crouch  
Essex  
CM0 8UA  
United Kingdom

**Tel:** +44 (0) 1621 785 173

**Fax:** +44 (0) 1621 785 393

**Email:** [sales@flagfinishes.co.uk](mailto:sales@flagfinishes.co.uk)

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0) 1621 785 173

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Eye Dam. 1: H318; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;  
Flam. Liq. 3: H226; Skin Sens. 1: H317

**Most important adverse effects:** Flammable liquid and vapour. Harmful if swallowed. May cause an allergic skin reaction.  
Causes serious eye damage. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

[cont...]

# SAFETY DATA SHEET

## PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 2

GHS05: Corrosion

GHS07: Exclamation mark

GHS09: Environmental



**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P302+P352: IF ON SKIN: Wash with plenty of water.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### COPPER (I) OXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-270-7	1317-39-1	-	Acute Tox. 4: H332; Acute Tox. 4: H302; Eye Dam. 1: H318; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	30-50%

##### LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	10-30%
-----------	------------	---	---	--------

##### ROSIN

232-475-7	8050-09-7	-	Skin Sens. 1: H317	1-10%
-----------	-----------	---	--------------------	-------

##### ZINC OXIDE

-	1314-13-2	-	Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%
---	-----------	---	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

[cont...]

# SAFETY DATA SHEET

## PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 3

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

[cont...]

**SAFETY DATA SHEET**  
PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 4

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	100	-	-	-

**Hazardous ingredients:**

**ROSIN**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.05 mg/m <sup>3</sup>	0.15 mg/m <sup>3</sup>	-	-

**ZINC OXIDE**

UK	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	-	-
----	---------------------	----------------------	---	---

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

[cont...]

**SAFETY DATA SHEET**  
PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 5

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Various

**Odour:** Aromatic

**Solubility in water:** Insoluble

**Viscosity:** Non-viscous

**Kinematic viscosity:** 6.0

**Boiling point/range°C:** 200

**Flash point°C:** 42

**Autoflammability°C:** >200

**Relative density:** 1.8

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

[cont...]

**SAFETY DATA SHEET**  
PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 6

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**COPPER (I) OXIDE**

IPR	MUS	LD50	380	mg/kg
ORL	RAT	LD50	470	mg/kg

**LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.**

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

**ZINC OXIDE**

IPR	RAT	LD50	240	mg/kg
ORL	MUS	LD50	7950	mg/kg

**Relevant hazards for product:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

[cont...]

**SAFETY DATA SHEET**  
PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 7

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Use principally as a fuel or other means to generate energy.

**Disposal of packaging:** Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1263

**14.2. UN proper shipping name**

**Shipping name:** PAINT

**14.3. Transport hazard class(es)**

**Transport class:** 3

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** Yes

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 3

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

**SAFETY DATA SHEET**  
PERFORMANCE EXTRA ANTIFOULING PAINT

Page: 8

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.  
H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



