

**DECLARATION OF PERFORMANCE N. CPR-IT1/0146**

- 1) Unique identification code of the product-type: **MAPECOAT I 24**
- 2) Intended uses: **Two-component coating for intended use in concrete surface protection by protection against ingress; moisture control and increasing resistivity; physical resistance; chemical resistance methods**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 2+  
System 3 (for reaction to fire)**
- 5) Harmonized standards: **EN 1504-2:2004**

Notified bodies: **the notified body ICMQ SpA, N. 1305, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.**

**The notified laboratory CSI S.p.A., N. 0497, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:

Essential characteristics	Performances
<b>Abrasion resistance:</b>	<b>&lt; 3000 mg</b>
<b>Permeability to CO<sub>2</sub>:</b>	<b>sD &gt; 50 m</b>
<b>Water vapour permeability:</b>	<b>Class III</b>
<b>Capillary absorption and permeability to water:</b>	<b>&lt; 0,1 kg*m<sup>-2</sup>*h<sup>-0,5</sup></b>
<b>Resistance to thermal shock:</b>	<b>≥ 2,0 N/mm<sup>2</sup></b>
<b>Resistance to severe chemical attack:</b>	<b>reduction in hardness Shore D &lt; 50%</b>
<b>Group 9 {CH<sub>3</sub>COOH (10%)}</b>	<b>Class II (with blistering)</b>
<b>Group 10 {H<sub>2</sub>SO<sub>4</sub> (20%)}</b>	<b>Class II</b>
<b>Group 11 {NaOH (20%)}</b>	<b>Class II</b>
<b>Group 12 {NaCl (20%)}</b>	<b>Class II</b>
<b>Impact resistance:</b>	<b>Class I</b>
<b>Adhesion strength by pull-off test:</b>	<b>≥ 1,5 N/mm<sup>2</sup></b>
<b>Reaction to fire:</b>	<b>Class B<sub>FL</sub>-s1 / C-s1,d0</b>
<b>Dangerous substances:</b>	<b>NPD</b>

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**  
**Milan, 29/01/2018**



.....  
*Paolo Murelli*

*DoP in Pdf format are available in the Mapei website.*

<b>Revision 1 notes:</b>	<i>the performance table has been updated</i>
--------------------------	---

**MAPECOAT I 24**  
**CE MARKING**  
*Annex to DoP N. CPR-IT1/0146*



 1305, 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it																														
<b>09</b> <b>CPR-IT1/0146</b> <b>EN 1504-2</b> <b>MAPECOAT I 24</b> <i>Two-component coating for intended use in concrete surface protection by protection against ingress; moisture control and increasing resistivity; physical resistance; chemical resistance methods</i>																															
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Abrasion resistance:</td> <td style="width: 50%; text-align: right;">&lt; 3000 mg</td> </tr> <tr> <td>Permeability to CO<sub>2</sub>:</td> <td style="text-align: right;">sD &gt; 50 m</td> </tr> <tr> <td>Water vapour permeability:</td> <td style="text-align: right;">Class III</td> </tr> <tr> <td>Capillary absorption and permeability to water:</td> <td style="text-align: right;">&lt; 0,1 kg*m<sup>-2</sup>*h<sup>-0,5</sup></td> </tr> <tr> <td>Resistance to thermal shock:</td> <td style="text-align: right;">≥ 2,0 N/mm<sup>2</sup></td> </tr> <tr> <td>Resistance to severe chemical attack:</td> <td style="text-align: right;">reduction in hardness Shore D &lt; 50%</td> </tr> <tr> <td>Group 9 {CH<sub>3</sub>COOH (10%)}</td> <td style="text-align: right;">Class II (with blistering)</td> </tr> <tr> <td>Group 10 {H<sub>2</sub>SO<sub>4</sub> (20%)}</td> <td style="text-align: right;">Class II</td> </tr> <tr> <td>Group 11 {NaOH (20%)}</td> <td style="text-align: right;">Class II</td> </tr> <tr> <td>Group 12 {NaCl (20%)}</td> <td style="text-align: right;">Class II</td> </tr> <tr> <td> </td> <td></td> </tr> <tr> <td>Impact resistance:</td> <td style="text-align: right;">Class I</td> </tr> <tr> <td>Adhesion strength by pull-off test:</td> <td style="text-align: right;">≥ 1,5 N/mm<sup>2</sup></td> </tr> <tr> <td>Reaction to fire:</td> <td style="text-align: right;">Class B<sub>FL</sub>-s1 / C-s1,d0</td> </tr> <tr> <td>Dangerous substances:</td> <td style="text-align: right;">NPD</td> </tr> </table>		Abrasion resistance:	< 3000 mg	Permeability to CO <sub>2</sub> :	sD > 50 m	Water vapour permeability:	Class III	Capillary absorption and permeability to water:	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>	Resistance to thermal shock:	≥ 2,0 N/mm <sup>2</sup>	Resistance to severe chemical attack:	reduction in hardness Shore D < 50%	Group 9 {CH <sub>3</sub> COOH (10%)}	Class II (with blistering)	Group 10 {H <sub>2</sub> SO <sub>4</sub> (20%)}	Class II	Group 11 {NaOH (20%)}	Class II	Group 12 {NaCl (20%)}	Class II	 		Impact resistance:	Class I	Adhesion strength by pull-off test:	≥ 1,5 N/mm <sup>2</sup>	Reaction to fire:	Class B <sub>FL</sub> -s1 / C-s1,d0	Dangerous substances:	NPD
Abrasion resistance:	< 3000 mg																														
Permeability to CO <sub>2</sub> :	sD > 50 m																														
Water vapour permeability:	Class III																														
Capillary absorption and permeability to water:	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>																														
Resistance to thermal shock:	≥ 2,0 N/mm <sup>2</sup>																														
Resistance to severe chemical attack:	reduction in hardness Shore D < 50%																														
Group 9 {CH <sub>3</sub> COOH (10%)}	Class II (with blistering)																														
Group 10 {H <sub>2</sub> SO <sub>4</sub> (20%)}	Class II																														
Group 11 {NaOH (20%)}	Class II																														
Group 12 {NaCl (20%)}	Class II																														
Impact resistance:	Class I																														
Adhesion strength by pull-off test:	≥ 1,5 N/mm <sup>2</sup>																														
Reaction to fire:	Class B <sub>FL</sub> -s1 / C-s1,d0																														
Dangerous substances:	NPD																														

**Note:**

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.