

DECLARATION OF PERFORMANCE N. CPR-IT1/0487

- 1) Unique identification code of the product-type: **PLASTIMUL**
- 2) Intended uses: **Polymer modified bituminous thick coating (PMBC–W1, CB1, C1) for waterproofing in below ground structures**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 15814 :2011+A2:2014**

Notified bodies: **the notified laboratory Materialprüfungsamt Nordrhein-Westfalen (MPA NRW), N. 0432, carried out the assessment of the performance on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:


Essential characteristics	Performances
Watertightness	Class W1
Crack bridging ability	Class CB1
Water resistance	Pass
Flexibility at low temperature	Pass
Dimensional stability at high temperatures	Pass
Reaction to fire	Class E
Resistance to compression	Class C1
Dangerous substances	NPD
Durability of water tightness and reaction to fire	Pass

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 08/02/2016





DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	Unchanged product, standard reference date updated
--------------------------	---

PLASTIMUL
CE MARKING
Annex to DoP N. CPR-IT1/0487



 0432	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
14 CPR-IT1/0487 EN 15814 PLASTIMUL <i>Polymer modified bituminous thick coating (PMBC–W1, CB1, C1) for waterproofing in below ground structures</i>	
Watertightness Crack bridging ability Water resistance Flexibility at low temperature Dimensional stability at high temperatures Reaction to fire Resistance to compression Dangerous substances Durability of water tightness and reaction to fire	Class W1 Class CB1 Pass Pass Pass Class E Class C1 NPD Pass

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.